

1. 192.168.0.176

http						
No.	Time	Source	Destination	Protocol	Length	Info
110	2.726042	192.168.0.176	128.119.245.12	HTTP	637	GET /wireshark-labs/TCP-wireshark-file1.
117	2.930266	128.119.245.12	192.168.0.176	HTTP	796	HTTP/1.1 200 OK (text/html)

```

> Frame 117: 796 bytes on wire (6368 bits), 796 bytes captured (6368 bits) on interface \Device\NPF_{EB5A1A4B-473C-418}
> Ethernet II, Src: Mercusys_31:88:a0 (00:eb:d8:31:88:a0), Dst: IntelCor_a8:d5:9a (dc:21:5c:a8:d5:9a)
< Internet Protocol Version 4, Src: 128.119.245.12, Dst: 192.168.0.176
  0100 .... = Version: 4

```

2. TCP (6)

http						
No.	Time	Source	Destination	Protocol	Length	Info
110	2.726042	192.168.0.176	128.119.245.12	HTTP	637	GET /wireshark-labs/TCP-wireshark-file1.
117	2.930266	128.119.245.12	192.168.0.176	HTTP	796	HTTP/1.1 200 OK (text/html)

```

> Frame 110: 637 bytes on wire (5096 bits), 637 bytes captured (5096 bits) on interface \Device\NPF_{EB5A1A4B-473C-418}
> Ethernet II, Src: IntelCor_a8:d5:9a (dc:21:5c:a8:d5:9a), Dst: Mercusys_31:88:a0 (00:eb:d8:31:88:a0)
< Internet Protocol Version 4, Src: 192.168.0.176, Dst: 128.119.245.12
  0100 .... = Version: 4
  .... 0101 = Header Length: 20 bytes (5)
  > Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
    Total Length: 623
    Identification: 0x2094 (8340)
  > 010. .... = Flags: 0x2, Don't fragment
    ...0 0000 0000 0000 = Fragment Offset: 0
    Time to Live: 128
    Protocol: TCP (6)
    Header Checksum: 0x0000 [validation disabled]

```

3. 20 bytes, 603 bytes, $623 - 20 = 603$ bytes

http						
No.	Time	Source	Destination	Protocol	Length	Info
110	2.726042	192.168.0.176	128.119.245.12	HTTP	637	GET /wireshark-labs/TCP-wireshark-file1.
117	2.930266	128.119.245.12	192.168.0.176	HTTP	796	HTTP/1.1 200 OK (text/html)

```

> Frame 110: 637 bytes on wire (5096 bits), 637 bytes captured (5096 bits) on interface \Device\NPF_{EB5A1A4B-473C-418:
> Ethernet II, Src: IntelCor_a8:d5:9a (dc:21:5c:a8:d5:9a), Dst: Mercusys_31:88:a0 (00:eb:d8:31:88:a0)
> Internet Protocol Version 4, Src: 192.168.0.176, Dst: 128.119.245.12
  0100 .... = Version: 4
  .... 0101 = Header Length: 20 bytes (5)
> Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
  Total Length: 623
  Identification: 0x2094 (8340)
> 010. .... = Flags: 0x2, Don't fragment
  ...0 0000 0000 0000 = Fragment Offset: 0
  Time to Live: 128
  Protocol: TCP (6)
  Header Checksum: 0x0000 [validation disabled]
  [Header checksum status: Unverified]
  Source Address: 192.168.0.176
  Destination Address: 128.119.245.12

```

4. 0x2094 (8340), 128

No.	Time	Source	Destination	Protocol	Length	Info
110	2.726042	192.168.0.176	128.119.245.12	HTTP	637	GET /wireshark-labs/TCP-wireshark-file1.
117	2.930266	128.119.245.12	192.168.0.176	HTTP	796	HTTP/1.1 200 OK (text/html)

```

> Frame 110: 637 bytes on wire (5096 bits), 637 bytes captured (5096 bits) on interface \Device\NPF_{EB5A1A4B-473C-418:
> Ethernet II, Src: IntelCor_a8:d5:9a (dc:21:5c:a8:d5:9a), Dst: Mercusys_31:88:a0 (00:eb:d8:31:88:a0)
> Internet Protocol Version 4, Src: 192.168.0.176, Dst: 128.119.245.12
  0100 .... = Version: 4
  .... 0101 = Header Length: 20 bytes (5)
> Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
  Total Length: 623
  Identification: 0x2094 (8340)
> 010. .... = Flags: 0x2, Don't fragment
  ...0 0000 0000 0000 = Fragment Offset: 0
  Time to Live: 128
  Protocol: TCP (6)
  Header Checksum: 0x0000 [validation disabled]
  [Header checksum status: Unverified]
  Source Address: 192.168.0.176
  Destination Address: 128.119.245.12

```