

Swinburne University of Technology*School of Science, Computing and Engineering Technologies***ASSIGNMENT COVER SHEET**

Subject Code: COS30008
Subject Title: Data Structures and Patterns
Assignment number and title: 1, Solution Design in C++
Due date: Wednesday, March 27, 2024, 23:59
Lecturer: Dr. Markus Lumpe

Your name: _____ **Your student ID:** _____

Marker's comments:

Problem	Marks	Obtained
1	26	
2	98	
3	32	
Total	156	

Extension certification:

This assignment has been given an extension and is now due on _____

Signature of Convener: _____

```
1 // Vector3D_PS1.cpp
2 // Created by NUR E SIAM
3
4 #include "Vector3D.h"
5 #include <sstream>
6
7 std::string Vector3D::toString() const noexcept {
8     // Create a stringstream to build the output string
9     std::stringstream stream;
10
11     // Format x, y, and w components with 4 decimal places and add to the stream
12     stream << "[" << std::round(x() * 10000.0f) / 10000.0f << ", "
13         << std::round(y() * 10000.0f) / 10000.0f << ", "
14         << std::round(w() * 10000.0f) / 10000.0f << "];"
15
16     // Extract the formatted string from the stringstream
17     std::string output = stream.str();
18
19     // Return the formatted string representation of the vector
20     return output;
21 }
22
```

```
1 // Matrix3x3_PS1.cpp
2 // Created By NUR E SIAM
3
4 #include "Matrix3x3.h"
5 #include <iostream>
6
7 // Matrix multiplication implementation
8 Matrix3x3 Matrix3x3::operator*(const Matrix3x3& aOther) const noexcept {
9     // Calculate the product of two matrices without using loops
10    // Each entry in the resulting matrix is the dot product of a row from
11    // the first matrix
12    // and a column from the second matrix
13
14    // Calculate the dot products for each entry of the resulting matrix
15    float result00 = row(0).dot(aOther.column(0));
16    float result01 = row(0).dot(aOther.column(1));
17    float result02 = row(0).dot(aOther.column(2));
18
19    float result10 = row(1).dot(aOther.column(0));
20    float result11 = row(1).dot(aOther.column(1));
21    float result12 = row(1).dot(aOther.column(2));
22
23    float result20 = row(2).dot(aOther.column(0));
24    float result21 = row(2).dot(aOther.column(1));
25    float result22 = row(2).dot(aOther.column(2));
26
27    // Create a new matrix with the calculated entries
28    Matrix3x3 result(Vector3D(result00, result01, result02),
29                    Vector3D(result10, result11, result12),
30                    Vector3D(result20, result21, result22));
31
32    return result;
33 }
34
35 // Determinant calculation implementation
36 float Matrix3x3::det() const noexcept {
37     float a = fRows[0][0], b = fRows[0][1], c = fRows[0][2];
38     float d = fRows[1][0], e = fRows[1][1], f = fRows[1][2];
39     float g = fRows[2][0], h = fRows[2][1], i = fRows[2][2];
40     return a * (e * i - f * h) - b * (d * i - f * g) + c * (d * h - e * g);
41 }
42
43 // Check if the matrix has an inverse
44 bool Matrix3x3::hasInverse() const noexcept {
45     return det() != 0.0f;
46 }
47
48 Matrix3x3 Matrix3x3::transpose() const noexcept {
49     Matrix3x3 result(Vector3D(fRows[0][0], fRows[1][0], fRows[2][0]),
```

```
49     Vector3D(fRows[0][1], fRows[1][1], fRows[2][1]),
50     Vector3D(fRows[0][2], fRows[1][2], fRows[2][2]));
51     return result;
52 }
53
54 Matrix3x3 Matrix3x3::inverse() const noexcept {
55     if (det() == 0) {
56         throw std::runtime_error("Inverse does not exist.");
57     }
58     float result00 = fRows[1][1] * fRows[2][2] - fRows[1][2] * fRows[2][1];
59     float result01 = fRows[0][2] * fRows[2][1] - fRows[0][1] * fRows[2][2];
60     float result02 = fRows[0][1] * fRows[1][2] - fRows[0][2] * fRows[1][1];
61
62     float result10 = fRows[1][2] * fRows[2][0] - fRows[1][0] * fRows[2][2];
63     float result11 = fRows[0][0] * fRows[2][2] - fRows[0][2] * fRows[2][0];
64     float result12 = fRows[0][2] * fRows[1][0] - fRows[0][0] * fRows[1][2];
65
66     float result20 = fRows[1][0] * fRows[2][1] - fRows[1][1] * fRows[2][0];
67     float result21 = fRows[0][1] * fRows[2][1] - fRows[0][0] * fRows[2][1];
68     float result22 = fRows[0][0] * fRows[1][1] - fRows[0][1] * fRows[1][0];
69
70     Matrix3x3 mult(Vector3D(result00, result01, result02),
71         Vector3D(result10, result11, result12),
72         Vector3D(result20, result21, result22));
73
74     Matrix3x3 output = mult * (1 / det());
75     return output;
76 }
77
78
79 std::ostream& operator<<(std::ostream& os, const Matrix3x3& matrix) {
80     // Output each row of the matrix
81     os << "[";
82     for (int i = 0; i < 3; ++i) {
83         os << matrix.fRows[i].toString();
84         if (i < 2) {
85             os << ",";
86         }
87     }
88     os << "];";
89     return os;
90 }
```

```
1 //Polygon_PS1.cpp
2
3 // Created by NUR E SIAM
4
5 #include "Polygon.h"
6 #include <cmath>
7
8
9 float Polygon::getSignedArea() const noexcept {
10     // Calculates the signed area of the polygon using the shoelace formula
11     float larea = 0.0f;
12
13     for (size_t lIndex = 0; lIndex < fNumberOfVertices; ++lIndex) {
14         size_t j = (lIndex == fNumberOfVertices - 1) ? 0 : lIndex + 1; // ↗
15         // Wrap around for closing edge
16
17         larea += fVertices[lIndex].x() * fVertices[j].y() -
18             fVertices[j].x() * fVertices[lIndex].y();
19     }
20     return larea / 2.0f;
21 }
22
23 Polygon Polygon::transform(const Matrix3x3& aMatrix) const noexcept {
24     // Creates a new polygon by applying the given transformation matrix to ↗
25     // each vertex
26     Polygon ltransformed;
27     ltransformed.fNumberOfVertices = fNumberOfVertices;
28
29     size_t lIndex = 0;
30     size_t rIndex = fNumberOfVertices - 1; // Start from opposite ends
31
32     while (lIndex <= rIndex) {
33         // Transform vertices from left to right
34         Vector3D vertex = aMatrix * Vector3D(fVertices[lIndex].x(), ↗
35             fVertices[lIndex].y(), 1.0f);
36         ltransformed.fVertices[lIndex] = Vector2D(vertex.x(), vertex.y());
37
38         // Transform vertices from right to left (for potential efficiency)
39         vertex = aMatrix * Vector3D(fVertices[rIndex].x(), fVertices ↗
40             [rIndex].y(), 1.0f);
41         ltransformed.fVertices[rIndex] = Vector2D(vertex.x(), vertex.y());
42
43         lIndex++;
44         rIndex--;
45     }
46
47     return ltransformed;
48 }
```