MOSAIC-Med: Multiplicity and Architectural Diversity Outperform Monolithic Scale in Resource-Constrained Electrocardiogram Diagnosis

Sibgha Faisal
Dept. of Biomedical Engineering
Riphah International University
Lahore, Pakistan
sibghafaisal88@gmail.com

Hamna Tanveer
Dept. of Artificial Intelligence
Univ. of Management and Technology
Sialkot, Pakistan
hamnaaa281@gmail.com

Mahad Aftab
Dept. of Biomedical Engineering
Univ. of Engineering and Technology
Lahore, Pakistan
Mahadaftab680@gmail.com

Fatima-Tu-Zahra[†]
Dept. of Biomedical Engineering
Riphah International University
Lahore, Pakistan
Fatima.zahra@riphah.edu.pk

Abstract—Deep neural networks for physiological signal classification predominantly rely on monolithic parameter scaling, which incurs high computational latency and uncalibrated overconfidence under clinical noise. In resource-constrained 12-lead electrocardiogram (ECG) multi-label diagnosis across 21,799 PTB-XL records, this study investigates distributing an invariant ∼2.0M parameter budget among compact specialized networks (MOSAIC-Med). The multiplicity hypothesis (H1) is validated: split architectures ($K = 2$: AUROC 0.9085 ± 0.0007; $K = 4$: 0.9084 ± 0.0008) statistically surpass the monolithic baseline ($K = 1$: 0.9059 ± 0.0010, DeLong $p = 3.63 \times 10^{-4}$). However, extreme over-fragmentation at $K = 16$ degrades AUROC to 0.9048 and triples latency. Architectural diversity (H2) yields a consistent descriptive improvement trend (0.9110 ± 0.0006; Holm $p = 0.058$) with lower CKA similarity (0.9008 vs 0.9458), but is not statistically significant at $\alpha = 0.05$. Learned Top-2 sparse routing (H3) achieves diagnostic parity (0.9113) while reducing computation by 28.2% relative to dense ensembling (297.8 vs 414.9 MFLOPs). Selective abstention (H4) on the 10% most uncertain records achieves a 4.18% relative risk reduction ($p = 0.0093$). Factorial ablation confirms diversity regularization prevents router collapse (0.9088 vs 0.9049).

Keywords—Electrocardiography, model splitting, mixture of experts, centered kernel alignment, selective classification, clinical robustness.

I. Introduction

In clinical artificial intelligence, foundational research established deep ensembling as an effective paradigm for reliable predictive uncertainty estimation [1]. Parallel foundational developments in safety-critical classification introduced selective prediction frameworks with integrated reject options, formalizing mechanisms for deep neural networks to abstain on ambiguous instances [2]. At the same time, representational similarity metrics like Centered Kernel Alignment (CKA) facilitated the quantitative assessment of hidden layer representations across the different families of neural networks [3]. The availability of large clinical repositories like PTB-XL [4] spurred systematic benchmarking of typical 12-lead electrocardiography (ECG) across deep architectures in cardiovascular medicine [5].

Despite these groundworks, key challenges related to the deployment of real-world clinical AI were brought to the fore in the literature during 2024. Black et al. [6] showed predictive multiplicity in clinical machine learning models: that several networks with the same overall discrimination exhibit conflicting predictions for high-risk patients. Forestier et al. [7] showed that feature orthogonality and the negative correlation between sub-networks improves generalizability in time-series ensembles to avoid correlated failure modes. For hospital deployment workflows, Kompa et al. [8] developed second opinion workflows, which showed that uncertainty-directed triage to human cardiologists significantly reduces diagnostic risk. However, monolithic scaling continued to be the main paradigm, including foundation models, like the ECGFounder which is pre-trained on 10 million recordings [9]. Scale is, however, costly in terms of computational overheads or latency in the case of edge hardware, thus prompting research into split learning and parameter partitioning for decentralized clinical edge inferences [10].

In 2025, investigations went into resource allocation, diversity formulations, and clinical escalation protocols. Argha et al. [11] proposed selective classification and dynamic clinician escalation for 12-lead ECG which was successfully validated, where they showed that avoiding the action of 'abstain' on borderline tracings avoids catastrophic false positives. To tackle the extreme compute demands, Chen et al. [12] proposed parameter budget allocation and ensemble pruning, demonstrating that the unconstrained model stacking approach is impractical for bedside and wearable monitors. A method to mitigate rigid foundation footprints is to use EnECG [13] that integrates foundation backbone, parameter-efficient adapters, and learned gating. At the same time, theoretical studies by Zhou et al. [14] derived diversity decompositions for collaborative ensembles, demonstrating sub-additive error scaling of combining different kinds of inductive biases. In the context of realistic sensor distortion, the 2026 frontier in physiological time-series AI has landed on adaptive routing and mixture-of-experts (MoE) formulations. Han et al. [15] proposed CogMoE, which showed the maintenance of diagnostic fidelity in the presence of acute physiological noise, by enabling quality-aware gating. Mert et al. [16] compared five deep architectures through the analysis of a comprehensive PTB-XL benchmark, and found

[†] Supervisor.

979-8-3195-2818-6/26/$31.00 ©2026 IEEE

TABLE I. Cohort Demographics and Diagnostic Prevalence on PTB-XL

Split Partition	Records	Patients	Age (SD)	Female (%)
Training (Folds 1–8)	17,411	15,082	59.8 ± 16.9	48.1%
Validation (Fold 9)	2,183	1,894	59.7 ± 17.0	47.9%
Test (Fold 10)	2,205	1,893	59.9 ± 16.7	48.0%
Diagnostic Superclass	**Train (%)**	**Val (%)**	**Test (%)**	**Clinical Category**
NORM (Normal ECG)	43.7%	43.6%	43.7%	Unremarkable 12-lead tracing
MI (Myocardial Infarction)	25.1%	25.1%	25.0%	Ischemia / Infarction necrosis
STTC (ST/T Changes)	24.3%	24.2%	24.4%	Repolarization anomaly
CD (Conduction Defect)	22.5%	22.4%	22.5%	Bundle branch / AV blocks
HYP (Hypertrophy)	12.2%	12.1%	12.2%	Ventricular/Atrial enlargement

that heterogeneous ensembles consistently outperform the individual foundation networks. At the same time, Wang et al. [17] introduced domain-expert-guided routing to handle the sensor lead dropouts; Xu et al. [18] presented a new technique named ECG-MoE, separating morphology features from rhythm periodicity.

However, while these are noteworthy progress, current medical MoE and ensemble methods have two major shortcomings: they increase the capacity of the aggregate parameters without considering multi-model multiplicity under a tightly constrained parameter budget ceiling, and they mostly replicate homogeneous backbones without considering orthogonal inductive biases [14].

In this study, we impose the invariant ∼2.0M parameter budget ceiling, and test if the small-model multiplicity can outperform the scale of monolithic models.

There are four contributions:

(1) **Fixed-Budget Multiplicity**: where $K \in \{1, 2, 4, 8, 16\}$ experts with an invariant budget of 2.0M to prove Capacity over-fragmentation boundary (validating Hypothesis 1: Multiplicity Superiority).

(2) **Inductive Bias Diversity**: A parameter-matched comparison (+0.92%) between homogeneous (4×ResNet) and heterogeneous (ResNet, MultiScale, TCN, Attention) experts quantified with linear CKA [3], which shows a consistent improvement trend (adjusted p = 0.058) for Hypothesis 2: Diversity Benefit.

(3) **Sparse Adaptive Routing**: A lightweight patient-specific router regularized with the diversity entropy and failure penalties, with dynamic Top-2 routing and reduced inference FLOPs by 28.2% (empowering Hypothesis 3: Routing Efficiency).

(4) **Clinical Robustness & Selective Abstention**: Systematic validation across five clinical stress tests and an uncertainty-triggered deferral protocol that yielded monotonic risk reduction [8], [11] (validating Hypothesis 4: Risk Reduction).

II. Methodology

A. Benchmark Dataset and Clinical Cohort

Empirical evaluation is conducted on the PTB-XL dataset [4], [5], a clinical ECG repository containing 21,799 records from 18,869 distinct patients. Each recording comprises 10-second standard 12-lead signals digitized at 100 Hz ($L = 1000$ samples per lead) alongside clinical diagnostic statements mapped to the SCP-ECG standard [5].

As documented in Table I and illustrated in Boxes 1–5 of Fig. 1, records are partitioned using the official patient-stratified 10-fold split: Folds 1–8 for training, Fold 9 for validation, and Fold 10 strictly held out for final testing, guaranteeing zero patient identity leakage [5]. Diagnostic classification is framed as multi-label binary prediction across five clinical superclasses: Normal ECG (NORM), Myocardial Infarction (MI), ST/T Changes (STTC), Conduction Defect (CD), and Hypertrophy (HYP). Let $x \in \mathbb{R}^{C\times L}$ denote an input 12-lead recording ($C = 12, L = 1000$), and let $y \in \{0, 1\}^M$ denote the binary target vector for $M = 5$ superclasses. All signals are standardized instance-by-instance across time ($L = 1000$) independently per lead: $x'_c(t) = (x_c(t) - \mu_c)/\max(\sigma_c, 10^{-6})$, with extreme values clipped to $[-10.0, 10.0]$. Because normalization statistics are computed strictly on individual 10-second recordings, zero dataset-level training distribution statistics are used during inference.

B. Multiplicity and Architectural Diversity

In standard monolithic deep learning, a single neural network $f_\Theta(x)$ maps $x \to \hat{y} \in [0, 1]^M$, subject to $|\Theta| \le B$. In the proposed multiplicity framework (Box 6 of Fig. 1), this fixed capacity quota $B \approx 2.0 \times 10^6$ parameters is partitioned among K distinct sub-networks $\{f_{\theta_k}\}_{k=1}^K$ such that:

$$\sum_{k=1}^{K} |\theta_k| \le B \approx 2.0 \times 10^6 \quad \text{parameters.} \tag{1}$$

For homogeneous capacity scaling, each sub-network f_{θ_k} is instantiated as a 1D Residual Network (ResNet-1D) with target capacity $|\theta_k| \approx \frac{B}{K}$. Base convolution filter widths W_K enforce the nominal 2.0×10^6 budget within a formal ±3.0% tolerance envelope ($[1.94\text{M}, 2.06\text{M}]$): $K = 1$ ($W_1 = 65$, 2,019,945 params, +1.00%), $K = 2$ ($W_2 = 46$, 2,030,450 params, +1.52%), $K = 4$ ($W_4 = 32$, 1,975,572 params, −1.22%), $K = 8$ ($W_8 = 23$, 2,054,952 params, +2.75%), and $K = 16$ ($W_{16} = 16$, 2,009,680 params, +0.48%).

To evaluate whether combining orthogonal inductive biases surpasses homogeneous replication, a 4-expert parameter-matched heterogeneous arm (Boxes 7–8 in Fig. 1) ensembles four distinct paradigms calibrated to ∼ 500K parameters: (i) **ResNet-1D** (493,893 params, 3 residual stages, kernels 7, 5, 3); (ii) **MultiScale-CNN** (508,909 params, parallel kernels 3, 7, 15, 31); (iii) **TCN-1D** (490,661 params, dilated causal convolutions $d \in \{1, 2, 4, 8\}$); and (iv) **ConvAttention-1D** (500,225 params, conv stem downsampling 4×, 2-layer Transformer, $d_{\text{model}} = 140$, 4 heads). The aggregate capacity is $1,993,688$ parameters, matching the homogeneous 4xResNet arm ($1,975,572$) within a +0.92% margin.

To empirically verify representational diversity, Centered Kernel Alignment (CKA) [3] is evaluated on penultimate feature activations over the held-out test cohort ($N = 2,198$). For centered activation matrices $X \in \mathbb{R}^{N\times D_1}, Y \in \mathbb{R}^{N\times D_2}$, linear CKA is:

$$\text{CKA}(X, Y) = \frac{\|Y^T X\|_F^2}{\|X^T X\|_F \|Y^T Y\|_F}. \tag{2}$$



Fig. 1. Comprehensive methodological flowchart of MOSAIC-Med detailing the fifteen core processing steps across data cohort partitioning (Boxes 1–5), fixed-budget capacity allocation and heterogeneous expert synthesis (Boxes 6–10), composite objective optimization (Box 11), and selective inference with clinical abstention (Boxes 12–15).

TABLE II. Fixed-Budget Multiplicity Performance Across 5 Seeds (Mean ± SD) within ±3.0% Parameter Budget on Held-Out PTB-XL Test Set ($N = 2,198$)

Configuration	Total Parameters	MFLOPs	Macro AUROC	Macro AUPRC	Brier Score	Latency (ms)
Single Large ($K = 1$)	2,019,945	123.9	0.9059 ± 0.0010	0.7663 ± 0.0025	0.0900 ± 0.0007	**1.99 ± 0.05**
Split-2 ($K = 2$)	2,030,450	126.9	**0.9085 ± 0.0007**	**0.7714 ± 0.0012**	0.0883 ± 0.0004	2.20 ± 0.00
Split-4 ($K = 4$)	1,975,572	126.8	0.9084 ± 0.0008	0.7711 ± 0.0010	**0.0881 ± 0.0002**	2.25 ± 0.01
Split-8 ($K = 8$)	2,054,952	136.2	0.9061 ± 0.0009	0.7667 ± 0.0013	0.0890 ± 0.0004	4.40 ± 0.02
Split-16 ($K = 16$)	2,009,680	139.8	0.9048 ± 0.0005	0.7643 ± 0.0011	0.0896 ± 0.0003	6.78 ± 0.03

C. Dynamic Gating and Routing Optimization

To dynamically dispatch experts without evaluating every waveform (Boxes 9–10 in Fig. 1), a lightweight Adaptive Router $g_\phi(x)$ (16,132 parameters, 1.19 MFLOPs) maps 12-lead inputs to patient-specific gating weights $w(x) \in \Delta^{K-1}$:

$$w(x) = \text{Softmax}\left(W_2 \cdot \text{ReLU}(W_1 \cdot \text{Pool}(\text{Conv1D}(x)))\right). \quad (3)$$

The router brings the total routed heterogeneous architecture to $2,009,820$ parameters $(1,993,688 + 16,132)$, which remains strictly within a +0.49% margin of the nominal 2.0M budget. In sparse Top-2 inference, gating weights are renormalized over the two highest-scoring experts:

$$\tilde{w}_k(x) = \begin{cases} \dfrac{w_k(x)}{\sum_{j \in \text{Top2}(w(x))} w_j(x)} & \text{if } k \in \text{Top2}(w(x)), \\ 0 & \text{otherwise.} \end{cases} \quad (4)$$

Predictions are $\hat{z}(x) = \sum_{k=1}^{K} \tilde{w}_k(x) z_k(x)$, and $\hat{y}_m(x) = \sigma(\hat{z}_m(x))$. The router optimizes composite loss (Box 11 of Fig. 1):

$$\mathcal{L}_{\text{total}} = \mathcal{L}_{\text{diag}} + \lambda_{\text{div}} \mathcal{L}_{\text{div}} + \lambda_{\text{fail}} \mathcal{L}_{\text{fail}}, \quad (5)$$

where $\mathcal{L}_{\text{diag}}$ is BCE, $\mathcal{L}_{\text{div}} = -\mathcal{H}(\bar{w})$ prevents expert collapse by maximizing mean gating entropy, and $\mathcal{L}_{\text{fail}} = \sum_k w_k(x) \mathcal{L}_{\text{BCE}}(f_{\theta_k}(x), y)$ penalizes routing toward inaccurate sub-networks ($\lambda_{\text{div}} = 0.05, \lambda_{\text{fail}} = 0.10$).

D. Uncertainty Estimation and Selective Classification

In clinical deployment (Boxes 12–15 of Fig. 1), automated models must signal low confidence on ambiguous tracings [8]. Predictive uncertainty $U(x)$ combines binary predictive entropy and epistemic ensemble disagreement [1]:

$$U(x) = \sum_{m=1}^{M} \mathcal{H}(\hat{y}_m(x)) + \alpha \cdot \sum_{m=1}^{M} \frac{1}{K} \sum_{k=1}^{K} (\sigma(z_{k,m}(x)) - \hat{y}_m(x))^2, \quad (6)$$

where the first term represents multi-label binary predictive entropy (aleatoric uncertainty), and the second term measures ensemble variance across expert predictions (epistemic disagreement). The scaling coefficient $\alpha = 2.0$ was selected on Validation Fold 9 to minimize the Area Under the Risk-Coverage Curve (AURC), and deferral thresholds for coverage levels $c \in \{0.80, 0.85, 0.90, 0.95\}$ were fitted on Fold 9 quantiles before applying to held-out test data. Under selective classification with coverage $c \in (0, 1]$, the model classifies the fraction c with lowest uncertainty $U(x)$ and abstains on the remaining $1 - c$ fraction [2]. Diagnostic error on the retained cohort $\mathcal{S}_c$ is measured via multi-label Hamming risk:

$$\text{Risk}(c) = \frac{1}{|\mathcal{S}_c| \cdot M} \sum_{i \in \mathcal{S}_c} \sum_{m=1}^{M} \mathbb{I}\left(\mathbb{I}(\hat{y}_{i,m} \geq 0.5) \neq y_{i,m}\right). \quad (7)$$

III. Experimental Results

A. Fixed-Budget Multiplicity Scaling ($K = 1$ to $K = 16$)

Table II and Fig. 2 summarize empirical scaling trade-offs as the invariant 2.0M parameter budget is partitioned across $K \in \{1, 2, 4, 8, 16\}$ experts over five independent seeds (42–46).

As revealed in Table II and plotted in Fig. 2, partitioning the fixed 2.0M parameter quota into $K = 2$ (0.9085 ± 0.0007) and $K = 4$ (0.9084 ± 0.0009) sub-networks achieves statistically significant improvements over the monolithic $K = 1$ architecture (0.9059 ± 0.0010, DeLong test $p = 3.63 \times 10^{-4}$,




Fig. 2. Multiplicity scaling trade-off across $K \in \{1, 2, 4, 8, 16\}$ sub-networks under an invariant 2.0M parameter budget. Solid curves show Macro AUROC (blue) and Macro AUPRC (teal) on the left axis; dashed curve shows probability calibration Brier score (purple, lower is better) on the right axis.

TABLE III. Parameter-Matched Control (5 Seeds)

Metric	Homo (4×ResNet)	Hetero Matched	Δ	Adj. p
Macro AUROC	0.9084 ± 0.0008	**0.9110 ± 0.0006**	+0.0026	0.0577
Macro AUPRC	0.7711 ± 0.0010	**0.7759 ± 0.0015**	+0.0048	0.0577
Brier Score	0.0881 ± 0.0002	**0.0867 ± 0.0005**	-0.0014	0.0577
ECE	0.0195 ± 0.0017	**0.0171 ± 0.0022**	-0.0024	0.0664

Holm-adjusted $p = 1.09 \times 10^{-3}$). Probability calibration follows an identical beneficial trend: Brier score drops from 0.0900 for Single Large to 0.0881 for $K = 4$, representing a marked reduction in probability estimation error.

The underlying mathematical mechanism driving this gain is ensemble variance reduction under fixed aggregate compute: intermediate capacity splitting ($K = 2, 4$) reduces idiosyncratic estimation error across diverse patient morphologies without reducing individual network capacity below the minimum threshold required to extract morphological 12-lead features. However, scaling to $K = 16$ triggers an acute capacity over-fragmentation boundary. When the 2.0M budget is divided among 16 sub-networks, individual models receive only $\sim$ 125K parameters ($W_{16} = 16$). At this impoverished capacity, individual networks lack the receptive field depth and spatial filter diversity needed to resolve subtle ST-elevation or multi-lead QRS changes. This results in the individual sub-networks' feature quality eroded and lowers the AUROC of the ensemble to 0.9048 ± 0.0005 (which falls below that of the monolithic baseline) and sequential latency of the ensemble is tripled to 6.78 ms.

B. Parameter-Matched Control and Inductive Bias Diversity

To compare the performance of the homogeneous 4×ResNet arm (1,975,572 parameters) with the parameter-matched heterogeneous arm (1,993,688 parameters, +0.92% delta), across five seeds, see Table III. The heterogeneous arm has better discrimination (AUROC 0.9110 vs 0.9084) and better probability calibration (Brier score 0.0867 vs 0.0881, ECE 0.0171 vs 0.0195).

The physical cause of this performance disparity is representational diversity. The four homogeneous arms in the Replica Set consists of very similar replicas, as evidenced by the high feature redundancy between them, with an off-diagonal mean Linear CKA of 0.9458. All four sub-networks have identical receptive fields and residual connectivity, leading to nearly collinear feature subspaces, and correlated failure modes.

The heterogeneous arm on the other hand uses a different set of architectural inductive biases, reducing the mean pairwise CKA to 0.9008. MultiScale-CNN and ConvAttention-1D achieve the lowest representational similarity with each other (CKA = 0.8824). The functional orthogonality suggests the different types of feature extraction mechanisms: MultiScale-CNN: extracts localized multi-frequency wavelet features at parallel kernel sizes (3, 15, 31 samples); ConvAttention-1D: models long-range rhythm periodicity and cross-beat dependencies through global self-attention heads.

These non-redundant feature representations are combined by ensembling so that the heterogenous ensemble is able to reduce uncorrelated errors of individual networks to obtain more reliable diagnosis under an invariant parameter footprint.

TABLE IV. Adaptive Routing Strategy Comparison (5 Seeds)

Routing Mode	Active	MFLOPs	Macro AUROC	AUPRC
Single Large (1×2M)	1.0	123.9	0.9059 ± 0.0010	0.7663 ± 0.0025
Uniform Average	4.0	413.7	0.9110 ± 0.0006	0.7759 ± 0.0015
Dense Learned Router	4.0	414.9	**0.9118 ± 0.0004**	**0.7761 ± 0.0012**
Sparse Top-2 Escalation	**2.0**	**297.8**	0.9113 ± 0.0008	0.7753 ± 0.0013

C. Adaptive Routing and Computational Efficiency

The details of computational complexity and predictive accuracy for the different routing paradigms are summarized in Table IV. Simple uniform averaging over the heterogeneous arm yields AUROC 0.9110 ± 0.0006, superior to SingleLarge (AUROC = 0.9059, Holm $p = 5.27 \times 10^{-5}$).

The dense learned Adaptive Router (16K parameters) performs at peak absolute discrimination (0.9118 ± 0.0004, Holm $p = 5.27 \times 10^{-5}$) at 414.9 MFLOPs. Importantly, the proposed Sparse Top-2 Router still maintains this discrimination (0.9113 ± 0.0008, Holm $p = 5.07 \times 10^{-5}$) but with just two experts being executed per patient tracing, which reduces inference compute to 297.8 MFLOPs (down 28.2% from dense routing).

The router specializes in medically informed cardiac pathologies: For Conduction Defects (CD) and Hypertrophy (HYP), the majority of the router sends the TCN-1D and MultiScale-CNN ($w_k > 0.30$), which use dilated convolutions to assess the PR interval, bundle branch blocks and the ventricular voltage criteria, respectively.

On the other hand, ResNet-1D and ConvAttention-1D have dominant gating weights ($w_k > 0.28$) thanks to their particular focus on localized ST-segment elevations and multi-lead reciprocal depression in the case of MI and ST/T changes (STTC). Two lowest-relevance models are dynamically removed for each patient, without loss of diagnostic information, and without unnecessary computation. Parameter budgets are matched within ±3.0% across arms, but inference compute is not: the Top-2 router uses 297.8




Fig. 3. Diagnostic retention under real-world clinical corruptions and site domain shift across five seeds (mean ± SD). Staggered percentage annotations indicate macro AUROC retention relative to clean baseline without text collision.




Fig. 4. Selective classification multi-label Hamming risk as a function of cohort coverage retention ($c \in [80\%, 100\%]$). Deferring the 10% most ambiguous records ($c = 90\%$) achieves a statistically significant 4.18% relative risk reduction.

TABLE V. Robustness Stress Testing Across 5 Seeds

Clinical Degradation	Single Large	MOSAIC-Med	Δ	Holm p
Clean Test Baseline	0.9059 ± 0.0010	**0.9113 ± 0.0008**	+0.0054	8.44×10^{-5}
EMG Noise ($\sigma = 0.15$)	0.8872 ± 0.0014	**0.8938 ± 0.0012**	+0.0066	1.23×10^{-4}
Baseline Wander	0.8998 ± 0.0012	**0.9042 ± 0.0015**	+0.0044	4.63×10^{-3}
Precordial Loss (V1–V3)	0.8710 ± 0.0018	**0.8791 ± 0.0016**	+0.0081	8.82×10^{-4}
Limb Loss (I–III)	0.8841 ± 0.0015	**0.8920 ± 0.0014**	+0.0079	8.82×10^{-4}
Held-Out Site ($s \neq 0$)	0.8984 ± 0.0011	**0.9049 ± 0.0009**	+0.0065	$\mathbf{3.72 \times 10^{-5}}$

MFLOPs (latency 3.42±0.08 ms on NVIDIA Quadro T1000) versus 123.9 MFLOPs (1.99 ± 0.05 ms) for the monolithic baseline. Sparse routing saves 28.2% compute relative to dense heterogeneous ensembling (414.9 MFLOPs), while requiring 2.40× the compute of the monolithic baseline.

D. Clinical Robustness Under Degradation and Domain Shift

Table V and Fig. 3 report diagnostic retention across five pre-specified clinical stress tests and domain shift across all five random seeds. Corruptions are mathematically formalized based on clinical standards [5]: (i) High-frequency EMG noise: $X_{\text{EMG}} = X + \epsilon$, $\epsilon \sim \mathcal{N}(0, \sigma^2)$, $\sigma = 0.15$; (ii) Low-frequency baseline wander: $X_{\text{drift}}[c,t] = X[c,t] + A\sin(2\pi f \frac{t}{f_s} + \phi_c)$, $A = 0.50$, $f = 0.20$ Hz, $f_s = 100$ Hz, $\phi_c \sim \mathcal{U}(0, 2\pi)$ per lead; (iii) Precordial lead disconnection: leads V1–V3 zeroed ($c \in \{6,7,8\}$); (iv) Limb lead disconnection: leads I–III zeroed ($c \in \{0,1,2\}$); and (v) Held-out acquisition site shift ($s \neq 0$) evaluated on test records from secondary recording hardware.

Across all stress conditions in Table V and Fig. 3, MOSAIC-Med retains significantly higher performance than the monolithic baseline. Under precordial lead dropout (V1–V3 missing), Single Large drops precipitously to AUROC 0.8710, whereas MOSAIC-Med retains 0.8791 (Δ = +0.0081, Holm $p = 8.82 \times 10^{-4}$). In clinical electrocardiography, leads V1–V3 provide the primary vector view of the anterior and septal myocardium; losing them blinds monolithic models to acute anteroseptal MI. In contrast, MOSAIC-Med's diverse sub-networks extract compensatory morphological signatures from remaining limb and lateral leads. Furthermore, under acquisition site shift ($s \neq 0$),

TABLE VI. Selective Classification Multi-Label Risk (5 Seeds)

Coverage (c)	Single Large	MOSAIC-Med	Risk Red.	Holm p
100% (Full Cohort)	12.37% ± 0.14%	**11.95% ± 0.11%**	3.40% ± 1.30%	3.51×10^{-3}
95% (5% Deferral)	11.53% ± 0.15%	**11.08% ± 0.16%**	3.94% ± 1.90%	3.78×10^{-3}
90% (10% Deferral)	10.83% ± 0.19%	**10.37% ± 0.16%**	**4.18% ± 2.02%**	$\mathbf{9.34 \times 10^{-3}}$
85% (15% Deferral)	10.12% ± 0.18%	**9.76% ± 0.22%**	3.59% ± 2.66%	1.31×10^{-2}
80% (20% Deferral)	9.45% ± 0.18%	**9.10% ± 0.16%**	3.72% ± 1.98%	1.31×10^{-2}

MOSAIC-Med achieves AUROC 0.9049 ± 0.0009 compared to 0.8984 ± 0.0011 ($p = 3.72 \times 10^{-5}$), demonstrating preliminary internal transferability against hardware-specific domain shift.

E. Selective Classification and Clinical Abstention

Table VI and Fig. 4 evaluate multi-label diagnostic risk as ambiguous cases are deferred based on predictive uncertainty $U(x)$.

As shown in Table VI and plotted in Fig. 4, diagnostic Hamming risk drops monotonically as coverage is reduced. Across the entire cohort ($c = 100\%$), MOSAIC-Med achieves 11.95% Hamming risk compared to 12.37% for Single Large. When the 10% most ambiguous tracings are deferred to clinical review ($c = 90\%$), MOSAIC-Med Hamming risk drops to 10.37%, yielding an empirical **4.18% relative risk reduction relative to the single large model at 90% coverage** ($p = 9.34 \times 10^{-3}$). The risk-coverage trajectory in Fig. 4 confirms that combining multi-label predictive entropy with epistemic ensemble disagreement yields well-ordered uncertainty estimates, selectively isolating borderline tracings without forfeiting coverage on clear-cut cases.

F. Loss-Term Regularization Ablation

Table VII presents the factorial ablation of router regularization across three seeds on frozen experts with cached logits.

Diversity entropy regularization ($\mathcal{L}_{\text{div}}$) recovers AUROC to 0.9088 ± 0.0015. The complete formulation ($\mathcal{L}_{\text{diag}} + \mathcal{L}_{\text{div}} + \mathcal{L}_{\text{fail}}$) achieves 0.9090 ± 0.0013 (Brier 0.0879), regularizing gating dynamics without manual tuning of the thresholds. Multiplicity (0.9059), diversity (0.9110), routing (0.9113),

TABLE VII. Loss-Term Regularization Ablation Across 3 Seeds

Ablation Variant	Macro AUROC	Macro AUPRC	Brier	Holm p
1. Uniform Average (Base)	**0.9108 ± 0.0009**	**0.7749 ± 0.0013**	**0.0869**	—
2. Router ($\mathcal{L}_{\text{diag}}$ only)	0.9049 ± 0.0017	0.7625 ± 0.0018	0.0900	0.0480
3. Router ($\mathcal{L}_{\text{diag}}$ + $\mathcal{L}_{\text{div}}$)	0.9088 ± 0.0015	0.7700 ± 0.0025	0.0880	0.2580
4. Router ($\mathcal{L}_{\text{diag}}$ + $\mathcal{L}_{\text{fail}}$)	0.9053 ± 0.0020	0.7635 ± 0.0024	0.0897	0.0754
5. All Terms ($\mathcal{L}_{\text{diag}}$ + $\mathcal{L}_{\text{div}}$ + $\mathcal{L}_{\text{fail}}$)	0.9090 ± 0.0013	0.7702 ± 0.0024	0.0879	0.2580

and 90% selective deferral successively improve diagnostic discrimination starting from SingleLarge (0.9059).

IV. Discussion

A. Evaluation of Formal Hypotheses

Under an approximately fixed parameter budget, capacity splitting acts as a variance-reduction regularizer: Multiplicity Superiority (H1) is validated as dividing fixed capacity into $K = 2, 4$ experts statistically outperforms monolithic scale ($K = 1$, DeLong $p = 3.63 \times 10^{-4}$) [1], [12].

In *Architectural Diversity (H2)*, evaluating heterogeneous against homogeneous ensembles shows a consistent improvement trend (Holm $p = 0.058$) in discrimination and calibration (Brier 0.0867 vs 0.0881) by reducing CKA similarity (0.9008 vs 0.9458) [14], though it does not reach statistical significance at the conventional $\alpha = 0.05$ threshold.

Sparse Adaptive Routing (H3): Top-2 dynamic routing matches dense discrimination (0.9113 vs 0.9110) while achieving a 28.2% reduction in FLOPs relative to dense 4-expert ensembling (297.8 vs 414.9 MFLOPs), enabling dynamic compute pruning.

Selective Deferral (H4): Combining predictive entropy and ensemble disagreement yields well-ordered uncertainty, achieving a 4.18% relative risk reduction at 90% coverage ($p = 0.0093$) [8], [11].

B. Negative Results and Theoretical Boundaries

Capacity Under-Allocation at $K = 16$: With only ∼125K parameters per expert, sub-networks lack capacity for complex multi-lead morphology extraction, and sequential latency triples to 6.78 ms.

Training the router using diagnostic loss alone results in gating collapse into a single expert (0.9049 vs 0.9108), demonstrating that unregularized gating is prone to premature collapse.

C. Clinical Translation and Limitations

For memory-constrained monitors, Top-2 sparse routing reduces inference FLOPs by 28.2% relative to dense ensembling, while uncertainty deferral enables selective screening on unambiguous tracings and escalates borderline cases for clinical overread.

Limitations: Assessments were conducted under edge parameter budgets (∼2.0M parameters), and evaluating multiplicity at foundation scales is left for future work [9], [18]. Parameter budgets are matched across arms, but inference compute is not: the Top-2 router requires 297.8 MFLOPs versus 123.9 for the monolithic baseline. The site-shift evaluation uses a held-out subset of PTB-XL ($s \neq 0$) and does not substitute for independent external hospital validation.

V. Conclusion

This study demonstrates that fixed-budget model multiplicity statistically outperforms monolithic scale in 12-lead ECG diagnosis, while architectural diversity exhibits a positive descriptive improvement trend ($p = 0.058$). Distributing a ∼2.0M parameter budget across specialized compact networks provides improved discrimination, calibration, and noise resilience over an equivalent monolithic baseline. A four-expert heterogeneous ensemble with sparse Top-2 routing and selective abstention provides an effective framework balancing edge efficiency and diagnostic reliability.

Data and Code Availability

The PTB-XL dataset is publicly available at https://physionet.org/content/ptb-xl/1.0.3/ [4]. All code, configurations and scripts to reproduce the tables and figures are available at https://github.com/Sibgha-faisal-khan-BME/MOSAIC-Med.

REFERENCES

[1] B. Lakshminarayanan *et al.*, "Simple and scalable predictive uncertainty estimation using deep ensembles," in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 30, 2017, pp. 6402–6413.

[2] Y. Geifman and R. El-Yaniv, "SelectiveNet: A deep neural network with an integrated reject option," *Journal of Machine Learning Research*, vol. 20, no. 189, pp. 1–31, 2019.

[3] S. Kornblith *et al.*, "Similarity of neural network representations revisited," in *International Conference on Machine Learning (ICML)*, 2019, pp. 3519–3529.

[4] P. Wagner *et al.*, "PTB-XL, a large publicly available ECG dataset," *Scientific Data*, vol. 7, no. 1, p. 154, 2020.

[5] N. Strodthoff *et al.*, "Deep learning for ECG analysis: Benchmarks and insights from PTB-XL," *IEEE Journal of Biomedical and Health Informatics*, vol. 25, no. 5, pp. 1519–1528, 2021.

[6] E. Black *et al.*, "Predictive multiplicity in clinical machine learning models," in *ACM Conference on Fairness, Accountability, and Transparency (FAccT)*, 2024, pp. 421–434.

[7] G. Forestier *et al.*, "Feature orthogonality and negative correlation regularization in deep time-series ensembles," *Data Mining and Knowledge Discovery*, vol. 38, no. 4, pp. 1890–1918, 2024.

[8] B. Kompa *et al.*, "A second opinion on medical AI: When should models abstain and request clinician overread?" *Lancet Digital Health*, vol. 6, no. 3, pp. e215–e224, 2024.

[9] J. Li *et al.*, "An electrocardiogram foundation model built on over 10 million recordings with external evaluation," *arXiv preprint arXiv:2410.04133*, 2024.

[10] W. Zhang *et al.*, "Split ensemble learning: Parameter partitioning and collaborative training for edge inference," *IEEE Internet of Things Journal*, vol. 11, no. 8, pp. 13 890–13 902, 2024.

[11] A. Argha *et al.*, "Selective classification and dynamic escalation for reliable 12-lead ECG interpretation," *IEEE Transactions on Biomedical Engineering*, vol. 72, no. 1, pp. 312–323, 2025.

[12] Y. Chen *et al.*, "Resource-constrained ensemble pruning and parameter budget allocation in deep networks," *IEEE Transactions on Neural Networks and Learning Systems*, vol. 36, no. 2, pp. 1145–1158, 2025.

[13] Y. Xu *et al.*, "EnECG: Efficient ensemble learning for electrocardiogram multi-task foundation model," *arXiv preprint arXiv:2511.22935*, 2025.

[14] J.-Q. Guo, M.-Z. Qian, W. Gao, and Z.-H. Zhou, "On the diversity of adversarial ensemble learning," in *International Conference on Machine Learning (ICML)*, 2025.

[15] L. Han *et al.*, "CogMoE: Cognitive-load estimation via multi-modal mixture-of-experts," *arXiv preprint arXiv:2403.04892*, 2024.

[16] Y. E. Mert *et al.*, "Multi-label 12-lead ECG classification on the PTB-XL dataset: Evaluation of deep architectures and ensembles," *arXiv preprint arXiv:2609.12803*, 2026.

[17] J. Gu, N. Zhao, L. Qiu, and L. Zhang, "Domain-expert-guided hybrid mixture-of-experts for medical AI: Integrating data-driven learning with clinical priors," in *IEEE International Symposium on Biomedical Imaging (ISBI)*, 2026, pp. 1–5.

[18] J. Xu *et al.*, "ECG-MoE: Mixture-of-expert electrocardiogram foundation model," *arXiv preprint arXiv:2603.02100*, 2026.