

DNS Walkthrough – Sibgha Mursaleen

When my FlyRank subdomain is provisioned, for example sibghamursaleen.flyrank.ai, DNS will connect that address to my existing portfolio hosted on Vercel. DNS (Domain Name System) translates human-readable domain names into information that computers can use to locate the requested service. A DNS resolver handles the lookup on behalf of the user's device, while authoritative nameservers contain the DNS records for the domain.

For my subdomain, the important record will be a **CNAME (Canonical Name) record**. A CNAME creates an alias from one hostname to another hostname rather than directly storing an IP address. The exact target/value will be the hostname that FlyRank/Ops provides for my Vercel deployment. I will not guess this value; I will use the value provided by the hosting setup.

The process will work roughly like this:

1. Someone enters sibghamursaleen.flyrank.ai into their browser.
2. The browser/operating system asks a recursive DNS resolver to find the address for that hostname.
3. If the resolver does not already have a valid cached answer, it follows the DNS hierarchy until it reaches the authoritative nameserver responsible for the domain.
4. The authoritative DNS records contain the CNAME for my FlyRank subdomain.
5. The resolver follows the CNAME to its target and obtains the information needed to reach the hosting service.
6. The resolver returns the DNS result to the user's device.
7. The browser then connects to the hosting service and requests the website using the FlyRank hostname.
8. After the custom domain is configured in Vercel, Vercel can serve the same portfolio through the new hostname and provide HTTPS for it.

DNS information can be cached by resolvers for a period determined by the record's TTL, so a DNS change may not appear everywhere immediately.

When my FlyRank subdomain is actually provisioned, my checklist will therefore be: add the FlyRank hostname as a custom domain in Vercel, use the DNS target/value supplied by Ops, wait for DNS propagation, and then open the HTTPS address and verify that the portfolio loads correctly and the browser shows a valid secure connection. The website itself does not need to be rebuilt because the custom domain is simply another hostname pointing to the existing deployment.