

# 05 • Tools

Siddharth M. Bhatia · siddharth@sidmb.com

July 1, 2026

## Contents

|                                  |   |
|----------------------------------|---|
| Define and register a tool ..... | 1 |
| Give a participant tools .....   | 2 |
| Live participant .....           | 2 |
| On a participant .....           | 2 |
| What the loop does .....         | 2 |

A `Tool` is a capability a participant can invoke mid-turn. The harness runs a uniform tool loop; each family parses its own native call format (Hermes/ Qwen `<tool_call>` JSON, Gemma ````tool_code`, Llama `<python_tag>`). Tools hold live callables, so they are **not** serializable — templates store tool *names* and resolve them against a `ToolRegistry` at build time (mirroring how models resolve from ids).

## Define and register a tool

```
from interlens import Tool, DEFAULT_REGISTRY

class Calculator(Tool):
    name = "calculator"

    @property
    def schema(self) → dict:
        return {
            "type": "function",
            "function": {
                "name": "calculator",
                "description": "Evaluate a basic arithmetic
expression and return the result.",
                "parameters": {
                    "type": "object",
                    "properties": {"expression": {"type": "string",
"description": "e.g. '2 * (3 + 4)'"}}},
                "required": ["expression"],
            },
        },
    }
```

```
def __call__(self, expression: str) → str:
    return str(eval(expression, {"__builtins__": {}})) #
    sandbox eval for the example only
DEFAULT_REGISTRY.register(Calculator()) # now resolvable by the
    name "calculator"
```

The schema is passed straight to `apply_chat_template(tools=...)`, so use the standard function-calling shape.

## Give a participant tools

### Live participant

```
from interlens import AutoModelParticipant
solver = AutoModelParticipant.from_pretrained(
    "Qwen/Qwen2.5-7B-Instruct", name="solver",
    tools=(Calculator(),), # the tool objects
    max_tool_iters=4, # bound the call→result→call loop
)
```

### On a participant

```
from interlens import Conversation, AutoModelParticipant
solver = AutoModelParticipant.from_pretrained("Qwen/Qwen2.5-7B-
    Instruct", name="solver",
                                           tools=(Calculator(),),
    max_tool_iters=4)
conv = Conversation(participants=[solver], shared_context="Compute
    17 * 23 using your tool, then explain.")
conv.run(turns=2)
```

Tools are resolved by name from `DEFAULT_REGISTRY` only when a saved conversation is reloaded (`Conversation.load`) — `save` stores each participant's tools by name; pass `registry=` there for a scoped registry.

## What the loop does

For each turn the model may emit tool calls; the harness executes each, appends the call + result to a *private* working view, and lets the model

react — up to `max_tool_iters` times. Only the **final natural-language message** reaches the shared transcript; the full call/result trail is kept in `msg.metadata["tool_trail"]`. Tool exceptions are returned to the model as `error: ... results (data, not crashes)`, so a failing tool doesn't kill the run.

```
msg = conv.transcript[-1]
for step in msg.metadata.get("tool_trail", []):
    print(step) # {"name": "calculator", "arguments": {...},
                 "output": "391", "error": False}
```

Use a scoped registry instead of the global one by passing `registry=` to `Conversation.load`.

Next: [hooks](#).