02 · Conversations in depth

Siddharth M. Bhatia · siddharth@sidmb.com
July 1, 2026

Contents

Build participants and a conversation manually 1
Framing ownership (who sees what) 2
Turn-taking 2
Stopping 3
Branching — fork a conversation for free 3
Fork from a specific turn — `branch_from` 4
Editing history in place — rewind, edit, reset 4
Editing history and the KV cache 5
Ephemeral sampling — read state without mutating it 5
Reasoning visibility (CoT models) 5

`Conversation.from_models` is a convenience wrapper. Build a `Conversation` by hand when you want **per-speaker framing** (different system prompts / private context), a custom moderator, policies, or hooks.

Build participants and a conversation manually

`AutoModelParticipant.from_pretrained(...)` is the HF-style loader (the participant analog of `AutoModelForCausalLM.from_pretrained`): it loads the model by id and returns the family-correct participant instance. Loading the same id twice shares one model object (weights are process-cached), so both speakers below share weights.

```
from interlens import Conversation, AutoModelParticipant

alice = AutoModelParticipant.from_pretrained(
    "Qwen/Qwen2.5-3B-Instruct", name="alice", device="cuda",
    system_prompt="You are a concise, skeptical debater. Keep replies
     under 3 sentences.",
    temperature=0.7, max_new_tokens=200,
)
bob = AutoModelParticipant.from_pretrained(
```

```
    "Qwen/Qwen2.5-3B-Instruct", name="bob", device="cuda",     # same id →
     shares alice's weights (cached)
    system_prompt="You are an enthusiastic optimist who loves analogies.",
    temperature=0.9, max_new_tokens=200,
)
conv = Conversation(
    participants=(alice, bob),
    shared_context="Topic: should cities ban cars downtown? Debate it.",
     # seeded as a moderator turn
    shared_system_prompt="Stay respectful and on-topic.",
     # prepended to every speaker's system block
    reasoning_visibility="strip",   # see below
)
conv.run(turns=6)
```

Framing ownership (who sees what)

- **Shared** framing lives on the `Conversation`: `shared_context` (injected once as a `moderator` turn everyone sees) and `shared_system_prompt` (merged into every speaker's system block).
- **Private** framing lives on each participant: `system_prompt` and `private_context` (a tuple of `ContextItem`) — invisible to the other speaker and to the transcript.

```
from interlens import ContextItem, AutoModelParticipant
spy = AutoModelParticipant.from_pretrained(
    "Qwen/Qwen2.5-3B-Instruct", name="spy",
    system_prompt="Secretly steer the topic toward trains.",
    private_context=(ContextItem("Remember: never admit you have an
     agenda.", role_hint="user", author="handler"),),
)
```

Turn-taking

- **`conv.step(speaker)`** — one turn by a specific speaker, committed to the transcript; returns the `Message` (or `None` if a hook denied it).
- **`conv.run(turns=N, until=..., first=...)`** — alternate speakers round-robin. `first` sets who starts.

```
conv.step(alice)                        # drive turns explicitly
conv.step(bob)
conv.run(turns=4, first=alice)          # or in bulk
```

Stopping

`until=` takes a single `StopCondition` or a list (any of which stops). Whichever of `turns`/`until` hits first ends the run.

```
from interlens import (
    TurnStopCondition, TokenStopCondition, ElapsedTimeStopCondition,
     StopStringCondition,
)
conv.run(until=[
    TurnStopCondition(max_turns=20),           # cap turns
    TokenStopCondition(max_tokens=4000),       # cap cumulative generated
     tokens
    ElapsedTimeStopCondition(seconds=120),     # wall-clock budget
    StopStringCondition(["I concede", "AGREED"]),  # stop when a turn
     contains any string
])
```

Branching — fork a conversation for free

`branch()` forks into a new `Conversation` that **reuses the same participant objects** (shared weights, zero extra GPU) with a *copied* transcript. Explore divergent continuations without touching the original — each branch has its own transcript, so they diverge independently:

```
base = conv.branch()
for _ in range(3):
    b = base.branch()
    b.run(turns=2, first="alice")     # first accepts a name, index,
     or Participant
    print("continuation:", b.transcript[-1].content[:80])
# `conv` and `base` are untouched; only each `b` advanced.
```

> Because branches **share the participant objects**, mutating a participant (e.g. `b.participant("alice").temperature = 0.3`) changes it for *every* branch and the original. To vary generation settings per

branch, set them right before you run, or pin `seed` and vary only the prompt/intervention — see 09.

Fork from a specific turn — `branch_from`

`branch_from(ref)` forks as if the conversation had stopped **right after** `ref`, ready for a different continuation. `ref` is a *message reference*: an `int` index (Python semantics — negatives count from the end) or the `Message` object itself (matched by identity). The original is untouched.

```
alt = conv.branch_from(-3)          # continue as if the last two turns
     never happened
alt.run(turns=4, first="alice")

pivot = conv.transcript[2]          # a Message object
alt2 = conv.branch_from(pivot)      # fork right after that specific turn
```

Editing history in place — rewind, edit, reset

Sometimes you want to alter the *current* conversation rather than fork. These mutate in place (and return `self`/the `Message` for chaining); `branch_from` first if you'd rather keep the original.

```
conv.rewind(to=-2)                  # drop everything after that turn;
     `to` becomes the new last turn
conv.rewind(to=some_message)         # ...or rewind to a specific Message

conv.edit(3, "a corrected reply")   # replace turn 3's content
conv.edit(-1, author="moderator")   # change who a turn is attributed to
conv.edit(msg, note="flagged")      # merge metadata onto a turn
     (untouched keys survive)
```

`edit` targets are the same message references as `branch_from` (int index, negative, or `Message`). Because a `Message` is a mutable dataclass held **by reference**, editing its fields directly — `conv.transcript[i].content = "…"`, or mutating the object `step()`/`sample()` returned — does the exact same thing; `edit` is just the ergonomic wrapper.

To wipe the dialogue and start the *same scenario* over, use `reset()` — it empties the transcript and re-seeds the `shared_context` framing:

```
conv.reset()                          # back to the fresh, pre-run state
     (framing restored)
conv.run(turns=6)
```

> `conv.reset()` keeps your `shared_context` / opening instructions; the lower-level `conv.transcript.clear()` does **not** — it wipes the seed turn too, leaving a genuinely empty transcript. Reach for `clear()` only when you want nothing at all left.

Editing history and the KV cache

Editing or rewinding is always safe with cross-turn KV reuse. The cache is reused only when the cached tokens are an **exact prefix** of the next prompt (`ModelParticipant._maybe_reuse_cache`); an `edit` changes tokens mid-history, so the prefix check fails and the model does a clean full prefill — the cache can never serve stale keys. A `rewind`/`branch_from` leaves a genuine prefix, so reuse still engages and only the new suffix is prefilled.

Ephemeral sampling — read state without mutating it

`sample()` generates a reply to an optional temporary message **without committing anything** — ideal for probing "what would X say now?" repeatedly.

```
for q in ["Summarize your position.", "What's your strongest objection?"]:
    print(conv.sample("alice", q, as_author="interviewer").content)
# conv.transcript is unchanged after all of this
```

`sample` and `step` accept the same interpretability options (`steering=`, `capture=`, `patch=`, `return_logprobs=`) — see 07.

Reasoning visibility (CoT models)

For models that emit `<think>…</think>`, `reasoning_visibility` controls whether a prior turn's parsed reasoning is re-injected into other speakers' views:

- `"strip"` (default) — reasoning never leaks into anyone's view.
- `"self_retain"` — a speaker sees only its *own* past reasoning.
- `"shared"` — everyone sees everyone's reasoning.

```
from interlens import ReasoningVisibility
conv = Conversation(participants=(alice,
     bob), reasoning_visibility=ReasoningVisibility.SELF_RETAIN)
```

The raw completion and parsed reasoning are always stored per message in `msg.metadata["raw_completion"]` / `msg.metadata["parsed_think"]`.

Next: participant & model options.

© 2026 Siddharth M. Bhatia. All rights reserved. Interlens is licensed under the GNU Affero General Public License v3.0.