Max Verstappen vs Lando Norris

Siddhant Shah

2024-12-05

Contents

Research Questions **1**

The dataset **1**
Pre-Processing . . . 2
Processing . . . 3

Statistical Analyses Used **3**
Multiple Linear Regression . . . 3
Two-Sample Testing . . . 4

Results **5**
Max Verstappen . . . 5
Lando Norris . . . 6
Comparative Analysis . . . 8

Conclusion **9**

Research Questions

- Primary Question: How do the factors affecting lap times differ between Lando Norris and Max Verstappen?
- Specific Questions:
  1. Are the coefficients of key predictors (e.g., tire choice, weather conditions) significantly different between the two drivers?
  2. Does the impact of certain variables (e.g., track characteristics) vary between the two drivers?
  3. Can statistical comparisons of the models provide insights into differences in driving styles or strategies?

The dataset

Data was taken from the FastF1 library. Laps where there was an incident on track were not included.

```
library(openxlsx)
library(dplyr)
library(plotly)
set.seed(42)
```

```r
data = read.xlsx("Data/Pre-Processed Data/Data.xlsx")
cat('Read', nrow(data), 'lines.')
```

```
Read 18435 lines.
```

```r
head(data)
```

```
  year round DriverNumber LapsLeft Compound TyreLife AirTemp TrackTemp  Rain
1 2023     1            1       54     SOFT        6    27.3      31.1 FALSE
2 2023     1            1       53     SOFT        7    27.3      31.2 FALSE
3 2023     1            1       52     SOFT        8    27.2      31.0 FALSE
4 2023     1            1       51     SOFT        9    27.2      31.0 FALSE
5 2023     1            1       50     SOFT       10    27.1      31.0 FALSE
6 2023     1            1       49     SOFT       11    27.1      30.9 FALSE
  HumidityWindInteraction WindChillFactor SurfaceGripIndex TrackLength
1                    13.2        29.58422           24.258    5338.635
2                     8.8        29.61579           24.336    5338.635
3                    22.0        29.43960           24.180    5338.635
4                    13.2        29.48553           24.180    5338.635
5                    13.2        29.38684           24.180    5338.635
6                    12.6        29.38684           24.411    5338.635
  NumberOfCorners TotalCurvature MaxCurvature CurvatureSD MinElevation
1              15       57.79127     6.278293   0.5204532      -16.013
2              15       57.79127     6.278293   0.5204532      -16.013
3              15       57.79127     6.278293   0.5204532      -16.013
4              15       57.79127     6.278293   0.5204532      -16.013
5              15       57.79127     6.278293   0.5204532      -16.013
6              15       57.79127     6.278293   0.5204532      -16.013
  TotalElevationChange ElevationSD PointsAtStart BestLapTimeDelta LapTime
1             16.86342    5.320401             0                0  98.006
2             16.86342    5.320401             0                0  97.976
3             16.86342    5.320401             0                0  98.035
4             16.86342    5.320401             0                0  97.986
5             16.86342    5.320401             0                0  98.021
6             16.86342    5.320401             0                0  98.154
```

Pre-Processing

To pre-process the data, I

- Filter the dataset to include only dry-weather laps for a specific driver,
- Remove identifier columns,
- Perform stratified sampling across tracks to select the fastest laps, ensuring a balanced representation across races.

```r
preprocess_data = function(data, driver)
{
  data = data[data$DriverNumber == driver, ]
  data = data[!data$Rain,]
  data = subset(data, select = -c(DriverNumber, year, Rain))

  # Stratified sampling across tracks with the fastest laps
  data = data |>
          group_by(round) |>
          slice_min(order_by = LapTime,
                    n = ceiling(500 / n_distinct(data$round))) |>
```

```
          ungroup()

  return(data)
}
```

Processing

Here, I

- One-hot encode the categorical variables `Compound` which takes 3 values - 'SOFT', 'MEDIUM' and 'HARD', taking 'HARD' as the reference variable.
- Introduce interaction terms to capture compound-specific effects of tire degradation.
- Clean up redundant data to ensure proper model behavior.

```
process_data = function(data)
{
  data = data.frame(
            data,
            Compound_Soft = as.numeric(data$Compound == "SOFT"),
            Compound_Medium = as.numeric(data$Compound == "MEDIUM")
            # Hard Compound is taken as reference
          )

  data$Soft_TyreLife = data$Compound_Soft * data$TyreLife
  data$Medium_TyreLife = data$Compound_Medium * data$TyreLife

  data = subset(data, select = -c(Compound))
  return(data)
}
```

Statistical Analyses Used

Multiple Linear Regression

The `make_lm` function creates a linear regression model (lm) that predicts lap times (LapTime) in Formula 1 races based on various environmental, track, and performance-related factors.

```
make_lm = function(data)
{
  lap_time_model = lm(LapTime ~ LapsLeft
                        + TrackLength
                          + NumberOfCorners + MaxCurvature + TotalCurvature + CurvatureSD
                          + MinElevation + TotalElevationChange + ElevationSD
                        + AirTemp + TrackTemp + HumidityWindInteraction
                          + WindChillFactor + SurfaceGripIndex
                        + PointsAtStart + BestLapTimeDelta
                        + TyreLife
                          + Compound_Soft + Compound_Medium
                          + Soft_TyreLife + Medium_TyreLife,
                        data = data)

  return(lap_time_model)
}
```

Model Pipeline

This function is the complete workflow for processing data, building a linear model, and analyzing its results for a specific Formula 1 driver.

1. It filters and stratifies the dataset for the specified driver and processes categorical variables and interaction terms.
2. it fits a linear regression model to predict lap times based on track, environmental, and performance-related features.
3. It prints a summary of the model, and identifies and prints statistically significant predictors ($p < 0.05$).
4. Returns the fitted model for further analysis.

```
pipeline = function(data, driver)
{
  alpha = 0.05

  data = preprocess_data(data, driver)
  data = process_data(data)
  model = make_lm(data)

  model_summary = summary(model)

  cat('Summary for Driver #', driver)
  print(model_summary)

  coeffs = model_summary$coefficients
  coeffs = rownames(coeffs[coeffs[,4] < alpha, ])[-1]
  cat(
        cat('\n\nSignificant Predictors for Driver #', driver, sep = ''),
        coeffs,
        sep = '\n- '
      )

  return(model)
}
```

Two-Sample Testing

We build two models, one for each driver, and compare the coefficients from both models using the standard two-sided Z-test with a significance level of 95%. The function returns the Coefficients, Z-scores and the respective p-values.

We only compare coefficients that are significant in both models.

```
compare_coefficients = function(model1, model2)
{
  alpha = 0.05
  coeffs1 = summary(model1)$coefficients[-1, ]
  coeffs2 = summary(model2)$coefficients[-1, ]

  coeffs1[, 1] = ifelse(
                          (coeffs1[, 4] < alpha)
                          & (coeffs2[, 4] < alpha),
                          1, 0
                        ) * coeffs1[, 1]
  coeffs2[, 1] = ifelse(
```

```
                          (coeffs1[, 4] < alpha)
                          & (coeffs2[, 4] < alpha),
                          1, 0
                        ) * coeffs2[, 1]

  diff = coeffs1[, 1] - coeffs2[, 1]
  se_diff = sqrt(coeffs1[, 2]^2 + coeffs2[, 2]^2)
  z_scores = diff / se_diff
  p_values = 2 * (1 - pnorm(abs(z_scores)))

  comparison = data.frame(
    Coeff_Model1 = coeffs1[, 1],
    Coeff_Model2 = coeffs2[, 1],
    Z = z_scores,
    P_Value = p_values
  )

  return(comparison)
}
```

Results

Max Verstappen

```
VER = 1
VER_model = pipeline(data, VER)
```

```
Summary for Driver # 1
Call:
lm(formula = LapTime ~ LapsLeft + TrackLength + NumberOfCorners +
    MaxCurvature + TotalCurvature + CurvatureSD + MinElevation +
    TotalElevationChange + ElevationSD + AirTemp + TrackTemp +
    HumidityWindInteraction + WindChillFactor + SurfaceGripIndex +
    PointsAtStart + BestLapTimeDelta + TyreLife + Compound_Soft +
    Compound_Medium + Soft_TyreLife + Medium_TyreLife, data = data)

Residuals:
     Min       1Q   Median       3Q      Max
-10.0776  -2.2665   0.2345   2.4652   7.9926

Coefficients:
                         Estimate Std. Error t value Pr(>|t|)
(Intercept)             1.464e+03  5.738e+02   2.551 0.011058 *
LapsLeft                8.552e-02  1.505e-02   5.682 2.30e-08 ***
TrackLength             1.045e-02  3.772e-04  27.701  < 2e-16 ***
NumberOfCorners         3.547e-01  7.387e-02   4.802 2.10e-06 ***
MaxCurvature           -2.352e+02  9.160e+01  -2.568 0.010520 *
TotalCurvature         -2.207e-02  4.990e-03  -4.423 1.21e-05 ***
CurvatureSD             2.056e+01  3.532e+00   5.822 1.06e-08 ***
MinElevation           -6.780e-03  7.200e-04  -9.416  < 2e-16 ***
TotalElevationChange   -1.433e-01  1.076e-01  -1.332 0.183420
```

```
ElevationSD              8.831e-01  3.784e-01   2.334 0.019998 *
AirTemp                 -1.492e+00  1.056e+00  -1.414 0.158107
TrackTemp               -3.546e-01  7.391e-02  -4.798 2.14e-06 ***
HumidityWindInteraction  1.927e-02  5.519e-03   3.491 0.000525 ***
WindChillFactor          2.080e+00  9.946e-01   2.092 0.036990 *
SurfaceGripIndex         8.118e-01  9.004e-02   9.017  < 2e-16 ***
PointsAtStart            6.966e-03  2.072e-03   3.362 0.000834 ***
BestLapTimeDelta         1.032e+01  8.665e-01  11.909  < 2e-16 ***
TyreLife                 1.659e-01  2.452e-02   6.767 3.80e-11 ***
Compound_Soft            5.188e+00  1.054e+00   4.923 1.17e-06 ***
Compound_Medium          5.655e-01  7.542e-01   0.750 0.453743
Soft_TyreLife           -9.652e-02  6.169e-02  -1.565 0.118309
Medium_TyreLife          2.344e-02  4.447e-02   0.527 0.598413
---
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 3.608 on 484 degrees of freedom
Multiple R-squared:  0.8946,    Adjusted R-squared:  0.8901
F-statistic: 195.7 on 21 and 484 DF,  p-value: < 2.2e-16



Significant Predictors for Driver #1
- LapsLeft
- TrackLength
- NumberOfCorners
- MaxCurvature
- TotalCurvature
- CurvatureSD
- MinElevation
- ElevationSD
- TrackTemp
- HumidityWindInteraction
- WindChillFactor
- SurfaceGripIndex
- PointsAtStart
- BestLapTimeDelta
- TyreLife
- Compound_Soft
```

- With a p-value that is $< 2.2e-16$, we get the model is significant with an adjusted R-squared of 0.8901

Lando Norris

```
NOR = 4
NOR_model = pipeline(data, NOR)
```

```
Summary for Driver # 4
Call:
lm(formula = LapTime ~ LapsLeft + TrackLength + NumberOfCorners +
    MaxCurvature + TotalCurvature + CurvatureSD + MinElevation +
    TotalElevationChange + ElevationSD + AirTemp + TrackTemp +
    HumidityWindInteraction + WindChillFactor + SurfaceGripIndex +
    PointsAtStart + BestLapTimeDelta + TyreLife + Compound_Soft +
```

```
    Compound_Medium + Soft_TyreLife + Medium_TyreLife, data = data)

Residuals:
    Min      1Q  Median      3Q     Max
-10.681  -2.334   0.112   1.990   9.353

Coefficients:
                           Estimate Std. Error t value Pr(>|t|)
(Intercept)              -2.565e+03  6.047e+02  -4.242 2.66e-05 ***
LapsLeft                  1.188e-01  1.850e-02   6.422 3.23e-10 ***
TrackLength               1.027e-02  4.277e-04  24.022  < 2e-16 ***
NumberOfCorners           8.979e-01  9.179e-02   9.783  < 2e-16 ***
MaxCurvature              4.073e+02  9.657e+01   4.218 2.95e-05 ***
TotalCurvature           -4.584e-02  6.090e-03  -7.526 2.59e-13 ***
CurvatureSD               2.430e+01  4.164e+00   5.836 9.81e-09 ***
MinElevation             -7.155e-03  1.221e-03  -5.860 8.57e-09 ***
TotalElevationChange      1.086e-01  1.407e-01   0.772 0.440306
ElevationSD              -2.877e-01  4.864e-01  -0.592 0.554426
AirTemp                  -3.588e-01  1.133e+00  -0.317 0.751614
TrackTemp                 1.349e-01  1.031e-01   1.308 0.191520
HumidityWindInteraction -2.305e-02  5.761e-03  -4.002 7.28e-05 ***
WindChillFactor           6.653e-01  1.071e+00   0.621 0.534692
SurfaceGripIndex          7.407e-02  1.002e-01   0.739 0.460036
PointsAtStart             1.879e-02  5.514e-03   3.408 0.000708 ***
BestLapTimeDelta          1.726e+00  6.136e-01   2.813 0.005109 **
TyreLife                  2.411e-01  2.745e-02   8.786  < 2e-16 ***
Compound_Soft             4.225e+00  1.109e+00   3.811 0.000156 ***
Compound_Medium          -4.704e-01  8.126e-01  -0.579 0.562950
Soft_TyreLife            -1.082e-01  6.921e-02  -1.563 0.118706
Medium_TyreLife          -1.516e-01  4.431e-02  -3.422 0.000675 ***
---
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 3.783 on 482 degrees of freedom
Multiple R-squared:  0.8885,    Adjusted R-squared:  0.8836
F-statistic: 182.9 on 21 and 482 DF,  p-value: < 2.2e-16



Significant Predictors for Driver #4
- LapsLeft
- TrackLength
- NumberOfCorners
- MaxCurvature
- TotalCurvature
- CurvatureSD
- MinElevation
- HumidityWindInteraction
- PointsAtStart
- BestLapTimeDelta
- TyreLife
- Compound_Soft
- Medium_TyreLife
```

- With a p-value that is $< 2.2e-16$, we get the model is significant with an adjusted R-squared of 0.8836

Comparative Analysis

Residuals

We now compare the residuals from each model to understand how we are performing for each driver.

```
compare_residuals = function(model1, model2)
{

  residuals_df <- data.frame(
    Residuals = c(residuals(model1), residuals(model2)),
    Model = factor(c(rep("Model 1", length(residuals(model1))),
                     rep("Model 2", length(residuals(model2)))))
  )

  plot = plot_ly(
              residuals_df,
              x = ~Model,
              y = ~Residuals,
              type = "box",
              color = ~Model      # Color by model
            ) |>
          layout(
              title = "Comparison of Residuals by Model",
              xaxis = list(title = "Model"),
              yaxis = list(title = "Residuals")
            )
  return(plot)
}
```

```
compare_residuals(VER_model, NOR_model)
```

We get the median error for Max is higher than the median error for Lando, meaning that we predict Lando's Lap times more accurately. We don't use the mean here due to its sensitivity to outliers.

Coefficient Comparison

```
alpha = 0.05
comparison = compare_coefficients(VER_model, NOR_model)
cat('The two drivers have significant differences for the following parameters:')
```

```
The two drivers have significant differences for the following parameters:
```

```
differences = comparison[comparison$P_Value < alpha, ]
print(differences)
```

```
                        Coeff_Model1 Coeff_Model2         Z      P_Value
NumberOfCorners          3.547252e-01   0.89794585 -4.610495 4.017112e-06
MaxCurvature            -2.352437e+02 407.28719785 -4.827428 1.383074e-06
TotalCurvature          -2.207022e-02  -0.04583675  3.018409 2.541060e-03
HumidityWindInteraction  1.926838e-02  -0.02305346  5.304872 1.127524e-07
PointsAtStart            6.966492e-03   0.01879216 -2.007746 4.467027e-02
BestLapTimeDelta         1.031862e+01   1.72608629  8.092848 6.661338e-16
TyreLife                 1.659124e-01   0.24114337 -2.044208 4.093296e-02
```

- `NumberOfCorners`, `MaxCurvature`, `TotalCurvature`:

  Max has a smaller coefficient for `NumberOfCorners` and `MaxCurvature` than Lando. This is implies that for tracks with more turns, Max's Lap time increases less than Lando's.

- `TyreLife`:

  Max has a smaller coefficient for `TyreLife` than Lando. This is implies that Max loses less time than Lando as their tires get worn out.

Conclusion

1. **Model Performance**: Both drivers' models showed high predictive accuracy, with adjusted R-squared values of 0.8901 (Verstappen) and 0.8836 (Norris), indicating that the statistical models effectively capture the complexity of lap time determinants.
2. **Significant Predictors**: Both drivers were similarly influenced by fundamental factors like:

- Laps left in the race (This was used as a stand-in for the fuel left in the car)
- Track length
- Track curvature
- Minimum elevation (altitude of the track)
- Tire compound (particularly soft tires)

3. **Key Differences in Driving Characteristics**

- *Track Complexity Impact*: Verstappen demonstrates more consistent performance on tracks with more corners. His lap times increase less dramatically with additional turns compared to Norris. The analysis showed statistically significant differences in how NumberOfCorners, MaxCurvature, and TotalCurvature affect each driver's lap times.
- *Tire Management*: Verstappen appears to have superior tire management. His lap times are less negatively impacted by tire wear compared to Norris, suggesting more efficient driving techniques or better adaptation to tire degradation.

4. Challenges:

- Only dry-weather laps were included, excluding potentially important insights from variable weather conditions
- The linear regression model assumes linear relationships between variables, which may not always accurately capture the complex dynamics of Formula 1 racing. The model has an inherent assumption that the same underlying factors affect both drivers similarly, despite the analysis showing differences. With an adjusted R-squared around 0.88-0.89, while good, there's still about 11-12% of lap time variation unexplained by the model
- The model doesn't take into account individual race strategies, team dynamics, and car-specific characteristics