
### AKSES DATABASE

### 


**5.ALAMAT** 




### SOFTWARE BANTUAN


- MySQL ADMINISTRATOR
  - STAND ALONE ADMIN PROGRAM
- MySQL QUERY BROWSER
  - STAND ALONE QUERY PROGRAM
- ► PHPMyADMIN:
  - WEB BASED ADMIN+QUERY PROGRAM

### MySQL ADMINISTRATOR



### MySQL QUERY BROWSER








#### Welcome to phpMyAdmin 2.10.3deb1ubuntu0.1

-Language 🗓							
English (utf-8)	<b>-</b>						
,							
Log in—							
Username:	root						
Password:	******	-					
		Go					



# NorthWind Example DB

North Wind MS Acces

mssql2mysql.bas



North Wind MySQL





IMPORT NWIND.SQL

Table	Action					Records	
categories			<u> </u>	3-1		×	8
customers			<u> </u>	3		×	91
employees			<u> </u>	3-1		×	9
orderdetails			<u> </u>	3		×	2,155
orders			2	3-6		×	830
products			<u> </u>	3		×	77
shippers			<u> </u>	3-6		×	3
suppliers			<u> </u>	3-6		×	29

#### TYPICAL DB ACCESS

- OPEN CONNECTION
- ► SELECT DATABASE
- RUN QUERY
- ► GET RESULT
- ► DO SOMETHING ON RESULT
  - DISPLAY

#### OPEN CONN

```
produk.php
mysql_connect("localhost","wp
 ","Wp");
```

### OPEN CONN

- BERHASIL:
  - TIDAK ADA TAMPILAN APAPUN
- GAGAL:
  - \*ACCESS DENIED
  - **UNKNOWN MySQL SERVER**

#### SELECT DATABASE

```
produk.php
<?
  mysql_connect("localhost","wp","wp";
  mysql_select_DB("nwind");
  print mysql_error();
?>
```

#### SELECT DATABASE

- ► BERHASIL:
  - TIDAK ADA TAMPILAN
- ► GAGAL:
  - ACCESS DENIED FOR USER ......

### RUN QUERY & GET RESULT

\$sql = "select productid,
productname, unitprice from

\$results = mysql\_query(\$sql);
print mysql\_error();

products";

#### DO SOMETHING: DISPLAY

```
while($data = mysql_fetch_array($results))
  print "Product ID: $data[productid] | Production
 Name: $data[productname] | Unit Price:
 $data[unitprice]<br>";
```

localhost / localhost / nwind | phpMyAdmin ...

http://localhost/p5/produk.php

Product ID: 1 | Product Name: Chai | Unit Price: 18

Product ID: 2 | Product Name: Chang | Unit Price: 19

Product ID: 3 | Product Name: Aniseed Syrup | Unit Price: 10

Product ID: 4 | Product Name: Chef Anton's Cajun Seasoning | Unit Price: 22

Product ID: 5 | Product Name: Chef Anton's Gumbo Mix | Unit Price: 21.35

Product ID: 6 | Product Name: Grandma's Boysenberry Spread | Unit Price: 25

Product ID: 7 | Product Name: Uncle Bob's Organic Dried Pears | Unit Price: 30

Product ID: 8 | Product Name: Northwoods Cranberry Sauce | Unit Price: 40

Product ID: 9 | Product Name: Mishi Kobe Niku | Unit Price: 97

Product ID: 10 | Product Name: Ikura | Unit Price: 31

Draduct ID: 11 | Draduct Name: Ougas Cabralas | Heit Drice. 21

#### MODIFIKASI

- print "<h2>Data Produk</h2>";
- print "";
- print "";
- print "Kode";
- print "Nama";
- print "Harga/unit";
- Print "";

#### MODIFIKASI

```
while( $data = mysql_fetch_array($results))
print "";
print "$data[productid]";
 print "$data[productname]";
print "$data[unitprice]":
 print "":
    print "";
```

#### **Data Produk**

Kode	Nama	Harga/Unit
1	Chai	18
2	Chang	19
3	Aniseed Syrup	10
4	Chef Anton's Cajun Seasoning	22
5	Chef Anton's Gumbo Mix	21.35
6	Grandma's Boysenberry Spread	25
7	Uncle Bob's Organic Dried Pears	30
8	Northwoods Cranberry Sauce	40
9	Mishi Kobe Niku	97
10	Птина	7.1

### FILE UPLOAD

#### FORM UPLOAD

- <form action="upload.php" method="post" enctype="multipart/form-data">
- Upload: <input name="myfile" type="file">
- <input type="submit" value="Upload"> </form>

### upload.php

- \$\_FILES['myfile']['name']
- -\$\_FILES['myfile']['type']
- \$\_FILES['myfile']['size']
- -\$\_FILES['myfile']['tmp\_name']
- \$\_FILES['myfile']['error']

### upload.php

```
$up_directory = "./images/";
$up_dest_file = $up_directory.$_FILES['myfile']['name'];
if (move_uploaded_file($_FILES['myfile']['tmp_name'],
  $up dest file))
    print "Upload sukses";
  } else {
    print "Uplaod gagal";
```

### upload.php

- File size check?
- File extension check?
- File already exist check?

# File size check

```
    If ($_FILES['myfile']['size'] < 100000)</li>
    {
            // upload the file
        }
        ......
```

# File extension check

```
$ext = substr($_FILE['myfile']['name'],-3);
if ($ext == 'gif' || $ext == 'jpg')
     // upload the file
```

## File already exist check

```
If (!file_exists($up_dest_file))
{
    // upload file
}
```

# mail

### Simplest mail()

- **><?**
- **?**>

Plain text mail !!!!!

### More mail()

- **►** <?
- \$receiver = "cs@acme.com";
- \$subject = "Need help on install";
- \$msg = "<html><body>we need instruction on installing the printer</body></html>";
- \$headers = "MIME-Version: 1.0\r\n";
- \$headers .= "Content-type: text/html; charset=iso-8859-1\r\n";
- \$headers .= "To: Customer Support <cs@acme.com>";
- \$headers .= "From: John <john@example.com>\r\n";
- Mail(\$receiver, \$subject, \$msg, \$headers)
- ?>

# phpmailer

mail() wrapper

#### Kelas

- Class.phpmailer.php
- Class.smtp.php

- ► <?php
- require("class.phpmailer.php");
- \$mail = new PHPMailer();
- \$mail->mailer = "mail";
- \$mail->From = "rudi@acme.com";
- \$mail->AddAddress("sigi@mysite.com");
- \$mail->Subject = "Coba php mailer";
- \$mail->Body = "halo!\n\n PHPMailernya bekerja dengan baik!";
- \$mail->WordWrap = 50;

```
if(!$mail->Send())
echo "Gagal";
   echo "Mailer Error: " . $mail->ErrorInfo;
else
   echo "Sukses";
```

### Contoh lain

- <php</pre>
- require("class.phpmailer.php");
- \$mail = new PHPMailer();
- \$mail->mailer = "smtp";
- \$mail->Host = "smtp.indosat.net.id";
- \$mail->SMTPAuth = "true";
- \$mail->Username = "rudi";
- \$mail->Password = "tabuti";

- \$mail->From = "rudi@acme.com";
- \$mail->AddAddress("sigi@mysite.com");
- \$mail->Subject = "Coba php mailer";
- \$mail->Subject = "Coba php mailer";
- \$mail->Body = "halo!\n\n PHPMailernya bekerja dengan baik!";
- \$mail->WordWrap = 50;
- **▶** ?>

### Contoh lain lagi

- ► <?php
- require("class.phpmailer.php");
- \$mail = new PHPMailer();
- \$mail->mailer = "smtp";
- \$mail->Host = "smtp.indosat.net.id";
- \$mail->SMTPAuth = "true";
- \$mail->Username = "rudi";
- \$mail->Password = "tabuti";
- \$mail->isHTML(true);

- \$mail->From = "rudi@acme.com";
- \$mail->AddAddress("sigi@mysite.com");
- \$mail->Subject = "Coba php mailer";
- \$mail->Subject = "Coba php mailer";
- \$mail->Body = "<font size=5>halo! </font><br/>baik!";
- \$mail->WordWrap = 50;
- **?**>