Candela Base Class

2025-09-17 17:59:39.894480

Parallel Tests

Traffic Details

s/no	test_name	Duration	status
1	MULTICAST TEST [Parallel 1]	1 mins	EXECUTED

MULTICAST Test

Device Under Test Information

Device Under Test	DUT Name	
	DUT Hardware Version	
	DUT Software Version	
	DUT Serial Number	

Test Configuration

Test Configuration	LANforge ip	192.168.204.75
	LANforge port	8080
	Upstream	eth1
	Test Duration	1m
	Polling Interval	5s
	Total No. of Devices	1

Radio Configuration

Individual throughput mcast download bps: 256000 traffic BE (WiFi).

The below graph represents individual throughput for 1 clients running BE (WiFi) traffic. Y- axis shows "Client names" and X-axis shows "Throughput in Mbps".



Client Alias	Host eid	Host Name	Device Type / Hw Ver	Endp Name	Port Name	Mode	Mac	SSID	Channel	Type of traffic	Traffic Protocol	Offered Upload Rate Per Client	Offered Download Rate Per Client	Upload Rate Per Client	Download Rate Per Client	Drop Percentage (%)
1.110_ubuntu24_Linux	1.110	ubuntu24	Linux/x86-64	MLT-mrx-BE-sta0-1	1.110.sta0	802.11bgn 20 2x2	5c:5f:67:27:4a:86	NETGEAR_2G_wpa2	11	BE	Mcast	0	256000	0	145067	0.0

Individual throughput upstream endp, offered upload bps: 0 offered download bps: 256000 /station for traffic BE (WiFi).

The below graph represents individual throughput for 1 clients running BE (WiFi) traffic. Y- axis shows "Client names" and X-axis shows "Throughput in Mbps".



Client Alias	Host eid	Host Name	Device Type / HW Ver	Endp Name	Port Name	Mode	Mac	SSID	Channel	Type of traffic	Traffic Protocol	Offered Upload Rate Per Client	Offered Download Rate Per Client	Upload Rate Per Client	Download Rate Per Client	Drop Percentage (%)
1.1_lf0312-7d02_Linux	1.1	lf0312-7d02	Linux/x86-64	MLT-mtx-BE-eth1-0	1.1.eth1		00:03:2d:3f:7d:03		[channel: 1]	BE	Mcast	0	256000	0	255983	0.0

Layer 3 Cx Traffic Last Reporting Interval eth1

Time epoch	Time	Total-Station-Count	UL-Min-Requested	UL-Max-Requested	DL-Min-Requested	DL-Max-Requested	UL-Min-PDU	UL-Max-PDU	DL-Min-PDU	DL-Max-PDU	Attenuation	Name	Rx-Bps	Tx-Bps	Rx-Link-Rate	Tx-Link-Rate	RSSI	AP	Mode	MAC	Channel	Lc
1758112173	09_17_2025_17_59_33	2	0	0	256000	256000	MTU	MTU	MTU	MTU	-1	eth1	29396	216198	1 Gbps	1 Gbps	NaN	NaN	NaN	00:03:2d:3f:7d:03	[channel: 1]	0

Layer 3 Cx Traffic Last Reporting Interval 1.110.sta0

Time epoch	Time	Total-Station-Count	UL-Min-Requested	UL-Max-Requested	DL-Min-Requested	DL-Max-Requested	UL-Min-PDU	UL-Max-PDU	DL-Min-PDU	DL-Max-PDU	Attenuation	Name	Rx-Bps	Tx-Bps	Rx-Link-Rate	Tx-Link-Rate	RSSI	AP	Mode	MAC
1758112173	09_17_2025_17_59_33	2	0	0	256000	256000	MTU	MTU	MTU	MTU	-1	1.110.sta0	88497	12	144.4 Mbps	0 Mbps	-10 dBm	94:A6:7E:74:26:22	802.11bgn 20 2x2	5c:5f:67:27:4a:8