Tx Power

2025-09-25-16-59-43

Test Configuration

Test Configuration	Test Name	Tx Power
	Outfile	test001
	AP	HFCL
	CC	US
	RD	US
	Band	5g
	Channel	36
	NSS	2
	Bandwidth	80
	Tx Power	20 22 24

1	Country Code	Regulatory Domain	Controller Test Rig: HFCl Location default location	Controller Channel	HFCL Client Reported Channel	Client NSS	Controller BW	Station Reported BW	Tx Power Setting	AP Tx Power Setting
	US	US	HFCL	36	36	2	80 MHz	80	20	20 of 1
	US	US	HFCL	36	36	2	80 MHz	80	22	22 of 1
	US	US	HFCL	36	36	2	80 MHz	80	24	24 of 1

1	Controller Reported Total Tx Power dBm From AP Summary	AP Reported Total Tx Power dBm	Allowed dBm Per Spatial Stream cc_dbm	Cabling Pathloss	Antenna Gain	Client Reported Noise	rssi_adj: noise bare - noise floor	Client Reported Rx Rate	Client Reported Beacon Signal dBm RSSI	Client Reported Combined Signal dBm RSSI (Signal ave)
	20	20	17	40	6	-92dBm	0	1200900Kbps	-29	-30
	22	22	19	40	6	-92dBm	0	292500Kbps	-27	-28
	24	24	21	40	6	-92dBm	0	292500Kbps	-26	-27

1	Client Reported Antenna Signal dBm SS 1	Client Reported Antenna Signal dBm SS 2	Client Reported Antenna Signal dBm SS 3	Client Reported Antenna Signal dBm SS 4	Calculated Antenna 1 = Antenna Sig dBm + pathloss + rssi_adj + ant gain	Calculated Antenna 2 = Antenna Sig dBm + pathloss + rssi_adj + ant gain	Calculated Antenna 3 = Antenna Sig dBm + pathloss + rssi_adj + ant gain	Calculated Antenna 4 = Antenna Sig dBm + pathloss + rssi_adj + ant gain	Offset 1 = Calculated Antenna 1 - cc_dbm(per SS)	Offset 2 = Calculated Antenna 2 - cc_dbm(per SS)
	-46	-30			0	16	0	0	-17	-1
	-44	-28			2	18	0	0	-17	-1
	-42	-27			4	19	0	0	-17	-2

1	Offset 3 = Calculated Antenna 3 - cc_dbm(per SS)	Offset 4 = Calculated Antenna 4 - cc_dbm(per SS)	Controller Reported dBm	Client Calc Beacon dBm beacon + pathloss + rssi_adj - antenna gain	Difference Between Controller dBm & Client Calc Beacon dBm (+/- 7 dBm)	Client Calc Combined Signal dBm total signal dBm + pathloss + rssi_adj - antenna gain	Difference Between Controller dBm & Client Calc Combined Signal dBm	PASS / FAIL (+= 10 dBm)	Time Stamp	Run Time Single Test
	NaN	NaN	20	17	-3	16	-4	FAIL	2025-09-24 07:39:08.946	0d 0h 1m 31s 18340 ms
	NaN	NaN	22	19	-3	18	-4	FAIL	2025-09-24 07:40:44.163	0d 0h 1m 35s 217110 ms
	NaN	NaN	24	20	-4	19	-5	FAIL	2025-09-24 07:42:16.804	0d 0h 1m 32s 641026 ms

1	Total Run Time	Information, Warnings, Errors
	0d 0h 1m 31s 18340 ms	ERROR: Controller Power : 20 != AP Power: 20 of 1.
	0d 0h 3m 6s 235450 ms	ERROR: Controller Power : 22 != AP Power: 22 of 1.
	0d 0h 4m 38s 876476 ms	ERROR: Controller Power : 24 != AP Power: 24 of 1.