# Tx Power

2025-09-25-17-00-34

## Test Configuration

| | | |
|---|---|---|
| Test Configuration | Test Name | Tx Power |
| | Outfile | test001 |
| | AP | HFCL |
| | CC | US |
| | RD | US |
| | Band | 5g |
| | Channel | 36 |
| | NSS | 2 |
| | Bandwidth | 80 |
| | Tx Power | 20 22 24 |

| 1 | Country Code | Regulatory Domain | Controller Test Rig: HFCl Location default location | Controller Channel | HFCL Client Reported Channel | Client NSS | Controller BW | Station Reported BW | Tx Power Setting | AP Tx Power Setting |
|---|---|---|---|---|---|---|---|---|---|---|
| | US | US | HFCL | 36 | 36 | 2 | 80 MHz | 80 | 20 | 20 of 1 |
| | US | US | HFCL | 36 | 36 | 2 | 80 MHz | 80 | 22 | 22 of 1 |
| | US | US | HFCL | 36 | 36 | 2 | 80 MHz | 80 | 24 | 24 of 1 |

| 1 | Controller Reported Total Tx Power dBm From AP Summary | AP Reported Total Tx Power dBm | Allowed dBm Per Spatial Stream cc_dbm | Cabling Pathloss | Antenna Gain | Client Reported Noise | rssi_adj: noise bare - noise floor | Client Reported Rx Rate | Client Reported Beacon Signal dBm RSSI | Client Reported Combined Signal dBm RSSI (Signal ave) |
|---|---|---|---|---|---|---|---|---|---|---|
| | 20 | 20 | 17 | 40 | 6 | -92dBm | 0 | 1200900Kbps | -29 | -30 |
| | 22 | 22 | 19 | 40 | 6 | -92dBm | 0 | 292500Kbps | -27 | -28 |
| | 24 | 24 | 21 | 40 | 6 | -92dBm | 0 | 292500Kbps | -26 | -27 |

| 1 | Client Reported Antenna Signal dBm SS 1 | Client Reported Antenna Signal dBm SS 2 | Client Reported Antenna Signal dBm SS 3 | Client Reported Antenna Signal dBm SS 4 | Calculated Antenna 1 = Antenna Sig dBm + pathloss + rssi_adj + ant gain | Calculated Antenna 2 = Antenna Sig dBm + pathloss + rssi_adj + ant gain | Calculated Antenna 3 = Antenna Sig dBm + pathloss + rssi_adj + ant gain | Calculated Antenna 4 = Antenna Sig dBm + pathloss + rssi_adj + ant gain | Offset 1 = Calculated Antenna 1 - cc_dbm(per SS) | Offset 2 = Calculated Antenna 2 - cc_dbm(per SS) |
|---|---|---|---|---|---|---|---|---|---|---|
| | -46 | -30 | | | 0 | 16 | 0 | 0 | -17 | -1 |
| | -44 | -28 | | | 2 | 18 | 0 | 0 | -17 | -1 |
| | -42 | -27 | | | 4 | 19 | 0 | 0 | -17 | -2 |

| 1 | Offset 3 = Calculated Antenna 3 - cc_dbm(per SS) | Offset 4 = Calculated Antenna 4 - cc_dbm(per SS) | Controller Reported dBm | Client Calc Beacon dBm beacon + pathloss + rssi_adj - antenna gain | Difference Between Controller dBm & Client Calc Beacon dBm (+/- 7 dBm) | Client Calc Combined Signal dBm total signal dBm + pathloss + rssi_adj - antenna gain | Difference Between Controller dBm & Client Calc Combined Signal dBm | PASS / FAIL ( += 10 dBm) | Time Stamp | Run Time Single Test |
|---|---|---|---|---|---|---|---|---|---|---|
| | NaN | NaN | 20 | 17 | -3 | 16 | -4 | FAIL | 2025-09-24 07:39:08.946 | 0d 0h 1m 31s 18340 ms |
| | NaN | NaN | 22 | 19 | -3 | 18 | -4 | FAIL | 2025-09-24 07:40:44.163 | 0d 0h 1m 35s 217110 ms |
| | NaN | NaN | 24 | 20 | -4 | 19 | -5 | FAIL | 2025-09-24 07:42:16.804 | 0d 0h 1m 32s 641026 ms |

| 1 | Total Run Time | Information, Warnings, Errors |
|---|---|---|
| | 0d 0h 1m 31s 18340 ms | ERROR: Controller Power : 20 != AP Power: 20 of 1. |
| | 0d 0h 3m 6s 235450 ms | ERROR: Controller Power : 22 != AP Power: 22 of 1. |
| | 0d 0h 4m 38s 876476 ms | ERROR: Controller Power : 24 != AP Power: 24 of 1. |