Tx Power

2025-09-26-17-00-30

Test Configuration

Test Configuration	Test Name	Tx Power
	Outfile	test001
	AP	HFCL
	CC	US
	RD	US
	Band	5g
	Channel	36
	NSS	2
	Bandwidth	80
	Tx Power	20 22 24
	Tests Passed	0/3

1	Country Code	Regulatory Domain	Controller Test Rig: HFCl Location default location	Controller Channel	HFCL Client Reported Channel	Client NSS	Controller BW	Station Reported BW	Tx Power Setting	AP Tx Power Setting	Controller Reported Total Tx Power dBm From AP Summary	AP Reported Total Tx Power dBm
	US	US	HFCL	36	36	2	80 MHz	80	20	20 of 1	20	20
	US	US	HFCL	36	36	2	80 MHz	80	22	22 of 1	22	22
	US	US	HFCL	36	36	2	80 MHz	80	24	24 of 1	24	24

1	Allowed dBm Per Spatial Stream cc_dbm	Cabling Pathloss	Antenna Gain	Client Reported Noise	rssi_adj: noise bare - noise floor	Client Reported Rx Rate	Client Reported Beacon Signal dBm RSSI	Client Reported Combined Signal dBm RSSI (Signal ave)	Client Reported Antenna Signal dBm SS 1	Client Reported Antenna Signal dBm SS 2	Client Reported Antenna Signal dBm SS 3	Client Reported Antenna Signal dBm SS 4
	17	40	6	-92dBm	0	1200900Kbps	-29	-30	-46	-30		
	19	40	6	-92dBm	0	292500Kbps	-27	-28	-44	-28		
	21	40	6	-92dBm	0	292500Kbps	-26	-27	-42	-27		

1	Calculated Antenna 1 = Antenna Sig dBm + pathloss + rssi_adj + ant gain	Calculated Antenna 2 = Antenna Sig dBm + pathloss + rssi_adj + ant gain	Calculated Antenna 3 = Antenna Sig dBm + pathloss + rssi_adj + ant gain	Calculated Antenna 4 = Antenna Sig dBm + pathloss + rssi_adj + ant gain	Offset 1 = Calculated Antenna 1 - cc_dbm(per SS)	Offset 2 = Calculated Antenna 2 - cc_dbm(per SS)	Offset 3 = Calculated Antenna 3 - cc_dbm(per SS)	Offset 4 = Calculated Antenna 4 - cc_dbm(per SS)	Controller Reported dBm	Client Calc Beacon dBm beacon + pathloss + rssi_adj - antenna gain	Difference Between Controller dBm & Client Calc Beacon dBm (+/- 7 dBm)	Client Calc Combined Signal dBm total signal dBm + pathloss + rssi_adj - antenna gain
	0	16	0	0	-17	-1	NaN	NaN	20	17	-3	16
	2	18	0	0	-17	-1	NaN	NaN	22	19	-3	18
	4	19	0	0	-17	-2	NaN	NaN	24	20	-4	19

1	Difference Between Controller dBm & Client Calc Combined Signal dBm	PASS / FAIL (+= 10 dBm)	Time Stamp	Run Time Single Test	Total Run Time	Information, Warnings, Errors
	-4	FAIL	2025-09-24 07:39:08.946	0d 0h 1m 31s 18340 ms	0d 0h 1m 31s 18340 ms	ERROR: Controller Power : 20 != AP Power: 20 of 1.
	-4	FAIL	2025-09-24 07:40:44.163	0d 0h 1m 35s 217110 ms	0d 0h 3m 6s 235450 ms	ERROR: Controller Power : 22 != AP Power: 22 of 1.
	-5	FAIL	2025-09-24 07:42:16.804	0d 0h 1m 32s 641026 ms	0d 0h 4m 38s 876476 ms	ERROR: Controller Power : 24 != AP Power: 24 of 1.