

SAFETY DATA SHEET — Chromated Epoxy Primer

SYNTHETIC DEMO CONTENT. CAS 18540-29-9 (hexavalent chromium).

Section 8 — Exposure Controls. OSHA 29 CFR 1910.1026: Action Level 2.5 micrograms per cubic meter (8-hour TWA); Permissible Exposure Limit (PEL) 5 micrograms per cubic meter.

Surveillance. Medical surveillance required per 1910.1026(k) for employees exposed at or above the action level 30 or more days per year.