

```
192.168.0.10 - Remote Desktop Connection
Information: Doing activity propagation for mode 'func' and corner 'fast' with error level 'medium' (POW-024)
Information: Timer-derived activity data is cached on scenario 'func_fast' (POW-052)
Information: Fast mode activity propagation power.rtl activity annotation setup is ignored. Always use accurate mode.
Information: Running switching activity propagation in scalar mode!

**** Information : No. of simulation cycles = 6 ****
Mode: func
Corner: fast
Scenario: func_fast
Voltage: 0.60
Temperature: 125.00

Voltage Unit      : 1V
Capacitance Unit  : 1fF
Time Unit         : 1ns
Temperature Unit   : 1C
Dynamic Power Unit: 1pW
Leakage Power Unit: 1pW

Switched supply net power scaling:
Scaling for leakage power

Supply nets:
VDD (power) probability 1.00 (default)
VSS (ground) probability 1.00 (default)

Cell Internal Power = N/A ( N/A )
Net Switching Power = N/A ( N/A )
Total Dynamic Power = N/A ( 0.0%)
Cell Leakage Power  = 2.52e+08 pW

Attributes
-----
0 - User defined power group
1 - Includes clock pin internal power

Power Group      Internal Power      Switching Power      Leakage Power      Total Power      ( % )      Attrs
-----
io_pad           N/A              N/A              0.00e+00          0.00e+00          ( 0.0%)
memory           N/A              N/A              1.12e+08          1.12e+08          ( 44.6%)
black_box        N/A              N/A              0.00e+00          0.00e+00          ( 0.0%)
clock_network    N/A              N/A              4.85e+03          4.85e+03          ( 0.0%)
register         N/A              N/A              6.63e+07          6.63e+07          ( 26.3%)
sequential       N/A              N/A              0.00e+00          0.00e+00          ( 0.0%)
combinational    N/A              N/A              7.31e+07          7.31e+07          ( 29.0%)
-----
Total            N/A              N/A              2.52e+08 pW      2.52e+08 pW
1
icc2 shell>
```

scripts: tcsh | work: icc2_shell

IC Compiler II - BlockWindow.1 - Design | Error Browser | work: icc2_shell - Konsole | powerplan.tcl (~/jbl_14nm/pd/scripts)

8:28 PM 8/12/2025

192.168.0.10 - Remote Desktop Connection

work : icc2_shell - Konsole

FileEditViewBookmarksSettingsHelp

Startpoint: u_min/u_parse/u_dffrl_adtype_sm/q_reg[3] (rising edge-triggered flip-flop clocked by jbus_gclk)
Endpoint: u_ncio/u_mto/u_mto_slice0/u_dffrl_vld/q_reg[0] (rising edge-triggered flip-flop clocked by jbus_gclk)
Mode: func
Corner: slow
Scenario: func slow
Path Group: REG2REG
Path Type: max

Point	Incr	Path
clock jbus_gclk (rise edge)	0.00	0.00
clock network delay (ideal)	0.00	0.00
u_min/u_parse/u_dffrl_adtype_sm/q_reg[3]/CK (SAEDRVT14_F0PCBQ_V2LP_1)	0.00	0.00 r
u_min/u_parse/u_dffrl_adtype_sm/q_reg[3]/Q (SAEDRVT14_F0PCBQ_V2LP_1)	0.09	0.09 f
U26681/X (SAEDRVT14_NR2_1)	0.01	0.10 r
U28112/X (SAEDRVT14_MD2_CDC_1)	0.01	0.11 f
U26688/X (SAEDRVT14_NR2_1)	1.38	1.50 r
U24361/X (SAEDRVT14_NR2_1)	0.45	1.95 f
U28117/X (SAEDRVT14_MD2_CDC_1)	0.08	2.03 r
U22680/X (SAEDRVT14_NR2_1)	0.04	2.06 f
U28118/X (SAEDRVT14_INV_0P5)	0.01	2.08 r
U22580/X (SAEDRVT14_NR2_1)	0.01	2.09 f
U22543/X (SAEDRVT14_NR2_1)	0.01	2.09 r
U18694/X (SAEDRVT14_A021_2)	0.02	2.11 r
U22300/X (SAEDRVT14_NR2_1)	0.01	2.12 f
U27328/X (SAEDRVT14_INV_0P5)	0.04	2.16 r
U19824/X (SAEDRVT14_INV_0P5)	0.04	2.20 f
U21907/X (SAEDRVT14_NR2_1)	1.43	3.63 r
U21759/X (SAEDRVT14_NR2_1)	0.64	4.27 f
U45104/X (SAEDRVT14_A021B_0P5)	0.12	4.39 f
u_ncio/u_mto/u_mto_slice0/u_dffrl_vld/q_reg[0]/RS (SAEDRVT14_F0PCBQ_V2LP_0P5)	0.00	4.39 f
data arrival time		4.39
clock jbus_gclk (rise edge)	0.11	0.11
clock network delay (ideal)	0.00	0.11
u_ncio/u_mto/u_mto_slice0/u_dffrl_vld/q_reg[0]/CK (SAEDRVT14_F0PCBQ_V2LP_0P5)	0.00	0.11 r
clock uncertainty	-0.33	-0.22
library setup time	0.04	-0.18
data required time		-0.18
data required time		-0.18
data arrival time		-4.39
slack (VIOLATED)		-4.37

50 items1 item selected325 KB

8:29 PM
8/12/2025

192.168.0.10 - Remote Desktop Connection

Buf/Inv Cell Count: 3215

Buf Cell Count: 1024

Inv Cell Count: 8191

Combinational Cell Count: 29356

Single-bit Isolation Cell Count: 0

Multi-bit Isolation Cell Count: 0

Isolation Cell Banking Ratio: 0.00%

Single-bit Level Shifter Cell Count: 0

Multi-bit Level Shifter Cell Count: 0

Level Shifter Cell Banking Ratio: 0.00%

Single-bit ELS Cell Count: 0

Multi-bit ELS Cell Count: 0

ELS Cell Banking Ratio: 0.00%

Sequential Cell Count: 8104

Integrated Clock-Gating Cell Count: 0

Sequential Macro Cell Count: 86

Single-bit Sequential Cell Count: 8018

Multi-bit Sequential Cell Count: 0

Sequential Cell Banking Ratio: 0.00%

BitsPerFlop: 1.00

Macro Count: 86

Area

Combinational Area: 8680.07

Noncombinational Area: 7425.18

Buf/Inv Area: 1785.77

Total Buffer Area: 331.08

Total Inverter Area: 1454.77

Macro/Black Box Area: 69152.67

Net Area: 0

Net XLength: 904267.34

Net YLength: 811486.58

Cell Area (netlist): 85257.84

Cell Area (netlist and physical only): 91761.11

Net Length: 1715753.92

Design Rules

Total Number of Nets: 41236

Nets with Violations: 3446

Max Trans Violations: 1851

Max Cap Violations: 3421

1

icc2 shell>

scripts : tcsh

work : icc2_shell

IC Compiler II - BlockWindow.1 - Design

Error Browser

work : icc2_shell - Konsole

powerplan.tcl (~/.jbl_14nm/pd/scripts)

50 items

1 item selected 325 KB

Search

8:32 PM 8/12/2025

192.168.0.10 - Remote Desktop Connection

```
ctmTdsLR_1_39282/X (SAEDRV14_ND2_CDC_4) 0.01 0.40 f
u_mout/pktout_asm/pktout_mux/ZBUF_30_inst_58673/X (SAEDRV14_BUF_20) 0.01 0.42 r
u_mout/pktout_asm/pktout_mux/U1613/X (SAEDRV14_BUF_20) 0.01 0.43 r
u_mout/pktout_asm/pktout_mux/ctmTdsLR_1_30169/X (SAEDSLVT14_NR2_MM_4) 0.01 0.44 f
u_mout/pktout_asm/pktout_mux/ZBUF_148_inst_58748/X (SAEDRV14_BUF_20) 0.01 0.45 f
u_mout/pktout_asm/pktout_mux/ctmTdsLR_1_30691/X (SAEDRV14_OR2_MM_12) 0.02 0.47 f
u_mout/pktout_asm/pktout_mux/ZINV_434_inst_79092/X (SAEDRV14_INV_12) 0.01 0.48 r
u_mout/pktout_asm/pktout_mux/ZBUF_195_inst_58768/X (SAEDRV14_BUF_20) 0.01 0.49 r
u_mout/pktout_asm/pktout_mux/ZBUF_1333_inst_58692/X (SAEDRV14_BUF_20) 0.01 0.50 r
u_mout/pktout_asm/pktout_mux/U1157/X (SAEDRV14_NR2_2) 0.01 0.51 f
u_mout/pktout_asm/pktout_mux/ctmTdsLR_2_76470/X (SAEDRV14_OR2_4) 0.02 0.53 f
u_mout/pktout_asm/pktout_mux/ctmTdsLR_1_76469/X (SAEDRV14_NR2_6) 0.01 0.54 r
u_mout/pktout_asm/pktout_mux/ctmTdsLR_1_44564/X (SAEDRV14_ND2_CDC_4) 0.01 0.55 f
ctmTdsLR_1_38438/X (SAEDSLVT14_BUF_20) 0.01 0.57 f
u_mout/pktout_asm/pktout_mux/U589/X (SAEDRV14_EN4_4) 0.05 0.62 f
u_mout/pktout_asm/pktout_mux/U315/X (SAEDRV14_EN4_2) 0.05 0.67 f
u_mout/pktout_asm/pktout_mux/ctmTdsLR_1_30510/X (SAEDSLVT14_E04_2) 0.03 0.70 f
ZBUF_95_inst_58702/X (SAEDSLVT14_BUF_20) 0.01 0.71 f
eco_cell_350/X (SAEDRV14_BUF_20) 0.02 0.74 f
jbi_io_j_adp[0] (out) 0.00 0.74 f
data arrival time -----
clock jbus_gclk (rise edge) 0.11 0.11
clock network delay (ideal) 0.00 0.11
clock uncertainty -0.33 -0.22
output external delay -0.07 -0.29
data required time -----
data required time -0.29
data arrival time -0.74
-----
slack (VIOLATED) -1.02
```

1
icc2 shell>

scripts : tcsh work : icc2_shell

IC Compiler II - BlockWindow.1 - Design work : icc2_shell - Konsole [No Name] - GVIM placement.tcl (~/.jbi_14nm/pd/scripts)

Rainy days ahead 22°C 11:09 AM 8/14/2025

```

192.168.0.10 - Remote Desktop Connection
Information: Using activity propagation for mode func and corner fast with error level medium (POW-624)
Information: Timer-derived activity data is cached on scenario func_fast (POW-652)
Information: Fast mode activity propagation power,rtl activity annotation setup is ignored. Always use accurate mode.
Information: Running switching activity propagation in scalar mode

**** Information : No. of simulation cycles = 6 ****
Mode: func
Corner: fast
Scenario: func_fast
Voltage: 0.60
Temperature: 125.00

Voltage Unit      : IV
Capacitance Unit  : fF
Time Unit         : ns
Temperature Unit   : IC
Dynamic Power Unit: IpW
Leakage Power Unit: IpW

Switched supply net power scalings:
scaling for leakage power

Supply nets:
VDD (power) probability 1.00 (default)
VSS (ground) probability 1.00 (default)

Cell Internal Power = N/A ( N/A )
Net Switching Power = N/A ( N/A )
Total Dynamic Power = N/A ( 0.6%)

Cell Leakage Power  = 5.98e+08 pW

Attributes
-----
u - User defined power group
i - Includes clock pin internal power

Power Group      Internal Power      Switching Power      Leakage Power      Total Power      ( % )      Attrs
-----
io_pad           N/A              N/A              0.00e+00          0.00e+00          ( 0.0%)
memory           N/A              N/A              1.12e+08          1.12e+08          ( 18.8%)
black_box        N/A              N/A              0.00e+00          0.00e+00          ( 0.0%)
clock_network    N/A              N/A              1.12e+05          1.12e+05          ( 0.0%)      i
register          N/A              N/A              6.22e+07          6.22e+07          ( 10.4%)
sequential       N/A              N/A              0.00e+00          0.00e+00          ( 0.0%)
combinational    N/A              N/A              4.23e+08          4.23e+08          ( 70.8%)
-----
Total            N/A              N/A              5.98e+08 pW      5.98e+08 pW

1
icc2 shell>

```

192.168.0.10 - Remote Desktop Connection

add (power) probability 1.00 (default)
vss (ground) probability 1.00 (default)

Cell Internal Power = N/A (N/A)
Net Switching Power = N/A (N/A)
Total Dynamic Power = N/A (0.0%)
Cell Leakage Power = 5.98e+08 pW

Attributes

u - User defined power group
l - Includes clock pin internal power

Power Group	Internal Power	Switching Power	Leakage Power	Total Power	(%)	Attrs
io pad	N/A	N/A	0.00e+00	0.00e+00	(0.0%)	
memory	N/A	N/A	1.12e+08	1.12e+08	(18.6%)	
black box	N/A	N/A	0.00e+00	0.00e+00	(0.0%)	
clock network	N/A	N/A	1.12e+05	1.12e+05	(0.0%)	1
register	N/A	N/A	6.22e+07	6.22e+07	(10.4%)	
sequential	N/A	N/A	0.00e+00	0.00e+00	(0.0%)	
combinational	N/A	N/A	4.23e+08	4.23e+08	(70.8%)	
Total	N/A	N/A	5.98e+08 pW	5.98e+08 pW		

1
icc2_shell> report_power > ../reports/placement_power.rpt
icc2_shell> report_area
Warning: Command 'report area' is disabled. (CMD-080)
Error: disabled command report area encountered
Use error_info for more info. (CMD-013)
icc2_shell> report_congestion
Warning: The congestion map is out dated. Specify -rerun_global_router option to regenerate one.

Report : congestion
Design : jbi
Version : W-2024.09-SP3
Date : Thu Aug 14 11:16:51 2025

Layer Name	overflow		# GRCs has	max overflow
	total	max		
Both Dirs	291	5	259 (0.03%)	1
H routing	96	2	94 (0.02%)	2
V routing	195	5	165 (0.03%)	1

1
icc2_shell>

scripts : tcsh

work : icc2_shell

IC Compiler II - BlockWindow 1 - Design

work : icc2_shell - Konsole

[No Name] - GVIM

placement.tcl (-jbi_14nm/pd/scripts)

22°C Mostly cloudy

Search

11:18 AM 8/14/2025

192.168.0.10 - Remote Desktop Connection

```
Leaf Cell Count: 45271
Buf/Inv Cell Count: 15071
Buf Cell Count: 5418
Inv Cell Count: 9653
Combinational Cell Count: 37167
Single-bit Isolation Cell Count: 0
Multi-bit Isolation Cell Count: 0
Isolation Cell Banking Ratio: 0.00%
Single-bit Level Shifter Cell Count: 0
Multi-bit Level Shifter Cell Count: 0
Level Shifter Cell Banking Ratio: 0.00%
Single-bit ELS Cell Count: 0
Multi-bit ELS Cell Count: 0
ELS Cell Banking Ratio: 0.00%
Sequential Cell Count: 8104
Integrated Clock-Gating Cell Count: 0
Sequential Macro Cell Count: 86
Single-bit Sequential Cell Count: 8018
Multi-bit Sequential Cell Count: 0
Sequential Cell Banking Ratio: 0.00%
BitsPerFlop: 1.00
Macro Count: 86
```

Area

```
Combinational Area: 15305.30
Noncombinational Area: 8986.56
Buf/Inv Area: 6000.93
Total Buffer Area: 3600.03
Total Inverter Area: 2392.89
Macro/Block Box Area: 69192.67
Net Area: 0
Net XLength: 421277.01
Net YLength: 453570.62
```

Cell Area (netlist): 93444.53
Cell Area (netlist and physical only): 99947.80
Net Length: 874847.63

Design Rules

```
Total Number of Nets: 48879
Nets with Violations: 557
Max Trans Violations: 0
Max Cap Violations: 557
```

1
icc2 shell>

scripts : tcsh work : icc2_shell

IC Compiler II - BlockWindow.1 - Design work : icc2_shell - Konsole INo Name1 - GVIM placement.tbl (-~/jbl_14nm/pd/scripts)

22°C Mostly cloudy 11:21 AM 8/14/2025


```
192.168.0.10 - Remote Desktop Connection
u_jbus_header/IO/sync_cluster_slave/q_r_reg/CK (low) 0.03 -0.29 (VIOLATED) jbus_gclk
u_jbus_header/IO/rst_repeater/repeater/IO/q_reg/CK (low) 0.04 -0.26 (VIOLATED) jbus_gclk
u_jbus_header/IO/sync_cluster_slave/so_l_reg/G (low) 0.03 -0.26 (VIOLATED) jbus_gclk
u_jbus_header/IO/rst_repeater/lockup/so_l_reg/G (low) 0.03 -0.26 (VIOLATED) jbus_gclk
u_jbus_header/IO/sync_cluster_master/q_r_reg/CK (low) 0.03 -0.29 (VIOLATED) jbus_gclk
-----
Number of min pulse width violation(s): 4
Total number of violation(s): 6

1
icc2_shell> report clock tree options
*****
Report : target skew and latency
Design : jbi
Date : Fri Aug 15 11:24:13 2025
*****

##Target Skew
Clock Corner Target
-----
cmp_gclk (mode func) fast 0.13635
cmp_gclk (mode func) slow 0.13635
jbus_gclk (mode func) fast 0.01665
jbus_gclk (mode func) slow 0.01665

##Target Latency
Clock Corner Target
-----
No target latency found.

##Max Level Count
Clock Count
-----
No max level constraints found.

##Root NDR Fanout Limit
Clock Fanout limit
-----
No Root NDR fanout limit constraints applied.

##Trunk nets specific drivers
-----
1
icc2_shell>
```

scripts: tcsh work: icc2_shell

IC Compiler II - BlockWindow.1 - Design work: icc2_shell - Konsole INo Name1 - GVIM cts.tcl (~/.jbi_14nm/jpd/scripts) - GVIM1

11:25 AM 8/15/2025

```
192.168.0.10 - Remote Desktop Connection

Clock          Corner          Target
-----
cmp_gclk (mode func)    fast          0.13635
cmp_gclk (mode func)    slow          0.13635
jbus_gclk (mode func)   fast          0.01665
jbus_gclk (mode func)   slow          0.01665

##Target Latency

Clock          Corner          Target
-----
No target latency found.

##Max Level Count

Clock          Count
-----
No max level constraints found.

##Root NDR Fanout Limit

Clock          Fanout limit
-----
No Root NDR fanout limit constraints applied.

##Trunk nets specific drivers

-----
1
icc2_shell> report_clock_tree_options > ../reports/cts_report_clock_tree.rpt
icc2_shell> report_clock
*****
Report : clock
Design : jbi
Mode : func
Version: W-2024.09-SP3
Date : Fri Aug 15 11:26:17 2025
*****

Attributes:
p - Propagated clock
G - Generated clock
U - Unexpanded generated clock

Clock    Period    Waveform    Attrs    Sources
-----
cmp_gclk    0.91    {0 0.4545}    p    {cmp_gclk}
jbus_gclk    0.11    {0 0.0555}    p    {jbus_gclk}

1
icc2_shell>
```

scripts : tcsh

work : icc2_shell

IC Compiler II - BlockWindow.1 - Design

work : icc2_shell - Konsole

[No Name] - GVIM

cts.tcl (~/jbi_14nm/jpd/scripts) - GVIM1

11:26 AM 8/15/2025

192.168.0.10 - Remote Desktop Connection

Report : clock qor
-type summary
Design : jbi
Version : W-2024.09-SP3
Date : Fri Aug 15 11:27:11 2025

Attributes
=====
M Master Clock
G Generated Clock
I Internal Generated Clock
U User Defined Skew Group
D Default Skew Group
* Generated Clock Balanced Separately

==== Summary Reporting for Corner fast =====

Clock / Skew Group	Attrs	Sinks	Levels	Clock Repeater Count	Clock Repeater Area	Clock Stdcell Area	Max Latency	Global Skew	Trans DRC Count	Cap DRC Count	Wire Length
### Mode: func, Scenario: func_fast											
jbus_gclk	M,D	5196	18	369	194.34	199.18	0.60	0.51	1	0	33345.51
cmp_gclk	M,D	2908	9	63	32.01	34.81	0.34	0.16	1	0	10730.82
All Clocks		8104	18	432	226.35	233.99	0.60	0.51	2	0	44076.33

Warning: Please use -largest / -smallest / -all switches with -show_verbose_paths / -show_paths to report the clock paths. (CTS-956)

==== Summary Reporting for Corner slow =====

Clock / Skew Group	Attrs	Sinks	Levels	Clock Repeater Count	Clock Repeater Area	Clock Stdcell Area	Max Latency	Global Skew	Trans DRC Count	Cap DRC Count	Wire Length
### Mode: func, Scenario: func_slow											
jbus_gclk	M,D	5196	18	369	194.34	199.18	0.56	0.47	1	0	33345.51
cmp_gclk	M,D	2908	9	63	32.01	34.81	0.33	0.15	1	0	10730.82
All Clocks		8104	18	432	226.35	233.99	0.56	0.47	2	0	44076.33

Warning: Please use -largest / -smallest / -all switches with -show_verbose_paths / -show_paths to report the clock paths. (CTS-956)

1
icc2_shell>

scripts : tcshwork : icc2_shell

IC Compiler II - BlockWindow.1 - Designwork : icc2_shell - Konsole[No Name] - GVIMcts.tcl (~/.jbi_14nm/jpd/scripts) - GVIM1

11:27 AM 8/15/2025

192.168.0.10 - Remote Desktop Connection

```
cmp_gclk      M,D      2908      9      63      32.01      34.81      0.34      0.10      1      0      10730.82
All Clocks    8104      18      432      226.35      233.99      0.60      0.51      2      0      44076.33

Warning: Please use -largest / -smallest / -all switches with -show_verbose_paths / -show_paths to report the clock paths. (CTS-956)
===== Summary Reporting for Corner slow =====

===== Summary Table for Corner slow =====
Clock / Skew Group      Attrs      Sinks Levels      Clock Repeater      Clock Repeater      Clock Stdcell      Max Latency      Global Skew      Trans DRC      Cap DRC      Wire Length
                        Count      Area      Count      Area
-----
### Mode: func, Scenario: func_slow
ibus_gclk      M,D      5196      18      369      194.34      199.18      0.56      0.47      1      0      33345.51
cmp_gclk      M,D      2908      9      63      32.01      34.81      0.33      0.15      1      0      10730.82
All Clocks    8104      18      432      226.35      233.99      0.56      0.47      2      0      44076.33

Warning: Please use -largest / -smallest / -all switches with -show_verbose_paths / -show_paths to report the clock paths. (CTS-956)
1 icc2_shell> report_clock_qor > ../reports/cts_report_clock_qor.rpt
icc2_shell> report_qor -summary
=====
Report : qor
       -summary
Design : jbi
Version: W-2024.00-SP3
Date   : Fri Aug 15 11:30:11 2025
=====

Timing
-----
Context      WNS      TNS      NVE
-----
func_slow    (Setup)    -1.12      -1848.94      6280
Design       (Setup)    -1.12      -1848.94      6280
func_fast    (Hold)     -0.58      -1845.14      6392
Design       (Hold)     -0.58      -1845.14      6392
-----

Miscellaneous
-----
Cell Area (netlist):      92858.27
Cell Area (netlist and physical only): 99361.54
Nets with DRC Violations: 165
1 icc2_shell>
```

scripts : tcsh

work : icc2_shell

IC Compiler II - BlockWindow.1 - Design

work : icc2_shell - Konsole

[No Name] - GVIM

cts.tcl (~/.jbi_14nm/jd/scripts) - GVIM1

11:30 AM

8/15/2025

192.168.0.10 - Remote Desktop Connection

```
*****
Report : timing
        -path type full
        -delay type min
        -max paths 1
        -report by design
Design : jbi
Version: W:2024.09-SP3
Date   : Fri Aug 15 11:32:39 2025
*****

Startpoint: u_jbus_header/i0/rst_repeater/syncff/i0/q_reg (rising edge-triggered flip-flop clocked by jbus_gclk)
Endpoint:  u_mout/jid_to_yid/jid_to_yid_table/yid_table_04_reg/q_reg[8] (rising edge-triggered flip-flop clocked by jbus_gclk)
Mode: func
Corner: fast
Scenario: func fast
Path Group: REG2REG
Path Type: min

Point                               Incr      Path
-----
clock jbus_gclk (rise edge)         0.00      0.00
clock network delay (propagated)    0.09      0.09

u_jbus_header/i0/rst_repeater/syncff/i0/q_reg/CK (SAEDRV14_FDPBBQ_V2LP_2)
0.00      0.09 r
u_jbus_header/i0/rst_repeater/syncff/i0/q_reg/Q (SAEDRV14_FDPBBQ_V2LP_2)
0.05      0.14 f
HPSBUF 60112 3596/X (SAEDSLVT14_BUF_20)
0.01      0.15 f
HPSBUF 25830 3582/X (SAEDSLVT14_BUF_20)
0.02      0.17 f
cops_h_inst101640/X (SAEDSLVT14_BUF_ECO_1)
0.03      0.20 f
HPSBUF 17970 3576/X (SAEDSLVT14_BUF_5_10)
0.01      0.22 f
u_mout/jid_to_yid/jid_to_yid_table/yid_table_04_reg/q_reg[8]/D (SAEDHVT14_FDPBBQ_V2LP_1)
0.00      0.22 f
data arrival time                    0.22

clock jbus_gclk (rise edge)         0.00      0.00
clock network delay (propagated)    0.53      0.53
u_mout/jid_to_yid/jid_to_yid_table/yid_table_04_reg/q_reg[8]/CK (SAEDHVT14_FDPBBQ_V2LP_1)
0.00      0.53 r
clock uncertainty                    0.22      0.75
library hold time                   0.04      0.80
data required time                  0.00
-----
data required time                   0.80
data arrival time                    -0.22
-----
slack (VIOLATED)                    -0.58
*****

1
icc2_shell>
```

scripts : tcsh work : icc2_shell

IC Compiler II - BlockWindow.1 - Design work : icc2_shell - Konsole [No Name] - GVIM cts.tcl (~/.jbi_14nm/jd/scripts) - GVIM1

11:32

11:33 AM 8/15/2025

192.168.0.10 - Remote Desktop Connection

```
clock_jbus_clk (rise edge)      0.00      0.00
clock_network_delay (propagated) 0.45      0.45

u_ncio/u_prqg_buf/u_prqg_buf/sram16x32_inst1/CE (SRAM1RW16x32)
                                0.00      0.45 r
u_ncio/u_prqg_buf/u_prqg_buf/sram16x32_inst1/0[1] (SRAM1RW16x32)
                                0.10      0.55 f -
HFSTNV_532_2805/X (SAEDSLVT14_INV_4) 0.04      0.59 r
ctmTdsLR_2_96042/X (SAEDSLVT14_INV_PS_1) 0.02      0.61 f
ctmTdsLR_1_97048/X (SAEDSLVT14_ND2B_U_0P5) 0.01      0.61 r
ctmTdsLR_3_96156/X (SAEDSLVT14_NR2_MM_0P5) 0.01      0.62 f
ctmTdsLR_1_96154/X (SAEDSLVT14_OA21B_1) 0.01      0.63 r
ctmTdsLR_1_94713/X (SAEDSLVT14_ND2_1) 0.01      0.64 f
ctmTdsLR_2_96125/X (SAEDSLVT14_ND2_MM_1) 0.01      0.65 r
ctmTdsLR_1_96124/X (SAEDSLVT14_ND2_CDC_1) 0.01      0.65 f
u_mout/pktout_asm/pktout_mux/ctmTdsLR_2_94802/X (SAEDSLVT14_ND2_CDC_1)
                                0.01      0.66 r
u_mout/pktout_asm/pktout_mux/ctmTdsLR_1_94801/X (SAEDSLVT14_ND2_1)
                                0.01      0.67 f
u_mout/pktout_asm/pktout_mux/ctmTdsLR_1_93529/X (SAEDSLVT14_BUF_12)
                                0.01      0.68 f
u_mout/pktout_asm/pktout_mux/ZBUF_5_inst_6204/X (SAEDSLVT14_BUF_12)
                                0.01      0.69 f
u_mout/pktout_asm/pktout_mux/ctmTdsLR_1_67262/X (SAEDSLVT14_OR4_1)
                                0.01      0.70 f
u_mout/pktout_asm/pktout_mux/ctmTdsLR_2_97956/X (SAEDSLVT14_E02_1)
                                0.03      0.73 r
u_mout/pktout_asm/pktout_mux/ctmTdsLR_1_97955/X (SAEDSLVT14_E02_V1_0P75)
                                0.02      0.75 f
u_mout/pktout_asm/pktout_mux/ctmTdsLR_1_96290/X (SAEDSLVT14_E04_2)
                                0.03      0.78 f
u_mout/pktout_asm/pktout_mux/U2436/X (SAEDSLVT14_EW4_2)
                                0.03      0.81 f
ZBUF_105_inst_57982/X (SAEDSLVT14_BUF_20) 0.01      0.82 f
eco_cell_347/X (SAEDSLVT14_BUF_20) 0.03      0.84 f
jbi_io_j_adp[3] (out) 0.00      0.84 f
data arrival time 0.84

clock_jbus_clk (rise edge)      0.11      0.11
clock_network_delay (propagated) 0.01      0.12
clock_uncertainty -0.33      -0.21
output_external_delay -0.07      -0.28
data_required_time -0.28
-----
data_arrival_time -0.84
-----
slack (VIOLATED) -1.12

1
icc2_shell>
```

scripts : tcsh work : icc2_shell

IC Compiler II - BlockWindow.1 - Design work : icc2_shell - Konsole [No Name] - GVIM cts.tcl (~/.jbi_14nm/jpd/scripts) - GVIM1

11:33 AM 8/15/2025

The image shows a Windows desktop environment. The primary focus is a terminal window titled "192.168.0.10 - Remote Desktop Connection". Inside the terminal, the user is in an "icc2_shell" and has executed a series of commands to generate and view timing reports. The output includes a detailed timing summary with values for various components like ZBUF, eco, jbi, and clock. Below this, it shows the command "report_timing -delay_type min" and its output, which includes a table of setup violations. The table has columns for "Total", "reg->reg", "in->reg", "reg->out", and "in->out", with rows for "WNS", "TNS", and "NUM". The output also shows hold violations. The terminal window is part of a taskbar at the bottom of the screen. The taskbar includes icons for "IC Compiler II - BlockWindow.1 - Design", "work : icc2_shell - Konsole", "[No Name] - GVIM", and "cts tcl (~\jbi_14nm\pd\scripts) - GVIM1". The system clock in the bottom right corner shows the time as 11:36 AM on 8/15/2024.