
Connection Architecture


How Claude Code reaches QuickBooks, how credentials are kept out of reach, and how read-only is enforced. Status key: **Implemented** is built and checked in this repo; **Proposed** is a design only.

Component diagram (Implemented)



Claude Code only ever receives tool results. The tokens stay inside the server process and its token store. No network listener exists, so nothing is exposed to attack. The workbook feeds the analysis; QuickBooks does not.

Credential lifecycle (Implemented)



Guards around the lifecycle: `CLAUDE.md` forbids reading secrets; a project hook blocks `Read`, `Grep` and `Bash` on secret, token and credential file names; saved evidence is redacted and a test checks it; the tracked-file secret scan found 0 findings in 176 files.

Read-only enforcement


The server registers a tool only if its category is not disabled. With `QUICKBOOKS_DISABLE_WRITE`, `QUICKBOOKS_DISABLE_UPDATE` and `QUICKBOOKS_DISABLE_DELETE` all set to `true`, create, update and delete tools **do not exist** for the client. That is stronger than telling the model not to call them.

Layer	Control	Status
Server	Three disable flags set to `true`; write tools never registered	Implemented
Project rule	`CLAUDE.md` forbids flipping the flags or calling write tools	Implemented
Live check	71 tools listed, none create, update or delete (2026-10-14)	Implemented
Credential	A separate write credential kept apart from the read-only one	**Not applied**

Limit: this is not an authorization boundary. The OAuth grant itself carries accounting scope, so anyone who obtains the tokens could write directly to the API.

Team hosting (Proposed)

Nothing here is built. The server speaks stdio only, so a shared service needs a wrapper that does not exist yet.



- One OAuth grant and one token store per client, mounted for exactly one server process, because two processes refreshing one rotating token can invalidate it.
- Verify each grant's realm ID against the expected company before first use.
- TLS on any network hop, a central audit log, alerts on refresh failures and approaching expiry, and a documented revoke-and-reauthorize runbook.
- Before production: fix the three runtime dependency findings in the dependency-risk note and decide who owns upgrades.

Evidence summary (2026-10-14, read-only)

Check	Result
(a) CompanyInfo read	PASS
(b) Monthly P&L Jan–Jun 2026 and Balance Sheet at 30 Jun 2026	PASS; the balance sheet balances at 5,488.75
(c) Tools registered	PASS; 71 tools, none create, update or delete
(d) Missing server folder	PASS; an actionable message and exit code 1
Earlier failure (2026-10-13)	A script bug, not an expired token: the server's tools take `{"params": {...}}` and the script sent `{}`. Fixed; failures are now classified with a next step

Rejected options

Option	Why not (for now)
Native Claude connector for QuickBooks	Availability for a sandbox company and its read-only controls were never established

Option	Why not (for now)
Custom QuickBooks REST client or MCP	We would own OAuth refresh, pagination and rate limits; the official server already does this
Third-party hosted MCP gateway	Puts client data and tokens with another party and adds a vendor to vet
Manual CSV or report exports	Not repeatable, and does not meet the brief to test the MCP route
Enabling write tools	No requirement; posting entries is a different risk class

These are judgements, not benchmarks; none was built or tried.