
GaussBetti

Release 1.0.0

Siddharth

Jul 19, 2021

CONTENTS

1	topologicalFunc	1
2	Utilities	3
3	gaussClass	5
4	Indices and tables	7
	Python Module Index	9
	Index	11

TOPOLOGICALFUNC

`topologicalFunc.GaussianFiltration(GaussianRandomField, type='lower')`

Generates Filtration for the Gaussian Random Field.

Parameters

- **GaussianRandomField** (*array*) – numpy 2-D array. The Gaussian Random Field generated from the class using `Gen_GRF` method.
- **type** (*string*) – Takes input either 'lower' or 'upper' for lower or upper filtration.
- **nsiz** (*integer*) – Size of the Gaussian Random Fields grid.

Returns Filtration Diagram

Return type Dionysus object

`topologicalFunc.GenerateBettiP(Filtration, thresholds_start, thresholds_stop, type='lower')`

Generates the Betti numbers from the Filtration diagram.

Parameters

- **Filtration** (*Dionysus object*) – Output of GaussianFiltration.
- **thresholds_start** (*float*) – start value for generating superlevels of the Gaussian Random field .
- **thresholds_stop** (*float*) – stop value for generating superlevels of the Gaussian Random field.

Returns Multidimensional array containing Betti numbers for different dimensions

Return type Numpy array

`topologicalFunc.GenerateGenus(Betti_array)`

Generates the Genus curve for gaussian random field using Betti arrays.

Parameters **array** (*Betti*) – Betti array from GenerateBettiP.

Returns 1-D array containing Genus curve for the Gaussian random field.

Return type Numpy array

UTILITIES

`utilities.KLdivergence(x, y1, y2)`

Calculates the KL divergence for 2 different Gaussian Random Field.

Parameters

- **x** (*array*) –
- **y1** (*array*) – Gaussian Random Field of null hypothesis as a 1-D array
- **y2** (*array*) – Gaussian Random Field of test hypothesis as a 1-D array

Returns KL divergence

Return type float

`utilities.SaveROC(PFA, PD, nsize, num_iter, H0, H1, Betti, type)`

Saves the PFA and PD array with the labels provided through parameters.

Parameters

- **PFA** (*array*) – numpy vector. The PFA array generated during ROC gen.
- **PD** (*array*) – numpy vector. The PD array generated during ROC gen.
- **nsize** (*integer*) – Size of the Gaussian Random Fields grid.
- **num_iter** (*integer*) – Number of iteration for which ROC gen is run.
- **H0** (*integer*) – Power spectral index of Null Hypothesis.
- **H1** (*integer*) – Power spectral index of Test Hypothesis.
- **type** (*string*) – type of the ROC curve generated

Returns None

Return type None

`utilities.likelihoodratio(correlation0, correlation1, X0, X1)`

Calculates the likelihood ratio for the False alarm and detection.

Parameters

- **correlation0** (*array*) – Correlation matrix for the Gaussian Random Field for null hypothesis.
- **correlation1** (*array*) – Correlation matrix for the Gaussian Random Field for test hypothesis.
- **X0** (*array*) – Gaussian Random Field of null hypothesis as a 1-D array
- **X1** (*array*) – Gaussian Random Field of test hypothesis as a 1-D array

Returns likelihood ratio

Return type float

`utilities.plotROC(PFA, PD, nsize, num_iter, H0, H1, Betti, type)`

Plots the PFA and PD ROC graph with the labels provided through parameters.

Parameters

- **PFA** (*array*) – numpy vector. The PFA array generated during ROC gen.
- **PD** (*array*) – numpy vector. The PD array generated during ROC gen.
- **nsize** (*integer*) – Size of the Gaussian Random Fields grid.
- **num_iter** (*integer*) – Number of iteration for which ROC gen is run.
- **H0** (*integer*) – Power spectral index of Null Hypothesis.
- **H1** (*integer*) – Power spectral index of Test Hypothesis.
- **type** (*string*) – type of the ROC curve generated

Returns None

Return type None

GAUSSCLASS

```
class gaussClass.GaussianRandomField(Nsize, n)
    The class for making Gaussian random field with specified spectral index and size of grid.

    Nsize
        size of the grid.
        Type int

    n
        Spectral index of the power law used to generate the Gaussian Random Field.
        Type int

    k_ind
        Grid in the fourier space.
        Type array

    PowerSpectrum
        The power spectrum grid made using the spectral index used to make the Gaussian Random Field.
        Type array

    corr_s
        Correlation matrix in the fourier space.
        Type array

    corr_f
        Correlation matrix in the spatial space.
        Type array

    Gen_GRF(type='grid')
        GenerateBettiP

        Generates the Gaussian Random field with the specified paramters.

        Parameters type (str) – Takes either ‘grid’ or ‘array’ in string format

        Returns: Numpy array: Gaussian Random field

    PowerSpectrum_grid_generator()
        Generates the powerspectrum grid.

    fourier_space_ind()
        Generates the fourier space grid.

    gen_correlation()
        Generates the correlation matrices in fourier and spatial spcae.
```


INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

g

gaussClass, [5](#)

t

topologicalFunc, [1](#)

u

utilities, [3](#)

INDEX

C

`corr_f` (*gaussClass.GaussianRandomField attribute*), 5
`corr_s` (*gaussClass.GaussianRandomField attribute*), 5

F

`fourier_space_ind()` (*gauss-
Class.GaussianRandomField method*), 5

G

`gaussClass`
 module, 5
`GaussianFiltration()` (*in module topologicalFunc*), 1
`GaussianRandomField` (*class in gaussClass*), 5
`gen_correlation()` (*gauss-
Class.GaussianRandomField method*), 5
`Gen_GRF()` (*gaussClass.GaussianRandomField method*),
 5
`GenerateBettiP()` (*in module topologicalFunc*), 1
`GenerateGenus()` (*in module topologicalFunc*), 1

K

`k_ind` (*gaussClass.GaussianRandomField attribute*), 5
`KLdivergence()` (*in module utilities*), 3

L

`likelihoodratio()` (*in module utilities*), 3

M

`module`
 gaussClass, 5
 topologicalFunc, 1
 utilities, 3

N

`n` (*gaussClass.GaussianRandomField attribute*), 5
`Nzise` (*gaussClass.GaussianRandomField attribute*), 5

P

`plotROC()` (*in module utilities*), 4
`PowerSpectrum` (*gaussClass.GaussianRandomField at-
tribute*), 5

`PowerSpectrum_grid_generator()` (*gauss-
Class.GaussianRandomField method*), 5

S

`SaveROC()` (*in module utilities*), 3

T

`topologicalFunc`
 module, 1

U

`utilities`
 module, 3