

## 1 Finish the Runtimes

Below we see the standard nested for loop, but with missing pieces!

```
1 for (int i = 1; i < ____; i = ____) {
2     for (int j = 1; j < ____; j = ____) {
3         System.out.println("Circle is the best TA");
4     }
5 }
```

For each part below, **some** of the blanks will be filled in, and a desired runtime will be given. Fill in the remaining blanks to achieve the desired runtime! There may be more than one correct answer.

**Hint:** You may find `Math.pow` helpful.

(a) Desired runtime:  $\Theta(N^2)$

```
1 for (int i = 1; i < N; i = i + 1) {
2     for (int j = 1; j < i; j = ____) {
3         System.out.println("This is one is low key hard");
4     }
5 }
```

(b) Desired runtime:  $\Theta(\log(N))$

```
1 for (int i = 1; i < N; i = i * 2) {
2     for (int j = 1; j < ____; j = j * 2) {
3         System.out.println("This is one is mid key hard");
4     }
5 }
```

(c) Desired runtime:  $\Theta(2^N)$

```
1 for (int i = 1; i < N; i = i + 1) {
2     for (int j = 1; j < ____; j = j + 1) {
3         System.out.println("This is one is high key hard");
4     }
5 }
```

(d) Desired runtime:  $\Theta(N^3)$

```
1 for (int i = 1; i < ____; i = i * 2) {
2     for (int j = 1; j < N * N; j = ____) {
3         System.out.println("yikes");
4     }
5 }
```

## 2 Asymptotics is Fun!

- (a) Using the function `g` defined below, what is the runtime of the following function calls? Write each answer in terms of `N`.

```

1  void g(int N, int x) {
2      if (N == 0) {
3          return;
4      }
5      for (int i = 1; i <= x; i++) {
6          g(N - 1, i);
7      }
8  }
```

`g(N, 1):  $\Theta(\quad)$`

`g(N, 2):  $\Theta(\quad)$`

- (b) Suppose we change line 6 to `g(N - 1, x)` and change the stopping condition in the for loop to `i <= f(x)` where `f` returns a random number between 1 and `x`, inclusive. For the following function calls, find the tightest  $\Omega$  and big  $O$  bounds.

```

1  void g(int N, int x) {
2      if (N == 0) {
3          return;
4      }
5      for (int i = 1; i <= f(x); i++) {
6          g(N - 1, x);
7      }
8  }
```

`g(N, 2):  $\Omega(\quad)$ ,  $O(\quad)$`

`g(N, N):  $\Omega(\quad)$ ,  $O(\quad)$`

### 3 Is This a BST?

In this setup, assume a BST (Binary Search Tree) has a **key** (the value of the tree root represented as an `int`) and pointers to two other child BSTs, `left` and `right`.

- (a) The following code should check if a given binary tree is a BST. However, for some trees, it returns the wrong answer. Give an example of a binary tree for which `brokenIsBST` fails.

```

1  public static boolean brokenIsBST(BST tree) {
2      if (tree == null) {
3          return true;
4      } else if (tree.left != null && tree.left.key > tree.key) {
5          return false;
6      } else if (tree.right != null && tree.right.key < tree.key) {
7          return false;
8      } else {
9          return brokenIsBST(tree.left) && brokenIsBST(tree.right);
10     }
11 }
```

- (b) Now, write `isBST` that fixes the error encountered in part (a).

*Hint:* You will find `Integer.MIN_VALUE` and `Integer.MAX_VALUE` helpful.

```

public static boolean isBST(BST T) {
    return isBSTHelper(______);
}
```

```

public static boolean isBSTHelper(______) {
```

```

}
```