

# 1. Creating a simple JSP Page

```
<%@ page language="java" contentType="text/html; charset=UTF-8"    pageEncoding="UTF-8"%>

<!DOCTYPE html>

<html>

<head>

<meta charset="UTF-8">

<title>Simple JSP</title>

</head>

<body>

<%

    out.println("<h2>My first JSP page.</h2>");

%>

</body>
```

---

# 2. JSP Implicit Object

```
<%@ page language="java" contentType="text/html; charset=UTF-8"    pageEncoding="UTF-8"%>

<%@ page errorPage = "handle-error.jsp" %>

<!DOCTYPE html>

<html>

<head>

<meta charset="UTF-8">

<title>JSP Implicit Objects</title>

</head>

<body>
```

```

<%
    String responseCheck = request.getParameter("office");
    if (responseCheck != null ) {
        response.setStatus(response.SC_MOVED_TEMPORARILY);
        response.setHeader("Location", "response-redirect.jsp?office=" + responseCheck);
    }

    String errorCheck = request.getParameter("error");
    if (errorCheck != null ) {
        int x = 0;
        if (x == 0)
            throw new RuntimeException("Exception has been raised");
    }
%>
<%

    int serverPort = request.getServerPort() ;
    out.println("The Server is running on port " + String.valueOf(serverPort) + "<br>");
    out.println("Servlet Name is " + config.getServletName() + "<br>");
    out.println("Server Info:" + application.getServerInfo() + "<br>");

    String pageName = page.toString();
    out.println("The name of the page is " + pageName + "<br>");

    pageContext.setAttribute("userid", "John Doe");
    out.println("userId attribute from pageContext: " + pageContext.getAttribute("userid") + "<br>");
%>

<a href="index.jsp?office=head_office">Show usage of response object</a><br>
<a href="index.jsp?error=1">Show usage of error object</a><br>

```

```
<%
    if (response.containsHeader("Office"))
        out.println("Current location is " + response.getHeader("Office"));
%>
```

```
</body>
```

```
</html>
```

```
<%@ page language="java" contentType="text/html; charset=UTF-8"    pageEncoding="UTF-8"%>
```

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<meta charset="UTF-8">
```

```
<title>Get Header Example</title>
```

```
</head>
```

```
<body>
```

```
<%
```

```
    String office = request.getParameter("office");
```

```
    if (office != null)
```

```
        out.println("value of Office obtained :" + office + "<br>");
```

```
    else
```

```
        out.println("No value of Office found<br>");
```

```
%>
```

```
</body>
```

```
</html>
```

```
<%@ page language="java" contentType="text/html; charset=UTF-8"    pageEncoding="UTF-8"
isErrorPage = "true"%>
```

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<meta charset="UTF-8">
```

```
<title>Error Handling page</title>
```

```
</head>
```

```
<body>
```

```
<% exception.printStackTrace(response.getWriter()); %>
```

```
<hr>
```

```
An exception was generated. Details are above:<br>
```

```
</body>
```

```
</html>
```

---

## 3. JSP Directives

```
<%@ page language="java" contentType="text/html; charset=UTF-8"    pageEncoding="UTF-8"%>
```

```
<%@ taglib prefix="c" uri="http://java.sun.com/jsp/jstl/core" %>
```

```
<%@ taglib prefix="fmt" uri="http://java.sun.com/jsp/jstl/fmt"%>
```

```
<!DOCTYPE html>
```

```
<!--
```

```
Download jstl.jar from http://central.maven.org/maven2/javax/servlet/jstl/1.2/jstl-1.2.jar
```

```
-->
```

```
<html>
```

```
<head>
```

```
<meta charset="UTF-8">
```

```
<title>JSP Directives</title>
```

```
</head>
```

```
<body>
```

This is content from the main file.

```
<%@ include file="included.jsp" %>
```

```
<hr>
```

Example of using JSTL taglibs for formatting output<br>

```
<p>
```

```
    Currency = <fmt:formatNumber value = "145" type = "currency"/>
```

```
<p>
```

```
<p>
```

```
    <c:set var = "now" value = "<%= new java.util.Date()%%" />
```

```
    Current date and time is <fmt:formatDate pattern = "yyyy-MM-dd hh:mm:ss" value = "${now}" />
```

```
</p>
```

```
</body>
```

```
</html>
```

```
<% out.println("This is content from included file.<br><br>"); %>
```

---

## 4. JSP Action Tags

```
<%@ page language="java" contentType="text/html; charset=UTF-8" pageEncoding="UTF-8"%>
```

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<meta charset="UTF-8">
```

```
<title>JSP Action Tags</title>
```

```
</head>
```

```
<body>
```

Usage of useBean tag<br>

```
<jsp:useBean id="productBean" class="com.ecommerce.ProductBean"
scope="session"></jsp:useBean>
```

```
    <jsp:setProperty property="productId" name="productBean" value="18791"/>
```

```
    <jsp:setProperty property="productName" name="productBean" value="Optical Wireless
Mouse"/>
```

```
    <jsp:setProperty property="price" name="productBean" value="600.00"/>
```

```
<a href="showbean.jsp">Access bean properties from another page</a><br>
```

```
<a href="forward.jsp">Use Forward action to go to Google</a><br>
```

```
<hr>
```

```
<jsp:text>
```

```
    <![CDATA[This is my content.<br/>This will show within a text action tag exactly as it has
been entered]]>
```

```
</jsp:text>
```

```
</body>
```

```
</html>
```

```
<%@ page language="java" contentType="text/html; charset=UTF-8" pageEncoding="UTF-8"%>
```

```
<jsp:forward page="forwarded.jsp"></jsp:forward>
```

```
<%@ page language="java" contentType="text/html; charset=UTF-8" pageEncoding="UTF-8"%>
```

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<meta charset="UTF-8">
```

```
<title>Forward Test</title>
```

```
</head>
```

```
<body>
```

This page came from forward.jsp by using jsp:forward action tag

```
</body>
```

```
</html>
```

```
<%@ page language="java" contentType="text/html; charset=UTF-8" pageEncoding="UTF-8"%>
```

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<meta charset="UTF-8">
```

```
<title>Display Bean properties</title>

</head>

<body>

<jsp:useBean id="productBean" class="com.ecommerce.ProductBean"
scope="session"></jsp:useBean>

    Product Id: <jsp:getProperty name="productBean" property="productId" /> <br>
    Product Name: <jsp:getProperty name="productBean" property="productName" /> <br>
    Product Price: <jsp:getProperty name="productBean" property="price" /> <br>

</body>

</html>
```

```
package com.ecommerce;

import java.io.Serializable;

public class ProductBean implements Serializable{

    private String productId;
    private String productName;
    private double price;

    public void setProductId(String value) {
        this.productId = value;
    }

    public void setProductName(String value) {
        this.productName = value;
    }

    public void setPrice(double value) {
        this.price = value;
    }
}
```



```

    }

    public String getProductId() {
        return this.productId;
    }

    public String getProductName() {
        return this.productName;
    }

    public double getPrice() {
        return this.price;
    }
}

```

---

## 5. Session Handling

```

<%@ page language="java" contentType="text/html; charset=UTF-8" pageEncoding="UTF-8"%>

<!DOCTYPE html>

<html>

<head>

<meta charset="UTF-8">

<title>JSP Sessions</title>

</head>

<body>

<%

    if (request.getParameter("error") != null)

        out.println("<b>Your session has expired or is invalid.</b><br>");

```

```
%>
```

```
<form action="login.jsp" metho="post">
```

```
    Name <input name="name" id="name" maxlength=40><br>
```

```
    Password <input type="password" name="pwd" id="pwd" maxlength="10"><br>
```

```
    <button>Submit</button>
```

```
</form>
```

```
</body>
```

```
</html>
```

```
<%@ page language="java" contentType="text/html; charset=UTF-8"    pageEncoding="UTF-8"%>
```

```
<%
```

```
    String name = request.getParameter("name");
```

```
    String pwd = request.getParameter("pwd");
```

```
    if (name == null || name.equals("") || pwd == null || pwd.equals("")) {
```

```
        response.sendRedirect("index.jsp?error=1");
```

```
    } else {
```

```
        session.setAttribute("name", name);
```

```
        response.sendRedirect("dashboard.jsp");
```

```
    }
```

```
%>
```

```
<%@ page language="java" contentType="text/html; charset=UTF-8" pageEncoding="UTF-8"%>

<!DOCTYPE html>

<html>

<head>

<meta charset="UTF-8">

<title>Dashboard</title>

</head>

<body>

<%

    if (session.getAttribute("name") == null) {

        response.sendRedirect("index.jsp?error=1");

    }

%>

<b>Hello <%= session.getAttribute("name") %></b><br>

<a href="logout.jsp">Click here to logout</a>

</body>

</html>
```

```
<%@ page language="java" contentType="text/html; charset=UTF-8" pageEncoding="UTF-8"%>

<!DOCTYPE html>

<html>

<head>

<meta charset="UTF-8">

<title>Session Logout</title>

</head>

<body>

<%

    session.invalidate();

%>
```

%>

<b>Your session has terminated.</b><br>

<a href="index.jsp">Login again</a>

</body>

</html>