Sl No	Tag Name	Description	Attributes	Values
1.	\<html\>... \</html\>	main html tag inside which the entire code is contained		
2.	\<head\>... \</head\>	header tag used for adding title & headers.		
3.	\<title\>...\</title\>	used to set title of the tag		
4.	\<body\>...\</body\>	All text & tags for the main page content is contained here	bg color alink, link vlink background	all colors " " image address
5.	\<h1\>... \<h1\>	Heading tag, to set heading $h_1 > h_2 > h_3 > h_4 > h_5 > h_6$		
6.	\<br\>	break tag, adds next line		
7.	\<u\>... \</u\>	underline tag		
8.	\<B\>...\</B\>	**BOLD**		
9.	\<I\>...\</I\>	Italic tag		
10.	\<hr\>	Horizontal line		
11.	\<small\>...\</small\>	Small text		
12.	\<big\>...\</big\>	Big text.		
13	\<Pre\>...\</Pre\>	Preserves the text (displayed same as source code).		
14.	\<bdo\>...\</bdo\>	used to override the current text direction	dir	"rtl" "ltr" rtl → Right to left ltr → left to right

Sl No.	Tag Name	Description	Attribute	Values
15.	<img>...</img>	Used to add images	*src, width, height, alt	address, int P_x, int P_x. Error msg (in case image fails)
16.	<marque>...</marque>	used to add marquee (moving text)	direction, height/width, scroll amount	Starting dir, int P_x, int (speed)
17.	<font>...<font>	used to add font to text	face, color, size	text style "-", color " ", size int ","
18.	<a>...<a>	anchor tag, used to link urls (from web device)	*href	url/address.
19.	...	ordered list . is used to add elements	type, Start	a, A, 1, i, I, "i" int, i^{th} element to start from
20.	...	unordered list is used inside to add elements.	type	"circle", "square", "disk".
21.	<DL>..<DL>	Defination list <DT>...</DT> to add title <DD>... </DD> to add defination.		