
Sep 29 13:07
Open
siddhi.c
/home/computer
Save
printf("1. Addition\n");
printf("2. Subtraction\n");
printf("3. Multiplication\n");
printf("4. Division\n");
printf("5. Modulus\n");
printf("Enter your choice: ");
scanf("%d", &choice);
switch(choice)
{
case 1:
printf("Addition is = %d\n", a + b);
break;
case 2:
printf("Subtraction is = %d\n", a - b);
break;
case 3:
printf("Multiplication is = %d\n", a * b);
break;
case 4:
if(b != 0)
printf("Division is = %d\n", a / b);
else
printf("Division by zero is not possible.\n");
break;
case 5:
if(b != 0)
printf("Modulus is = %d\n", a % b);
else
printf("Modulus by zero is not possible.\n");
break;
default:
printf("Invalid choice.\n");
}
return 0;
}
C
Tab Width: 8
Ln 1, Col 1
INS


Sep 29 13:07
Open
siddhi.c
/home/computer
Save
printf("1. Addition\n");
printf("2. Subtraction\n");
printf("3. Multiplication\n");
printf("4. Division\n");
printf("5. Modulus\n");
printf("Enter your choice: ");
scanf("%d", &choice);
switch(choice)
{
case 1:
printf("Addition is = %d\n", a + b);
break;
case 2:
printf("Subtraction is = %d\n", a - b);
break;
case 3:
printf("Multiplication is = %d\n", a * b);
break;
case 4:
if(b != 0)
printf("Division is = %d\n", a / b);
else
printf("Division by zero is not possible.\n");
break;
case 5:
if(b != 0)
printf("Modulus is = %d\n", a % b);
else
printf("Modulus by zero is not possible.\n");
break;
default:
printf("Invalid choice.\n");
}
return 0;
}
C
Tab Width: 8
Ln 1, Col 1
INS




```
Multiplication is = 60
computer@computer-Dell-Pro-Slim-Essential-QVS1260:~$ ./a.out
Enter two numbers: 20 4

--- MENU ---
1. Addition
2. Subtraction
3. Multiplication
4. Division
5. Modulus
Enter your choice: 3
Multiplication is = 80
computer@computer-Dell-Pro-Slim-Essential-QVS1260:~$
```

main.c

```c
#include <stdio.h>

int main()
{
    int age;

    printf("Enter your age:");
    scanf("%d", &age);

    printf("You entered : %d", age);

    return 0;
}
```

Problems Output Debug Console Terminal Ports

```
PS C:\Users\sassy\OneDrive\Desktop\siddhi c programs> gcc main.c
PS C:\Users\sassy\OneDrive\Desktop\siddhi c programs> .\a.exe
Enter your age:20
You entered : 20
PS C:\Users\sassy\OneDrive\Desktop\siddhi c programs>
```

oblems Output Debug Console Terminal Ports

```
PS C:\Users\sassy\OneDrive\Desktop\siddhi c programs> gcc main.c
PS C:\Users\sassy\OneDrive\Desktop\siddhi c programs> .\a.exe
Hello World!
My Name is Siddhi
PS C:\Users\sassy\OneDrive\Desktop\siddhi c programs>
```

main.c

```c
#include <stdio.h>

int main()
{
    printf("Hello World!\n");
    printf("My Name is Siddhi\n");

    return 0;
}
```

```
PS C:\Users\sassy\OneDrive\Desktop\siddhi c programs> gcc main.c
PS C:\Users\sassy\OneDrive\Desktop\siddhi c programs> .\a.exe
Can vote, not drink.
PS C:\Users\sassy\OneDrive\Desktop\siddhi c programs>
```

```c
int main()
{
    int age = 20;

    if (age >= 18) {
        if (age >= 21)
            printf("Can drink.\n");
        else
            printf("Can vote, not drink.\n");
    } else {
        printf("Not eligible.\n");
    }

    return 0;
}
```

```
PS C:\Users\sassy\OneDrive\Desktop\siddhi c programs> gcc main.c
PS C:\Users\sassy\OneDrive\Desktop\siddhi c programs> .\a.exe
Grade B
PS C:\Users\sassy\OneDrive\Desktop\siddhi c programs>
```

```c
int main()
{
    int marks = 75;

    if (marks >= 90)
        printf("Grade A");
    else if (marks >= 75)
        printf("Grade B");
    else if (marks >= 50)
        printf("Grade C");
    else
        printf("Grade D");

    return 0;
}
```

```
PS C:\Users\sassy\OneDrive\Desktop\siddhi c programs> gcc main.c
PS C:\Users\sassy\OneDrive\Desktop\siddhi c programs> .\a.exe
Minor
PS C:\Users\sassy\OneDrive\Desktop\siddhi c programs>
```

```c
#include <stdio.h>

int main()
{
    int age = 17;
    const char *msg = (age >= 18) ? "Adult" : "Minor";

    printf("%s\n", msg);

    return 0;
}
```

Problems Output Debug Console Terminal Ports

```
PS C:\Users\sassy\OneDrive\Desktop\siddhi c programs> gcc main.c
PS C:\Users\sassy\OneDrive\Desktop\siddhi c programs> .\a.exe
Negative
PS C:\Users\sassy\OneDrive\Desktop\siddhi c programs>
```

siddhi c programs > C main.c

```c
#include <stdio.h>
int main ()
{
    int n = -5;
    if(n>=0) {
        printf("Positive\n");
    } else {
    printf ("Negative\n");
    }



    return 0;
}

```

```
PS C:\Users\sassy\OneDrive\Desktop\siddhi c programs> gcc main.c
PS C:\Users\sassy\OneDrive\Desktop\siddhi c programs> .\a.exe
You can vote.
PS C:\Users\sassy\OneDrive\Desktop\siddhi c programs>
```

programs > C main.c

```c
#include <stdio.h>
int main ()
{
    int age = 18;
    if (age>=18) {
        printf("You can vote.\n");
    }



    return 0;
}
```

```
Character (2): 2
Float (5.750000): 5.750000
Double (123.456789): 123.456789
Long int (1234567890): 1234567890
String (Hello C): Hello C
Hex (19): 19
Octal (31): 31
Address (0061FF00): 0061FF00
Percent (%): %
PS C:\Users\sassy\OneDrive\Desktop\siddhi c programs>
```

```
          ^~~~~
PS C:\Users\sassy\OneDrive\Desktop\siddhi c programs> gcc main.c
PS C:\Users\sassy\OneDrive\Desktop\siddhi c programs> ./a.exe
PS C:\Users\sassy\OneDrive\Desktop\siddhi c programs> .\a.exe
Integer (25): 25
Unsigned (300): 300
Character (2): 2
Float (5.750000): 5.750000
Double (123.456789): 123.456789
```

```c
#include<stdio.h>
int main () {
    int a =25;
    unsigned int b =300;
    char ch ='2';
    float f =5.75f;
    double d =123.456789;
    long int li =1234567890;
    char str[] = "Hello C";

    printf ("Integer (%d): %d\n",a);
     printf("Unsigned (%u) : %u\n", b);

      printf("Character (%c) : %d \n",ch);
       printf("Float (%f) : %2f\n",f);
        printf("Double (%lf): %6lf\n" , d);
         printf("Long int (%ld): %ld\n",li);

        printf("String (%s) : %s\n",d);

          printf("Hex (%x) : %x\n", a);
           printf("Octal (%o) :%o\n",a);
            printf("Address (%p): %p\n", &a);
             printf("Percent (%%) : %%\n");
             return 0;
}
```