

Name: Siddhi Sunil Khade  
Division: TE3  
Batch: B  
Roll.No: 22

## Experiment 9

### Aim:

To configure Linux FTP server using VSFTPD.

1. Set up anonymous access of FTP server.
2. Enable individual logins and add FTP users with Read- only access.
3. Transfer Files.

### Installing the package: vsftpd

```
osboxes@osboxes: ~  
osboxes@osboxes:~$ sudo apt-get install vsftpd  
[sudo] password for osboxes:  
Reading package lists... Done  
Building dependency tree  
Reading state information... Done  
The following NEW packages will be installed:  
  vsftpd  
0 upgraded, 1 newly installed, 0 to remove and 64 not upgraded.  
Need to get 111 kB of archives.  
After this operation, 361 kB of additional disk space will be used.  
Get:1 http://us.archive.ubuntu.com/ubuntu/ trusty-updates/main vsftpd amd64 3.0.2-1ubuntu2.14.04.1 [111 kB]  
Fetched 111 kB in 1s (72.4 kB/s)  
Preconfiguring packages ...  
Selecting previously unselected package vsftpd.  
(Reading database ... 167462 files and directories currently installed.)  
Preparing to unpack .../vsftpd_3.0.2-1ubuntu2.14.04.1_amd64.deb ...  
Unpacking vsftpd (3.0.2-1ubuntu2.14.04.1) ...  
Processing triggers for man-db (2.6.7.1-1ubuntu1) ...  
Processing triggers for ureadahead (0.100.0-16) ...  
ureadahead will be reprofiled on next reboot  
Setting up vsftpd (3.0.2-1ubuntu2.14.04.1) ...  
vsftpd start/running, process 2578  
Processing triggers for ureadahead (0.100.0-16) ...  
osboxes@osboxes:~$
```

### Changing directory towards etc folder and to edit the vsftpd config file

```
osboxes@osboxes:~$ sudo su  
[sudo] password for osboxes:  
Sorry, try again.  
[sudo] password for osboxes:  
root@osboxes:/home/osboxes# cd /etc  
root@osboxes:/etc# nano vsftpd.conf  
root@osboxes:/etc# nano vsftpd.conf
```

Making the anonymous\_enable from NO → YES

Commenting out the line local\_enable

Uncommenting out the line write\_enable

Saving the changes by → ctrl+O and hitting enter

Exiting by → ctrl+X

```
root@osboxes: /etc
GNU nano 2.2.6 File: vsftpd.conf

anonymous_enable=YES
#
# Uncomment this to allow local users to log in.
#local_enable=YES
#
# Uncomment this to enable any form of FTP write command.
write_enable=YES
#
# Default umask for local users is 077. You may wish to change this to 022,
# if your users expect that (022 is used by most other ftpd's)
#local_umask=022
#
# Uncomment this to allow the anonymous FTP user to upload files. This only
# has an effect if the above global write enable is activated. Also, you will
# obviously need to create a directory writable by the FTP user.
#anon_upload_enable=YES
#
# Uncomment this if you want the anonymous FTP user to be able to create
# new directories.
#anon_mkdir_write_enable=YES

^G Get Help ^O WriteOut ^R Read File ^Y Prev Page ^K Cut Text ^C Cur Pos
^X Exit ^J Justify ^W Where Is ^V Next Page ^U UnCut Text ^T To Spell
```

**Restarting the vsftpd service → service vsftpd restart & Using netstat to check the working of ftp protocol service**

```
root@osboxes:/etc# cd ..
root@osboxes:/# service vsftpd restart
vsftpd stop/waiting
vsftpd start/running, process 3184
root@osboxes:/# netstat -an|grep tcp
tcp        0      0 0.0.0.0:21          0.0.0.0:*           LISTEN
tcp        0      0 127.0.1.1:53       0.0.0.0:*           LISTEN
tcp        0      0 127.0.0.1:631      0.0.0.0:*           LISTEN
tcp        0      0 10.0.2.15:58296    172.217.174.67:443   TIME_WAIT
tcp        0      0 10.0.2.15:39296    34.98.75.36:443      TIME_WAIT
tcp        0      0 10.0.2.15:36510    34.107.221.82:80     TIME_WAIT
tcp        0      0 10.0.2.15:35714    104.18.165.34:443    TIME_WAIT
tcp        0      0 10.0.2.15:53022    52.84.46.134:443     TIME_WAIT
tcp        0      0 10.0.2.15:36304    157.240.16.52:443    ESTABLISHED
tcp        0      0 10.0.2.15:36280    117.18.237.29:80     TIME_WAIT
tcp        0      0 10.0.2.15:41474    142.250.192.68:443   TIME_WAIT
tcp        0      0 10.0.2.15:41446    142.250.192.68:443   TIME_WAIT
tcp        0      0 10.0.2.15:36312    157.240.16.52:443    ESTABLISHED
tcp        0      0 10.0.2.15:57500    172.217.160.163:443  TIME_WAIT
tcp        0      0 10.0.2.15:52488    13.227.214.21:443    ESTABLISHED
tcp        0      0 10.0.2.15:33576    34.215.36.246:443    ESTABLISHED
tcp        0      0 10.0.2.15:43276    142.250.183.110:443  TIME_WAIT
tcp        0      0 10.0.2.15:46542    35.244.181.201:443   ESTABLISHED
tcp        0      0 10.0.2.15:39320    13.227.166.120:443   TIME_WAIT
tcp        0      0 10.0.2.15:36576    172.217.160.202:443  TIME_WAIT
tcp        0      0 10.0.2.15:35668    104.18.165.34:443    TIME_WAIT
root@osboxes:/#
```

**Using ifconfig to get the IP address of the ubuntu system**

**My IP address is: 127.0.0.1**

```

root@osboxes:/# ifconfig
eth0      Link encap:Ethernet  HWaddr 08:00:27:ba:62:88
          inet addr:10.0.2.15  Bcast:10.0.2.255  Mask:255.255.255.0
          inet6 addr: fe80::a00:27ff:feba:6288/64 Scope:Link
          UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
          RX packets:14954 errors:0 dropped:0 overruns:0 frame:0
          TX packets:3663 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:1000
          RX bytes:19378506 (19.3 MB)  TX bytes:347745 (347.7 KB)

lo        Link encap:Local Loopback
          inet addr:127.0.0.1  Mask:255.0.0.0
          inet6 addr: ::1/128 Scope:Host
          UP LOOPBACK RUNNING  MTU:65536  Metric:1
          RX packets:808 errors:0 dropped:0 overruns:0 frame:0
          TX packets:808 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:1
          RX bytes:113938 (113.9 KB)  TX bytes:113938 (113.9 KB)

root@osboxes:/#

```

## Connecting my ip address with ftp and login as anonymous

```

root@osboxes:/# ftp 127.0.0.1
Connected to 127.0.0.1.
220 (vsFTPD 3.0.2)
Name (127.0.0.1:osboxes): anonymous
331 Please specify the password.
Password:
230 Login successful.
Remote system type is UNIX.
Using binary mode to transfer files.
ftp> pwd
257 "/"
ftp> bye
221 Goodbye.
root@osboxes:/#

```

## Making the config file as it is

```

root@osboxes: /etc
GNU nano 2.2.6      File: vsftpd.conf

#
# Allow anonymous FTP? (Disabled by default)
anonymous_enable=NO
#
# Uncomment this to allow local users to log in.
local_enable=YES
#
# Uncomment this to enable any form of FTP write command.
#write_enable=YES
#
# Default umask for local users is 077. You may wish to change this to 022,
# if your users expect that (022 is used by most other ftpd's)
#local_umask=022
#
# Uncomment this to allow the anonymous FTP user to upload files. This only
# has an effect if the above global write enable is activated. Also, you will
# obviously need to create a directory writable by the FTP user.
#anon_upload_enable=YES
#

^G Get Help  ^O WriteOut  ^R Read File  ^Y Prev Page  ^K Cut Text   ^C Cur Pos
^X Exit      ^J Justify   ^W Where Is  ^V Next Page  ^U UnCut Text ^T To Spell

```




## Now, adding a user

```
root@osboxes:/# adduser jainish
Adding user `jainish' ...
Adding new group `jainish' (1001) ...
Adding new user `jainish' (1001) with group `jainish' ...
Creating home directory `/home/jainish' ...
Copying files from `/etc/skel' ...
Enter new UNIX password:
Retype new UNIX password:
passwd: password updated successfully
Changing the user information for jainish
Enter the new value, or press ENTER for the default
    Full Name []: jainish
    Room Number []: 25
    Work Phone []: 1
    Home Phone []: 0
    Other []: 0
Is the information correct? [Y/n] y
root@osboxes:/#
```

```
root@osboxes:/# ftp 127.0.0.1
Connected to 127.0.0.1.
220 (vsFTPd 3.0.2)
Name (127.0.0.1:osboxes): jainish
331 Please specify the password.
Password:
230 Login successful.
Remote system type is UNIX.
Using binary mode to transfer files.
ftp> pwd
257 "/home/jainish"
ftp> mkdir "practical-jainish"
257 "/home/jainish/practical-jainish" created
ftp> bye
221 Goodbye.
root@osboxes:/#
```

**User has been added successfully**



**A directory is successfully created under user**

