



Before tackling the assignment, run the following in a SQL Worksheet in Snowsight.

This code might look both overwhelming and boring (which is a unique combination!), but trust me, copying and pasting this code and just running it is an important step. It will load all the data you need to work for this assignment—and more importantly, it will load the data you'll need for pretty much all of the following assignments!

You don't have to understand it for the moment—by the end of the course, it will make sense. Just go ahead and run it.

And don't worry if this code differs a little bit from the code we ran in the video -- that's on purpose. (For example, we'll use an XL warehouse here, and not the 3XL we used in the video.)

```
USE ROLE accountadmin;

/*--
database, schema and warehouse creation
--*/

-- create tasty_bytes database
CREATE OR REPLACE DATABASE tasty_bytes;

-- create raw_pos schema
CREATE OR REPLACE SCHEMA tasty_bytes.raw_pos;

-- create raw_customer schema
CREATE OR REPLACE SCHEMA tasty_bytes.raw_customer;

-- create harmonized schema
CREATE OR REPLACE SCHEMA tasty_bytes.harmonized;

-- create analytics schema
CREATE OR REPLACE SCHEMA tasty_bytes.analytics;

-- create warehouse for ingestion
CREATE OR REPLACE WAREHOUSE demo_build_wh
```

```

WAREHOUSE_SIZE = 'xlarge'
WAREHOUSE_TYPE = 'standard'
AUTO_SUSPEND = 60
AUTO_RESUME = TRUE
INITIALLY_SUSPENDED = TRUE;

/*--
file format and stage creation
--*/

CREATE OR REPLACE FILE FORMAT tasty_bytes.public.csv_ff
type = 'csv';

CREATE OR REPLACE STAGE tasty_bytes.public.s3load
url = 's3://sfquickstarts/tasty-bytes-builder-education/'
file_format = tasty_bytes.public.csv_ff;

/*--
raw zone table build
--*/

-- country table build
CREATE OR REPLACE TABLE tasty_bytes.raw_pos.country
(
    country_id NUMBER(18,0),
    country VARCHAR(16777216),
    iso_currency VARCHAR(3),
    iso_country VARCHAR(2),
    city_id NUMBER(19,0),
    city VARCHAR(16777216),
    city_population VARCHAR(16777216)
);

-- franchise table build
CREATE OR REPLACE TABLE tasty_bytes.raw_pos.franchise
(
    franchise_id NUMBER(38,0),
    first_name VARCHAR(16777216),
    last_name VARCHAR(16777216),
    city VARCHAR(16777216),
    country VARCHAR(16777216),
    e_mail VARCHAR(16777216),

```

```

    phone_number VARCHAR(16777216)
);

-- location table build
CREATE OR REPLACE TABLE tasty_bytes.raw_pos.location
(
    location_id NUMBER(19,0),
    placekey VARCHAR(16777216),
    location VARCHAR(16777216),
    city VARCHAR(16777216),
    region VARCHAR(16777216),
    iso_country_code VARCHAR(16777216),
    country VARCHAR(16777216)
);

-- menu table build
CREATE OR REPLACE TABLE tasty_bytes.raw_pos.menu
(
    menu_id NUMBER(19,0),
    menu_type_id NUMBER(38,0),
    menu_type VARCHAR(16777216),
    truck_brand_name VARCHAR(16777216),
    menu_item_id NUMBER(38,0),
    menu_item_name VARCHAR(16777216),
    item_category VARCHAR(16777216),
    item_subcategory VARCHAR(16777216),
    cost_of_goods_usd NUMBER(38,4),
    sale_price_usd NUMBER(38,4),
    menu_item_health_metrics_obj VARIANT
);

-- truck table build
CREATE OR REPLACE TABLE tasty_bytes.raw_pos.truck
(
    truck_id NUMBER(38,0),
    menu_type_id NUMBER(38,0),
    primary_city VARCHAR(16777216),
    region VARCHAR(16777216),
    iso_region VARCHAR(16777216),
    country VARCHAR(16777216),
    iso_country_code VARCHAR(16777216),
    franchise_flag NUMBER(38,0),

```

```

    year NUMBER(38,0),
    make VARCHAR(16777216),
    model VARCHAR(16777216),
    ev_flag NUMBER(38,0),
    franchise_id NUMBER(38,0),
    truck_opening_date DATE
);

-- order_header table build
CREATE OR REPLACE TABLE tasty_bytes.raw_pos.order_header
(
    order_id NUMBER(38,0),
    truck_id NUMBER(38,0),
    location_id FLOAT,
    customer_id NUMBER(38,0),
    discount_id VARCHAR(16777216),
    shift_id NUMBER(38,0),
    shift_start_time TIME(9),
    shift_end_time TIME(9),
    order_channel VARCHAR(16777216),
    order_ts TIMESTAMP_NTZ(9),
    served_ts VARCHAR(16777216),
    order_currency VARCHAR(3),
    order_amount NUMBER(38,4),
    order_tax_amount VARCHAR(16777216),
    order_discount_amount VARCHAR(16777216),
    order_total NUMBER(38,4)
);

-- order_detail table build
CREATE OR REPLACE TABLE tasty_bytes.raw_pos.order_detail
(
    order_detail_id NUMBER(38,0),
    order_id NUMBER(38,0),
    menu_item_id NUMBER(38,0),
    discount_id VARCHAR(16777216),
    line_number NUMBER(38,0),
    quantity NUMBER(5,0),
    unit_price NUMBER(38,4),
    price NUMBER(38,4),
    order_item_discount_amount VARCHAR(16777216)
);

```

```

-- customer loyalty table build
CREATE OR REPLACE TABLE tasty_bytes.raw_customer.customer_loyalty
(
    customer_id NUMBER(38,0),
    first_name VARCHAR(16777216),
    last_name VARCHAR(16777216),
    city VARCHAR(16777216),
    country VARCHAR(16777216),
    postal_code VARCHAR(16777216),
    preferred_language VARCHAR(16777216),
    gender VARCHAR(16777216),
    favourite_brand VARCHAR(16777216),
    marital_status VARCHAR(16777216),
    children_count VARCHAR(16777216),
    sign_up_date DATE,
    birthday_date DATE,
    e_mail VARCHAR(16777216),
    phone_number VARCHAR(16777216)
);

/*--
harmonized view creation
--*/

-- orders_v view
CREATE OR REPLACE VIEW tasty_bytes.harmonized.orders_v
AS
SELECT
    oh.order_id,
    oh.truck_id,
    oh.order_ts,
    od.order_detail_id,
    od.line_number,
    m.truck_brand_name,
    m.menu_type,
    t.primary_city,
    t.region,
    t.country,
    t.franchise_flag,
    t.franchise_id,
    f.first_name AS franchisee_first_name,

```

```

    f.last_name AS franchisee_last_name,
    l.location_id,
    cl.customer_id,
    cl.first_name,
    cl.last_name,
    cl.e_mail,
    cl.phone_number,
    cl.children_count,
    cl.gender,
    cl.marital_status,
    od.menu_item_id,
    m.menu_item_name,
    od.quantity,
    od.unit_price,
    od.price,
    oh.order_amount,
    oh.order_tax_amount,
    oh.order_discount_amount,
    oh.order_total
FROM tasty_bytes.raw_pos.order_detail od
JOIN tasty_bytes.raw_pos.order_header oh
    ON od.order_id = oh.order_id
JOIN tasty_bytes.raw_pos.truck t
    ON oh.truck_id = t.truck_id
JOIN tasty_bytes.raw_pos.menu m
    ON od.menu_item_id = m.menu_item_id
JOIN tasty_bytes.raw_pos.franchise f
    ON t.franchise_id = f.franchise_id
JOIN tasty_bytes.raw_pos.location l
    ON oh.location_id = l.location_id
LEFT JOIN tasty_bytes.raw_customer.customer_loyalty cl
    ON oh.customer_id = cl.customer_id;

-- loyalty_metrics_v view
CREATE OR REPLACE VIEW tasty_bytes.harmonized.customer_loyalty_metrics_v
AS
SELECT
    cl.customer_id,
    cl.city,
    cl.country,
    cl.first_name,
    cl.last_name,

```

```

        cl.phone_number,
        cl.e_mail,
        SUM(oh.order_total) AS total_sales,
        ARRAY_AGG(DISTINCT oh.location_id) AS visited_location_ids_array
FROM tasty_bytes.raw_customer.customer_loyalty cl
JOIN tasty_bytes.raw_pos.order_header oh
ON cl.customer_id = oh.customer_id
GROUP BY cl.customer_id, cl.city, cl.country, cl.first_name,
cl.last_name, cl.phone_number, cl.e_mail;

/*--
analytics view creation
--*/

-- orders_v view
CREATE OR REPLACE VIEW tasty_bytes.analytics.orders_v
COMMENT = 'Tasty Bytes Order Detail View'
AS
SELECT DATE(o.order_ts) AS date, * FROM tasty_bytes.harmonized.orders_v o;

-- customer_loyalty_metrics_v view
CREATE OR REPLACE VIEW tasty_bytes.analytics.customer_loyalty_metrics_v
COMMENT = 'Tasty Bytes Customer Loyalty Member Metrics View'
AS
SELECT * FROM tasty_bytes.harmonized.customer_loyalty_metrics_v;

/*--
raw zone table load
--*/

USE WAREHOUSE demo_build_wh;

-- country table load
COPY INTO tasty_bytes.raw_pos.country
FROM @tasty_bytes.public.s3load/raw_pos/country/;

-- franchise table load
COPY INTO tasty_bytes.raw_pos.franchise
FROM @tasty_bytes.public.s3load/raw_pos/franchise/;

-- location table load
COPY INTO tasty_bytes.raw_pos.location

```

```
FROM @tasty_bytes.public.s3load/raw_pos/location/;

-- menu table load
COPY INTO tasty_bytes.raw_pos.menu
FROM @tasty_bytes.public.s3load/raw_pos/menu/;

-- truck table load
COPY INTO tasty_bytes.raw_pos.truck
FROM @tasty_bytes.public.s3load/raw_pos/truck/;

-- customer_loyalty table load
COPY INTO tasty_bytes.raw_customer.customer_loyalty
FROM @tasty_bytes.public.s3load/raw_customer/customer_loyalty/;

-- order_header table load
COPY INTO tasty_bytes.raw_pos.order_header
FROM @tasty_bytes.public.s3load/raw_pos/subset_order_header/;

-- order_detail table load
COPY INTO tasty_bytes.raw_pos.order_detail
FROM @tasty_bytes.public.s3load/raw_pos/subset_order_detail/;

DROP WAREHOUSE demo_build_wh;
```