



This is not mandatory reading, but here's the code we'll run in the "Cloning" video. It may come in handy when you're doing the associated hands-on assignment.

```
---> create a clone of the truck table
CREATE OR REPLACE TABLE tasty_bytes.raw_pos.truck_clone
  CLONE tasty_bytes.raw_pos.truck;

/* look at metadata for the truck and truck_clone tables from the
table_storage_metrics view in the information_schema */
SELECT * FROM TASTY_BYTES.INFORMATION_SCHEMA.TABLE_STORAGE_METRICS
WHERE TABLE_NAME = 'TRUCK_CLONE' OR TABLE_NAME = 'TRUCK';

/* look at metadata for the truck and truck_clone tables from the tables view in the
information_schema */
SELECT * FROM TASTY_BYTES.INFORMATION_SCHEMA.TABLES
WHERE TABLE_NAME = 'TRUCK_CLONE' OR TABLE_NAME = 'TRUCK';

---> insert the truck table into the clone (thus doubling the clone's size!)
INSERT INTO tasty_bytes.raw_pos.truck_clone
SELECT * FROM tasty_bytes.raw_pos.truck;

---> now use the tables view to look at metadata for the truck and truck_clone tables
again
SELECT * FROM TASTY_BYTES.INFORMATION_SCHEMA.TABLES
WHERE TABLE_NAME = 'TRUCK_CLONE' OR TABLE_NAME = 'TRUCK';

---> clone a schema
CREATE OR REPLACE SCHEMA tasty_bytes.raw_pos_clone
  CLONE tasty_bytes.raw_pos;

---> clone a database
CREATE OR REPLACE DATABASE tasty_bytes_clone
  CLONE tasty_bytes;

---> clone a table based on an offset (so the table as it was at a certain interval in
the past)
CREATE OR REPLACE TABLE tasty_bytes.raw_pos.truck_clone_time_travel
  CLONE tasty_bytes.raw_pos.truck AT(OFFSET => -60*10);
```

```
SELECT * FROM tasty_bytes.raw_pos.truck_clone_time_travel;
```