



This is not mandatory reading, but here's the code we'll run in the "Permanent, Transient, and Temporary Tables" video.

```
---> drop truck_dev if not dropped previously
DROP TABLE TASTY_BYTES.RAW_POS.TRUCK_DEV;

---> create a transient table
CREATE TRANSIENT TABLE TASTY_BYTES.RAW_POS.TRUCK_TRANSIENT
  CLONE TASTY_BYTES.RAW_POS.TRUCK;

---> create a temporary table
CREATE TEMPORARY TABLE TASTY_BYTES.RAW_POS.TRUCK_TEMPORARY
  CLONE TASTY_BYTES.RAW_POS.TRUCK;

---> show tables that start with the word TRUCK
SHOW TABLES LIKE 'TRUCK%';

---> attempt (successfully) to set the data retention time to 90 days for the standard
table
ALTER TABLE TASTY_BYTES.RAW_POS.TRUCK SET DATA_RETENTION_TIME_IN_DAYS = 90;

---> attempt (unsuccessfully) to set the data retention time to 90 days for the
transient table
ALTER TABLE TASTY_BYTES.RAW_POS.TRUCK_TRANSIENT SET DATA_RETENTION_TIME_IN_DAYS = 90;

---> attempt (unsuccessfully) to set the data retention time to 90 days for the
temporary table
ALTER TABLE TASTY_BYTES.RAW_POS.TRUCK_TEMPORARY SET DATA_RETENTION_TIME_IN_DAYS = 90;

SHOW TABLES LIKE 'TRUCK%';

---> attempt (successfully) to set the data retention time to 0 days for the transient
table
ALTER TABLE TASTY_BYTES.RAW_POS.TRUCK_TRANSIENT SET DATA_RETENTION_TIME_IN_DAYS = 0;

---> attempt (successfully) to set the data retention time to 0 days for the temporary
table
ALTER TABLE TASTY_BYTES.RAW_POS.TRUCK_TEMPORARY SET DATA_RETENTION_TIME_IN_DAYS = 0;
```

```
SHOW TABLES LIKE 'TRUCK%';
```