



This is not mandatory reading, but here's the code we'll run in the Snowpipe videos.

```
---> create the storage integration
CREATE OR REPLACE STORAGE INTEGRATION S3_role_integration
  TYPE = EXTERNAL_STAGE
  STORAGE_PROVIDER = S3
  ENABLED = TRUE
  STORAGE_AWS_ROLE_ARN = "REMOVED"
  STORAGE_ALLOWED_LOCATIONS = ("s3://intro-to-snowflake-snowpipe/");

---> describe the storage integration to see the info you need to copy over to AWS
DESCRIBE INTEGRATION S3_role_integration;

---> create the database
CREATE OR REPLACE DATABASE S3_db;

---> create the table (automatically in the public schema, because we didn't specify)
CREATE OR REPLACE TABLE S3_table(food STRING, taste INT);

USE SCHEMA S3_db.public;

---> create stage with the link to the S3 bucket and info on the associated storage
integration
CREATE OR REPLACE STAGE S3_stage
  url = ('s3://intro-to-snowflake-snowpipe/')
  storage_integration = S3_role_integration;

SHOW STAGES;

---> see the files in the stage
LIST @S3_stage;

---> select the first two columns from the stage
SELECT $1, $2 FROM @S3_stage;

USE WAREHOUSE COMPUTE_WH;

---> create the snowpipe, copying from S3_stage into S3_table
```

```
CREATE PIPE S3_db.public.S3_pipe AUTO_INGEST=TRUE as  
  COPY INTO S3_db.public.S3_table  
  FROM @S3_db.public.S3_stage;
```

```
SELECT * FROM S3_db.public.S3_table;
```

---> see a list of all the pipes

```
SHOW PIPES;
```

```
DESCRIBE PIPE S3_db.public.S3_pipe;
```

---> pause the pipe

```
ALTER PIPE S3_db.public.S3_pipe SET PIPE_EXECUTION_PAUSED = TRUE;
```

---> drop the pipe

```
DROP PIPE S3_pipe;
```

```
SHOW PIPES;
```