



This is not mandatory reading, but here's the code we'll run in the "Stages and Basic Ingestion" videos. It may come in handy when you're doing the associated hands-on assignment.

```
USE ROLE accountadmin;

---> create tasty_bytes database
CREATE OR REPLACE DATABASE tasty_bytes;

---> create raw_pos schema
CREATE OR REPLACE SCHEMA tasty_bytes.raw_pos;

---> create raw_customer schema
CREATE OR REPLACE SCHEMA tasty_bytes.raw_customer;

---> create harmonized schema
CREATE OR REPLACE SCHEMA tasty_bytes.harmonized;

---> create analytics schema
CREATE OR REPLACE SCHEMA tasty_bytes.analytics;

---> create warehouses
CREATE OR REPLACE WAREHOUSE demo_build_wh
    WAREHOUSE_SIZE = 'xxlarge'
    WAREHOUSE_TYPE = 'standard'
    AUTO_SUSPEND = 60
    AUTO_RESUME = TRUE
    INITIALLY_SUSPENDED = TRUE
COMMENT = 'demo build warehouse for tasty bytes assets';

CREATE OR REPLACE WAREHOUSE tasty_de_wh
    WAREHOUSE_SIZE = 'xsmall'
    WAREHOUSE_TYPE = 'standard'
    AUTO_SUSPEND = 60
    AUTO_RESUME = TRUE
    INITIALLY_SUSPENDED = TRUE
COMMENT = 'data engineering warehouse for tasty bytes';
```

```

USE WAREHOUSE tasty_de_wh;

---> file format creation
CREATE OR REPLACE FILE FORMAT tasty_bytes.public.csv_ff
type = 'csv';

---> stage creation
CREATE OR REPLACE STAGE tasty_bytes.public.s3load
url = 's3://sfquickstarts/frostbyte_tastybytes/'
file_format = tasty_bytes.public.csv_ff;
---> example of creating an internal stage
-- CREATE OR REPLACE STAGE tasty_bytes.public.internal_stage_test;

---> list files in stage
ls @tasty_bytes.public.s3load;

---> country table build
CREATE OR REPLACE TABLE tasty_bytes.raw_pos.country
(
    country_id NUMBER(18,0),
    country VARCHAR(16777216),
    iso_currency VARCHAR(3),
    iso_country VARCHAR(2),
    city_id NUMBER(19,0),
    city VARCHAR(16777216),
    city_population VARCHAR(16777216)
);

---> franchise table build
CREATE OR REPLACE TABLE tasty_bytes.raw_pos.franchise
(
    franchise_id NUMBER(38,0),
    first_name VARCHAR(16777216),
    last_name VARCHAR(16777216),
    city VARCHAR(16777216),
    country VARCHAR(16777216),
    e_mail VARCHAR(16777216),
    phone_number VARCHAR(16777216)
);

---> location table build

```

```

CREATE OR REPLACE TABLE tasty_bytes.raw_pos.location
(
    location_id NUMBER(19,0),
    placekey VARCHAR(16777216),
    location VARCHAR(16777216),
    city VARCHAR(16777216),
    region VARCHAR(16777216),
    iso_country_code VARCHAR(16777216),
    country VARCHAR(16777216)
);

```

---> menu table build

```

CREATE OR REPLACE TABLE tasty_bytes.raw_pos.menu
(
    menu_id NUMBER(19,0),
    menu_type_id NUMBER(38,0),
    menu_type VARCHAR(16777216),
    truck_brand_name VARCHAR(16777216),
    menu_item_id NUMBER(38,0),
    menu_item_name VARCHAR(16777216),
    item_category VARCHAR(16777216),
    item_subcategory VARCHAR(16777216),
    cost_of_goods_usd NUMBER(38,4),
    sale_price_usd NUMBER(38,4),
    menu_item_health_metrics_obj VARIANT
);

```

---> truck table build

```

CREATE OR REPLACE TABLE tasty_bytes.raw_pos.truck
(
    truck_id NUMBER(38,0),
    menu_type_id NUMBER(38,0),
    primary_city VARCHAR(16777216),
    region VARCHAR(16777216),
    iso_region VARCHAR(16777216),
    country VARCHAR(16777216),
    iso_country_code VARCHAR(16777216),
    franchise_flag NUMBER(38,0),
    year NUMBER(38,0),
    make VARCHAR(16777216),
    model VARCHAR(16777216),
    ev_flag NUMBER(38,0),

```

```

franchise_id NUMBER(38,0),
truck_opening_date DATE
);

---> order_header table build
CREATE OR REPLACE TABLE tasty_bytes.raw_pos.order_header
(
  order_id NUMBER(38,0),
  truck_id NUMBER(38,0),
  location_id FLOAT,
  customer_id NUMBER(38,0),
  discount_id VARCHAR(16777216),
  shift_id NUMBER(38,0),
  shift_start_time TIME(9),
  shift_end_time TIME(9),
  order_channel VARCHAR(16777216),
  order_ts TIMESTAMP_NTZ(9),
  served_ts VARCHAR(16777216),
  order_currency VARCHAR(3),
  order_amount NUMBER(38,4),
  order_tax_amount VARCHAR(16777216),
  order_discount_amount VARCHAR(16777216),
  order_total NUMBER(38,4)
);

---> order_detail table build
CREATE OR REPLACE TABLE tasty_bytes.raw_pos.order_detail
(
  order_detail_id NUMBER(38,0),
  order_id NUMBER(38,0),
  menu_item_id NUMBER(38,0),
  discount_id VARCHAR(16777216),
  line_number NUMBER(38,0),
  quantity NUMBER(5,0),
  unit_price NUMBER(38,4),
  price NUMBER(38,4),
  order_item_discount_amount VARCHAR(16777216)
);

---> customer loyalty table build
CREATE OR REPLACE TABLE tasty_bytes.raw_customer.customer_loyalty
(

```

```

customer_id NUMBER(38,0),
first_name VARCHAR(16777216),
last_name VARCHAR(16777216),
city VARCHAR(16777216),
country VARCHAR(16777216),
postal_code VARCHAR(16777216),
preferred_language VARCHAR(16777216),
gender VARCHAR(16777216),
favourite_brand VARCHAR(16777216),
marital_status VARCHAR(16777216),
children_count VARCHAR(16777216),
sign_up_date DATE,
birthday_date DATE,
e_mail VARCHAR(16777216),
phone_number VARCHAR(16777216)
);

```

--> orders_v view

```

CREATE OR REPLACE VIEW tasty_bytes.harmonized.orders_v
AS
SELECT
    oh.order_id,
    oh.truck_id,
    oh.order_ts,
    od.order_detail_id,
    od.line_number,
    m.truck_brand_name,
    m.menu_type,
    t.primary_city,
    t.region,
    t.country,
    t.franchise_flag,
    t.franchise_id,
    f.first_name AS franchisee_first_name,
    f.last_name AS franchisee_last_name,
    l.location_id,
    cl.customer_id,
    cl.first_name,
    cl.last_name,
    cl.e_mail,
    cl.phone_number,
    cl.children_count,

```

```

        cl.gender,
        cl.marital_status,
        od.menu_item_id,
        m.menu_item_name,
        od.quantity,
        od.unit_price,
        od.price,
        oh.order_amount,
        oh.order_tax_amount,
        oh.order_discount_amount,
        oh.order_total
FROM tasty_bytes.raw_pos.order_detail od
JOIN tasty_bytes.raw_pos.order_header oh
    ON od.order_id = oh.order_id
JOIN tasty_bytes.raw_pos.truck t
    ON oh.truck_id = t.truck_id
JOIN tasty_bytes.raw_pos.menu m
    ON od.menu_item_id = m.menu_item_id
JOIN tasty_bytes.raw_pos.franchise f
    ON t.franchise_id = f.franchise_id
JOIN tasty_bytes.raw_pos.location l
    ON oh.location_id = l.location_id
LEFT JOIN tasty_bytes.raw_customer.customer_loyalty cl
    ON oh.customer_id = cl.customer_id;

---> loyalty_metrics_v view
CREATE OR REPLACE VIEW tasty_bytes.harmonized.customer_loyalty_metrics_v
AS
SELECT
    cl.customer_id,
    cl.city,
    cl.country,
    cl.first_name,
    cl.last_name,
    cl.phone_number,
    cl.e_mail,
    SUM(oh.order_total) AS total_sales,
    ARRAY_AGG(DISTINCT oh.location_id) AS visited_location_ids_array
FROM tasty_bytes.raw_customer.customer_loyalty cl
JOIN tasty_bytes.raw_pos.order_header oh
    ON cl.customer_id = oh.customer_id
GROUP BY cl.customer_id, cl.city, cl.country, cl.first_name,

```

```

cl.last_name, cl.phone_number, cl.e_mail;

---> orders_v view
CREATE OR REPLACE VIEW tasty_bytes.analytics.orders_v
COMMENT = 'Tasty Bytes Order Detail View'
AS
SELECT DATE(o.order_ts) AS date, * FROM tasty_bytes.harmonized.orders_v o;

---> customer_loyalty_metrics_v view
CREATE OR REPLACE VIEW tasty_bytes.analytics.customer_loyalty_metrics_v
COMMENT = 'Tasty Bytes Customer Loyalty Member Metrics View'
AS
SELECT * FROM tasty_bytes.harmonized.customer_loyalty_metrics_v;

USE WAREHOUSE demo_build_wh;

---> country table load
COPY INTO tasty_bytes.raw_pos.country
FROM @tasty_bytes.public.s3load/raw_pos/country/;

---> franchise table load
COPY INTO tasty_bytes.raw_pos.franchise
FROM @tasty_bytes.public.s3load/raw_pos/franchise/;

---> location table load
COPY INTO tasty_bytes.raw_pos.location
FROM @tasty_bytes.public.s3load/raw_pos/location/;

---> menu table load
COPY INTO tasty_bytes.raw_pos.menu
FROM @tasty_bytes.public.s3load/raw_pos/menu/;

---> truck table load
COPY INTO tasty_bytes.raw_pos.truck
FROM @tasty_bytes.public.s3load/raw_pos/truck/;

---> customer_loyalty table load
COPY INTO tasty_bytes.raw_customer.customer_loyalty
FROM @tasty_bytes.public.s3load/raw_customer/customer_loyalty/;

---> order_header table load
COPY INTO tasty_bytes.raw_pos.order_header

```

```
FROM @tasty_bytes.public.s3load/raw_pos/order_header/;

---> order_detail table load
COPY INTO tasty_bytes.raw_pos.order_detail
FROM @tasty_bytes.public.s3load/raw_pos/order_detail/;

---> drop demo_build_wh
DROP WAREHOUSE IF EXISTS demo_build_wh;

USE WAREHOUSE TASTY_DE_WH;

SELECT file_name, error_count, status, last_load_time FROM
snowflake.account_usage.copy_history
ORDER BY last_load_time DESC
LIMIT 10;
```