



This is not mandatory reading, but here's the code we'll run in the "Stored Procedures" videos. It may come in handy when you're doing the associated hands-on assignment.

---> list all procedures

```
SHOW PROCEDURES;
```

```
SELECT * FROM TASTY_BYTES_CLONE.RAW_POS.ORDER_HEADER  
LIMIT 100;
```

---> see the latest and earliest order timestamps so we can determine what we want to delete

```
SELECT MAX(ORDER_TS), MIN(ORDER_TS) FROM TASTY_BYTES_CLONE.RAW_POS.ORDER_HEADER;
```

---> save the max timestamp

```
SET max_ts = (SELECT MAX(ORDER_TS) FROM TASTY_BYTES_CLONE.RAW_POS.ORDER_HEADER);
```

```
SELECT $max_ts;
```

```
SELECT DATEADD('DAY', -180, $max_ts);
```

---> determine the necessary cutoff to go back 180 days

```
SET cutoff_ts = (SELECT DATEADD('DAY', -180, $max_ts));
```

---> note how you can use the cutoff\_ts variable in the WHERE clause

```
SELECT MAX(ORDER_TS) FROM TASTY_BYTES_CLONE.RAW_POS.ORDER_HEADER  
WHERE ORDER_TS < $cutoff_ts;
```

```
USE DATABASE TASTY_BYTES;
```

---> create your procedure

```
CREATE OR REPLACE PROCEDURE delete_old()
```

```
RETURNS BOOLEAN
```

```
LANGUAGE SQL
```

```
AS
```

```
$$
```

```
DECLARE
```

```
    max_ts TIMESTAMP;
```

```
    cutoff_ts TIMESTAMP;
```

```

BEGIN
    max_ts := (SELECT MAX(ORDER_TS) FROM TASTY_BYTES_CLONE.RAW_POS.ORDER_HEADER);
    cutoff_ts := (SELECT DATEADD('DAY', -180, :max_ts));
    DELETE FROM TASTY_BYTES_CLONE.RAW_POS.ORDER_HEADER
    WHERE ORDER_TS < :cutoff_ts;
END;
$$
;

SHOW PROCEDURES;

---> see information about your procedure
DESCRIBE PROCEDURE delete_old();

---> run your procedure
CALL DELETE_OLD();

---> confirm that that made a difference
SELECT MIN(ORDER_TS) FROM TASTY_BYTES_CLONE.RAW_POS.ORDER_HEADER;

---> it did! We deleted everything from before the cutoff timestamp
SELECT $cutoff_ts;

```