



This is not mandatory reading, but here's the code we'll run in the Views videos. It may come in handy when you're doing the associated hands-on assignment.

--> create the orders_v view - note the "CREATE VIEW view_name AS SELECT" syntax

```
CREATE VIEW tasty_bytes.harmonized.orders_v
```

```
AS
```

```
SELECT
```

```
    oh.order_id,  
    oh.truck_id,  
    oh.order_ts,  
    od.order_detail_id,  
    od.line_number,  
    m.truck_brand_name,  
    m.menu_type,  
    t.primary_city,  
    t.region,  
    t.country,  
    t.franchise_flag,  
    t.franchise_id,  
    f.first_name AS franchisee_first_name,  
    f.last_name AS franchisee_last_name,  
    l.location_id,  
    cl.customer_id,  
    cl.first_name,  
    cl.last_name,  
    cl.e_mail,  
    cl.phone_number,  
    cl.children_count,  
    cl.gender,  
    cl.marital_status,  
    od.menu_item_id,  
    m.menu_item_name,  
    od.quantity,  
    od.unit_price,  
    od.price,  
    oh.order_amount,  
    oh.order_tax_amount,  
    oh.order_discount_amount,
```

```

        oh.order_total
FROM tasty_bytes.raw_pos.order_detail od
JOIN tasty_bytes.raw_pos.order_header oh
    ON od.order_id = oh.order_id
JOIN tasty_bytes.raw_pos.truck t
    ON oh.truck_id = t.truck_id
JOIN tasty_bytes.raw_pos.menu m
    ON od.menu_item_id = m.menu_item_id
JOIN tasty_bytes.raw_pos.franchise f
    ON t.franchise_id = f.franchise_id
JOIN tasty_bytes.raw_pos.location l
    ON oh.location_id = l.location_id
LEFT JOIN tasty_bytes.raw_customer.customer_loyalty cl
    ON oh.customer_id = cl.customer_id;

```

```

SELECT COUNT(*) FROM tasty_bytes.harmonized.orders_v;

```

```

CREATE VIEW tasty_bytes.harmonized.brand_names
AS
SELECT truck_brand_name
FROM tasty_bytes.raw_pos.menu;

```

```

SHOW VIEWS;

```

```

---> drop a view

```

```

DROP VIEW tasty_bytes.harmonized.brand_names;

```

```

SHOW VIEWS;

```

```

---> see metadata about a view

```

```

DESCRIBE VIEW tasty_bytes.harmonized.orders_v;

```

```

---> create a materialized view

```

```

CREATE MATERIALIZED VIEW tasty_bytes.harmonized.brand_names_materialized
AS
SELECT DISTINCT truck_brand_name
FROM tasty_bytes.raw_pos.menu;

```

```

SELECT * FROM tasty_bytes.harmonized.brand_names_materialized;

```

```

SHOW VIEWS;

```

```
SHOW MATERIALIZED VIEWS;
```

---> see metadata about the materialized view we just made

```
DESCRIBE VIEW tasty_bytes.harmonized.brand_names_materialized;
```

```
DESCRIBE MATERIALIZED VIEW tasty_bytes.harmonized.brand_names_materialized;
```

---> drop the materialized view

```
DROP MATERIALIZED VIEW tasty_bytes.harmonized.brand_names_materialized;
```