Started on	Thursday, 22 August 2024, 10:14 AM
State	Finished
Completed on	Thursday, 22 August 2024, 10:33 AM
Time taken	18 mins 51 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Write a program to take value V and we want to make change for V Rs, and we have infinite supply of each of the denominations in Indian currency, i.e., we have infinite supply of { 1, 2, 5, 10, 20, 50, 100, 500, 1000} valued coins/notes, what is the minimum number of coins and/or notes needed to make the change.

Input Format:

Take an integer from stdin.

Output Format:

print the integer which is change of the number.

Example Input :

64

Output:

4

Explanaton:

We need a 50 Rs note and a 10 Rs note and two 2 rupee coins.

Answer: (penalty regime: 0 %)

```
1   #include<stdio.h>
2   int main(){
3       int cash[]={1,2,5,10,20,50,100,500,1000},V,index=8,count=0;
4       scanf("%d",&V);
5       while(V>0  && index>=0){
6           if(V-cash[index]>0){
7               V-=cash[index];
8               count++;
9           }
10          else{
11              index--;
12          }
13      }
14      printf("%d",count);
15      return 0;
16  }
```

	Input	Expected	Got	
✔	49	5	5	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

◄ Problem 5: Finding Complexity using counter method

Jump to...

2-G-Cookies Problem ►