

- Overview
- Crispy
- Kaart
- Energy
- Activity
- History
- HACS
- Media
- To-do lists

- Settings
- Notifications
- floris
- Energy
- Activity
- History
- HACS
- Media
- To-do lists

Crispy

Moisture · HIGH · 59 W · 23.2°C inside

ON

AUTO

MOISTURE

NO LAUNDRY

59 W

AUTO HIGH

HIGH

BYPASS

40m

RF OK

MOISTURE · HIGH

23.2°C indoor · 22.5°C supply

Intake 21.9°C · ΔT 1.3°C · 59 W

MAX CRISPY

Full automatic attack

NORMAL

Release to HRC

Target

21 °C

21

Cooling strategy

Auto

Auto

LAUNDRY DRY...

Off · ΔAH 3.57

g/m³

Tonight

LITTLE FREE COOLING EXPECTED

0 useful hours · window No useful window

16.8°C

Foreca...

22.9°C

Estima...

19:00

Coldes...

0.0 kWh

Estimated overnig...

0 W

Estimated peak p...

19.8°C

Tomorrow forecast maximum

Decision Engine

CRISPY WANTS HIGH

Moisture control · Thermal MEDIUM · Moisture HIGH · Laundry NONE · Actual HIGH

BASE MEDIUM

ΔT 1.3°C · normal cooling ladder

MOMENTUM NONE

WARMING FAST · +0.12°C/h · pressure off

HEAT MEMORY NONE

+0.2°C since 2h low · low 23.0°C

FINAL THERMAL MEDIUM

Strongest of base · momentum · heat memory

23.2°C

INDOOR · +2.2°C vs target

21.0°C

EFFECTIVE TARGET · heat-memory guard +0.3°C

21.9°C

INTAKE · cold guard 12.0°C

1.3°C

COOLING ADVANTAGE · MEDIUM territory

MOISTURE HIGH

Independent ventilation demand

LAUNDRY NONE

Independent drying demand

Temperature levels & escalation

Base ΔT ladder: <0.5°C = NONE · 0.5–<1.0°C = LOW · 1.0–<3.0°C = MEDIUM · ≥3.0°C = HIGH.

Fast momentum (15 min): s=−0.10°C/h = cooling fast · −0.10–<−0.03 = cooling · −0.03–<+0.04 = stable · +0.04–<+0.10 = warming · ≥+0.10 = warming fast. Sustained warming for 10 min arms **thermal pressure**; it releases after 15 min without qualifying warming.

Heat memory: recent gain is current indoor temperature minus the lowest indoor temperature seen over roughly 2 hours. <0.5°C adds nothing. At ≥0.5°C, Crispy escalates the base demand one useful step (LOW → MEDIUM, MEDIUM → HIGH). At ≥1.0°C, it requests HIGH. Heat-memory escalation only applies above target + 0.3°C, with at least 0.5°C cooling advantage and a safe intake temperature.

Final thermal demand = strongest of Base, Momentum and Heat Memory. Quiet mode caps automatic HIGH to MEDIUM. Moisture and Laundry are then arbitrated independently, and any higher external HRC demand is preserved.

Live Air Path

21.9°

INTAKE

22.5°

A/C

SUPPLY

23.2°

INDOOR

54%

Cool-air delivery

+0.6°C

Duct / unit heat pl...

Air path: Intake is outside air entering the HRC; Supply is what reaches the apartment. Cool-air delivery shows how much of the available temperature advantage reaches the supply. Heat ninkun is warming between intake and supply.

Hourly Weather

Partly cloudy

Forecast Thuis

15.8 °C

Unknown

Fri

11:00 AM

12:00 PM

1:00 PM

2:00 PM

3:00 PM

16.7"

17"

17.3"

17.4"

17.5"

Actual Performance

59 W

Coolin...

-0.15

Apert...

14.7 h

ETA to ...

Removed since 1...

0.06 kWh

This Crispy session

0%

Pre-cool progress

-0.51°C

Apartment drop t...


Performance: Cooling W is estimated thermal heat removal, not electrical use. °C/h is the measured apartment trend. ETA extrapolates the current trend, so it can move sharply as conditions change. kWh accumulates estimated heat.

AC ASSIST MAY HELP

Free cooling is currently not reducing indoor temperature quickly enough for the selected target.

- Settings
- Notifications
- f floriss
- Energy
- Activity
- History
- HACS
- Media
- To-do lists

Last 24 Hours



Hide Advanced Console

Manual RF control · fan/bypass · airflow · dew point ...

Supervisory Control

Quiet Crispy

Cap HIGH ... MED...

Heatwave

Target -0.5°C

Cold Intake Guard

12 C

12

Moisture control

Automatic RH/AH ...

NO EXTERNAL ...

Higher HRC / phys...

Quiet caps automatic HIGH at MEDIUM. Heatwave lowers the effective target by 0.5°C. Cold Intake Guard hands bypass control back to the HRC below its configured minimum.

Manual Fan

LOW

60 min

MED

60 min

HIGH

60 min

Manual fan commands run for 60 minutes and disable automatic Crispy first, so the controller will not immediately fight your override.

Bypass

FORCE OPEN

Manual bypass

AUTO

Release bypass

PHYSICALLY OPEN

Reported mode: on

A WTW normally recovers heat into incoming air. When indoor heat is unwanted and outside is colder, FORCE OPEN bypasses that heat recovery. AUTO hands bypass control back to the HRC.

Humidity & Dew Point

58.0%

Indoor RH

44.0%

Intake RH

12.06 ...

Indoor ...

8.49 g...

Intake ...

3.57 g...

Drying ...

MOISTURE BOO...

RH rate -0.00 %/h

OFF

Baseline 0.0 g/m³

14.5°C

Indoor dew point

8.0°C

Supply above dew ...

Relative humidity is temperature-dependent, so Crispy also calculates absolute humidity. Drying advantage = indoor AH - intake AH: positive means ventilation can export moisture. Moisture control uses hysteresis: 1 supply Mode uses the same

Airflow Engineering

251 m³/h


Supply

173 m³/h

Exhaust

78 m³/h

Reported supply - exhaust



Supply and exhaust are HRC-reported airflow values. Their difference is diagnostic only and should not be read as a measured apartment pressure imbalance.

Moisture & Laundry Laboratory

Absolute humidity · 12h

Indoor AH 12.06 g/m³, Intake AH 8.49 g/m³, Laundry baseline 0.0 g/m³

Drying opportunity · 12h

Indoor minus intake AH 3.57 g/m³

Moisture demand · 12h

Moisture 3, Laundry 0, Final 3

Laundry lab: absolute humidity is actual water content in the air. Positive Drying Opportunity means indoor air contains more water per cubic metre than intake air, so ventilation can export moisture. Laundry baseline is captured when

Controller & RF

DATA HEALTHY

Oldest critical rea...

SYNCED

Expected HIGH · a...

Confirmed HIGH

HIGH 60 @ 10:35:57

DATA HEALTHY means critical telemetry is available and fresh. SYNCED compares Crispy's expected state with what the HRC reports. Command feedback shows the latest RF control

Maintenance & Release

83%

Filter · 150 days

RELEASE EVERY...

Crispy OFF · Bypas...


Filter status comes from HRC telemetry. RELEASE EVERYTHING turns Crispy off and returns bypass control to AUTO.

Flight Recorder

- Settings
- Notifications
- f floriss
- Energy
- Activity
- History
- HACS
- Media
- To-do lists

- Settings
- Notifications
- f floriss
- Energy
- Activity
- History
- HACS

Thermal control · 24h




Flight Recorder: demand levels use 0=NONE, 1=LOW, 2=MEDIUM, 3=HIGH. Thermal Base shows the normal ΔT ladder; Momentum Boost shows sustained heat-rise rejection; Heat-memory Boost shows sustained heat-rise rejection; Heat-memory Boost shows escalation after accumulated temperature.


About Crispy

Crispy is a supervisory controller over the existing HRC. It combines thermal free-cooling, sustained thermal-momentum rejection, recent heat-gain memory, moisture demand and Laundry Drying Mode, while preserving any detected external fan demand that is higher than Crispy's own request. **AUTO** uses the normal Delta-T fan ladder; **MAN** uses the HRC ladder until test phase.

Demand arbitration · 24h



Cooling response · 24h



Apartment momentum · 24h

