HTML

Your First Webpage

***Write the following codes in Notepad and save as Sample.html*

```
<html>
<head>
<title> My First Page </title>
</head>
<body>
Hello Computer Lab<br>
POWI, Jorhat
</body>
</html>
```

POWIET COMPUTER LAB

Structure of HTML

```
<HTML>
    <title></title>
    <head>
        <link> ..... </link>
    </head>
    <body>
        ------------
        ------------
    </body>
</HTML>
```

Head Section

Body Section

tag- HEAD

The HTML <head> element is a container for the following elements: <title>, <style>, <meta>, <link>, <script>, and <base>.

Write the following codes in Notepad and save as **Samplehead.html

```
<html>
<head>
<title> My First Page </title>
</head>
<body>
<h1>Heading 1</h1>
<h2>Heading 2</h2>
<h3>Heading 3</h3>
<h4>Heading 4</h4>
<h5>Heading 5</h5>
<h6>Heading 6</h6>
</body>
```

POMFET COMPUTER LAB

</html>

HTML Styles

The HTML style attribute is used to add styles to an element, such as color, font, size, and more.

The HTML style attribute has the following syntax:

<*tagname* style="property:value;">

The property is a CSS property. The value is a CSS value.

1. Background Color

The CSS background-color property defines the background color for an HTML element.

<body style="background-color:powderblue;">

</body>

2. Text Color.

The CSS color property defines the text color for an HTML element

<h1 style="color:blue;">This is a heading</h1>

** This is a paragraph. **

POLYTECHNIC COMPUTER LAB

3. Fonts

The CSS font-family property defines the font to be used for an HTML element

```
<h1 style="font-family:verdana;">This is a heading </h1>
<p style="font-family:courier;">This is a paragraph. </p>
```

4. Text Size

The CSS font-size property defines the text size for an HTML element:

```
<h1 style="font-size:300%;">This is a heading</h1>
<p style="font-size:160%;">This is a paragraph.</p>
```

Write the following codes in Notepad and save as* ***SampleStyle.html

```
<html>
<body style="background-color:powderblue;">

<p>Prince Of Wales</p>
<p style="color:red;">Institute of Engineering &
Technology</p>
<p style="color:blue;">Jorhat- 785001</p>
<p style="font-size:50px;">Assam</p>

</body>
```

POWIET COMPUTER LAB

```
</html>
```

Write the following codes in Notepad and save as* ***<u>SampleStyle123.html</u>

```
<html>
<head>
<title>Sample HTML Page </title>
<style>
body {background-color: powderblue;}
h1 {color: red;}
h2 {color: blue;}
h3 {color: red;}
h4 {color: blue;}
h5 {color: red;}
h6 {color: blue;}
p {color: red;}
</style>
</head>
```

POWIET COMPUTER LAB

```
<body>
<h1>This is a Heading 1</h1>
<h2>Heading 2</h2>
<h3>Heading 3</h3>
<h4>Heading 4</h4>
<h5>Heading 5</h5>
<h6>Heading 6</h6>

<p>This is a sample paragraph.</p>
<p>The landmark 73rd Amendment to the
Constitution of India has definitely
empowered women in terms of numbers.
The vision was that these women –
headed councils would bring greater
transparency and governance.</p>

</body>
</html>
```

POWER COMPUTER LAB

HTML Formatting Elements

Formatting elements were designed to display special types of text:

<b> - Bold text

<i> - Italic text

 - Emphasized text

<mark> - Marked text

<small> - Smaller text

<del> - Deleted text

<ins> - Inserted text

<sub> - Subscript text

<sup> - Superscript text

POWER COMPUTER LAB

HTML Display

HTML text displayed on large or small screens, and resized windows will create different results.

Any extra spaces or extra lines in HTML code, thhe browser will automatically remove all extra spaces and lines when the HTML page is displayed.

Write the following codes in Notepad and save as* ***Sampletext.html

```
<html>
<body>
<p>
This paragraph
contains a lot oflines
in the source code,
but the browser
ignores it.
</p>
<p>
This paragraph
contains a lot ofspaces
in the source code,
```

POWIET COMPUTER LAB

but the browser

ignores it.

</p>

The number of lines in a paragraph depends on the size of the browser window. If you resize the browser window, the number of lines in this paragraph will change.

The HTML <pre> element defines preformatted text.

The text inside a <pre> element is displayed in a fixed-width font (usually Courier), and it preserves both spaces and line breaks:

**** Add the following codelines to the*Sampletext.html*** inside <body> section.

<pre>

My Bonnie lies over the ocean.

My Bonnie lies over the sea.

My Bonnie lies over the ocean.

Oh, bring back my Bonnie to me.

</pre>

</body>

</html>

POLYTECHNIC COMPUTER LAB

HTML Tables

A table in HTML consists of table cells inside rows and columns.

Table headers are defined with **<th>** elements. Each **<th>** element represents a table cell.

<tr> is a tag that tells the browser to begin a new row in the table. Anything in between the opening tag <tr> and the closing tag </tr> constitutes a single row.

Each table cell is defined by a <td> and a </td> tag. <td> stands for table data. Everything between <td> and </td> is the content of a table cell.

*Write the following codes in Notepad and save as**Sample.html***

```
<html>
<style>
table, th, td {
border:1px solid black;
}
</style>
<body>
<table style="width:100%">
<tr>
```

POWIET COMPUTER LAB

```
<th>Name</th>
<th>Branch</th>
<th>Semister</th>
</tr>
<tr>
<td>Amlan</td>
<td>Civil</td>
<td>2nd</td>
</tr>
<tr>
<td>Binit</td>
<td>Mechanical</td>
<td>4th</td>
</tr>
</table>
</body>
</html>
```

POWER COMPUTER LAB

List

OL (Ordered List)& UL (Unordered List)

```
<html>
<body>

<h1>The ol and ul elements</h1>

<p>The ol element defines an ordered list:</p>
<ol>
<li>Coffee</li>
<li>Tea</li>
<li>Milk</li>
</ol>

<p>The ul element defines an unordered list:</p>
<ul>
<li>Coffee</li>
<li>Tea</li>
<li>Milk</li>
</ul>

</body>
</html>
```

POWIET COMPUTER LAB

FORM

```
<html>
<body>

<h1>The form element</h1>

<form action="/action_page.php">
<label for="fname">First name:</label>
<input type="text" id="fname" name="fname"><br><br>
<label for="lname">Last name:</label>
<input type="text" id="lname" name="lname"><br><br>
<input type="submit" value="Submit">
</form>

<p>Click the "Submit" button and the form-data will be sent to a page on the
server called "action_page.php".</p>

</body>
</html>
```

NB: server part codeline(action_page.php) are not part of called HTML

POWIET COMPUTER LAB

CSS(Cascading Style Sheets)

CSS saves a lot of work. It can control the layout of multiple web pages all at once.

Cascading Style Sheets (CSS) is used to format the layout of a webpage.

With CSS, you can control the color, font, the size of text, the spacing between elements, how elements are positioned and laid out, what background images or background colors are to be used, different displays for different devices and screen sizes, and much more

CSS can be added to HTML documents in 3 ways:

Inline - by using the style attribute inside HTML elements

POWIET COMPUTER LAB

Internal - by using a <style> element in the <head>section

External - by using a <link> element to link to an external CSS file

The most common way to add CSS, is to keep the styles in external CSS files.

External CSS

An external style sheet is used to define the style for many HTML pages.

To use an external style sheet, add a link to it in the <head> section of each HTML page:

Write the following codes in Notepad and save as **Sample.html

```
<html>
<head>
<link rel="stylesheet" href="styles.css">
</head>
```

POWIET COMPUTER LAB

```
<body>

<h1>H.R.H The Prince Of Wales Instt.</h1>
<p>JORHAT</p>

</body>
</html>
```

Write the following codes in Notepad and save as **styles.css

```
body {
background-color: powderblue;
}
h1 {
color: blue;
}
p {
color: red;
```

POWIET COMPUTER LAB

}

Hyperlink :

The HTML <a> tag defines a hyperlink. It has the following syntax:

<a href="url">link text</a>

***Write the following codes in Notepad and save as* <u>**Samplehyper.html**</u>

<html>

<body>

<h2>The href Attribute</h2>

HTML links are defined with the a tag. The link address is specified in the href attribute:

POWIET COMPUTER LAB

```
<a href="https://powietjrt.in">Visit POWIET Website</a>


</body>
</html>
```

Linking Image.

```
<html>
<body>


<h2>The src Attribute</h2>
<p>HTML images are defined with the img tag, and the filename of the image source is specified in the src attribute:</p>


<a href="https://powietjrt.in" Visit POWIET Website>
<imgsrc="C:\Users\HP\Pictures\himanta.jpeg" width="500" height="600"></a>
```

POWIET COMPUTER LAB

```
</body>
</html>
```

POWIET COMPUTER LAB