

# BREADTH-FIRST AND DEPTH FIRST SEARCH

Data Structures and Algorithms  
Waheed Iqbal

---




Department of Data Science, FCIT  
University of the Punjab, Lahore, Pakistan

# Credit


- These notes contain material from Chapter 22 of Cormen, Leiserson, Rivest, and Stein (3rd Edition).
- Lecture notes of Prof. Constantinos Daskalakis of MIT.

# Tree vs Graph

- A **tree data structure** is a **hierarchical** data structure that consists of **nodes** connected by edges. Each node can have multiple child nodes, but only one parent node.
- A graph data structure is a **collection of nodes** (also called **vertices**) and **edges** that connect them. Nodes can represent entities, such as people, places, or things, while edges represent relationships between those entities.



Tree




Graph

# Graph Representation


- Adjacency list and adjacency matrix may use to represent a graph  $G(V, E)$ ; where  $V$  and  $E$  represents vertices and edges respectively
- A graph could be directed or undirected
- **Sparse Graph:** number of edges ( $E$ ) are minimal ( $|E|$  is much less than  $|V^2|$ )
- **Dense Graph:** number of edges ( $E$ ) are close to maximum possible edges minimal ( $|E|$  is close to  $|V^2|$ )

# Undirected Graph



**Figure 22.1** Two representations of an undirected graph. (a) An undirected graph  $G$  with 5 vertices and 7 edges. (b) An adjacency-list representation of  $G$ . (c) The adjacency-matrix representation of  $G$ .

# Directed Graph






**Figure 22.2** Two representations of a directed graph. (a) A directed graph  $G$  with 6 vertices and 8 edges. (b) An adjacency-list representation of  $G$ . (c) The adjacency-matrix representation of  $G$ .

# Graph Representation in Python

```
# Define the graph as a dictionary
graph = {
    1: [2, 3],
    2: [1, 3, 4],
    3: [1, 2, 4],
    4: [2, 3]
}
```

```
# Define the adjacency matrix
adj_matrix = [
    [0, 1, 1, 0],
    [1, 0, 1, 1],
    [1, 1, 0, 1],
    [0, 1, 1, 0]
]
```

# Graphs in Action






# Breadth-First Search (BFS)

- One of the simplest algorithm for searching a graph
- Given a graph  $G = (V, E)$  and a distinguished **source vertex**  $s$ , **breadth-first** search systematically explores the edges of  $G$  to “discover” every vertex that is reachable from  $s$
- It computes the distance (smallest number of edges) from  $s$  to each reachable vertex

# Breadth-First Search (Cont.)

## Algorithm



BFS( $G, s$ )

```

1  for each vertex  $u \in G.V - \{s\}$ 
2       $u.color = \text{WHITE}$ 
3       $u.d = \infty$ 
4       $u.\pi = \text{NIL}$ 
5   $s.color = \text{GRAY}$ 
6   $s.d = 0$ 
7   $s.\pi = \text{NIL}$ 
8   $Q = \emptyset$ 
9  ENQUEUE( $Q, s$ )
10 while  $Q \neq \emptyset$ 
11      $u = \text{DEQUEUE}(Q)$ 
12     for each  $v \in G.Adj[u]$ 
13         if  $v.color == \text{WHITE}$ 
14              $v.color = \text{GRAY}$ 
15              $v.d = u.d + 1$ 
16              $v.\pi = u$ 
17             ENQUEUE( $Q, v$ )
18      $u.color = \text{BLACK}$ 
    
```

# Breadth-First Search (Cont.)

## Analysis

- Enqueueing and dequeuing take  $O(1)$
- Total time devoted to queue operations take  $O(V)$
- Total time scanning adjacency lists is  $O(E)$
- Total running time of the BFS procedure is  $O(V + E)$

# Breadth-First Search (Cont.)

## Shortest Path


- The procedure BFS builds a breadth-first tree as it searches the graph
- Shortest-path from **s** to **v** as the minimum number of edges in any path from vertex **s** to vertex **v**;

PRINT-PATH( $G, s, v$ )


```
1  if  $v == s$ 
2      print  $s$ 
3  elseif  $v.\pi == \text{NIL}$ 
4      print “no path from”  $s$  “to”  $v$  “exists”
5  else PRINT-PATH( $G, s, v.\pi$ )
6      print  $v$ 
```

# Depth-first Search (DFS)


- Depth-first search explores edges out of the most recently discovered vertex that still has unexplored edges leaving it.
- Once all of  $v$ 's edges have been explored, the search “backtracks” to explore edges leaving the vertex from which was discovered.
- This process continues until we have discovered all the vertices that are reachable from the original source vertex.




(a)




(b)




(c)




(d)




(e)




(f)




(g)




(h)




(i)




(j)




(k)




(l)




(m)



(n)



(o)



(p)

## DFS(G)

```

1  for each vertex  $u \in G.V$ 
2       $u.color = \text{WHITE}$ 
3       $u.\pi = \text{NIL}$ 
4   $time = 0$ 
5  for each vertex  $u \in G.V$ 
6      if  $u.color == \text{WHITE}$ 
7          DFS-VISIT( $G, u$ )

```


## DFS-VISIT( $G, u$ )

```


1   $time = time + 1$ 
2   $u.d = time$ 
3   $u.color = \text{GRAY}$ 
4  for each  $v \in G.Adj[u]$ 
5      if  $v.color == \text{WHITE}$ 
6           $v.\pi = u$ 
7          DFS-VISIT( $G, v$ )
8   $u.color = \text{BLACK}$ 
9   $time = time + 1$ 
10  $u.f = time$ 

```







(a)




(b)




(c)




(d)




(e)




(f)




(g)




(h)




(i)




(j)




(k)




(l)




(m)



(n)



(o)



(p)

DFS(*G*)

```

1  for each vertex  $u \in G.V$ 
2       $u.color = WHITE$ 
3       $u.\pi = NIL$ 
4   $time = 0$ 
5  for each vertex  $u \in G.V$ 
6      if  $u.color == WHITE$ 
7          DFS-VISIT( $G, u$ )
  
```

DFS-VISIT( $G, u$ )

```

1   $time = time + 1$ 
2   $u.d = time$ 
3   $u.color = GRAY$ 
4  for each  $v \in G.Adj[u]$ 
5      if  $v.color == WHITE$ 
6           $v.\pi = u$ 
7          DFS-VISIT( $G, v$ )
8   $u.color = BLACK$ 
9   $time = time + 1$ 
10  $u.f = time$ 
  
```


- DFS is  $O(V)$  exclusive of DFS-VISIT
- DFS-VISIT is  $O(E)$
- The running time of DFS is therefore  $O(V+E)$

# Tradeoffs

- Solving Rubik's cube?
  - BFS gives shortest solution
- Robot exploring a building?
  - Robot can trace out the exploration path
  - Just drops markers behind
- Only difference is “next vertex” choice
  - BFS uses a queue
  - DFS uses a stack (recursion)



# Topological Sort



TOPOLOGICAL-SORT( $G$ )

- 1 call DFS( $G$ ) to compute finishing times  $v.f$  for each vertex  $v$
- 2 as each vertex is finished, insert it onto the front of a linked list
- 3 **return** the linked list of vertices

