

Specifications Platinum Beam 5R PRO

- Philips MSD Platinum 5R Lamp - 3,000 Hour Average Life*

*Applies to Philips™ 5R lamps with a production date of February 25, 2015, or later.

Actual lamp life may vary depending on several factors including but not limited to: environmental conditions, power/voltage, usage patterns (on-off cycling), control, and dimming.

- 56230 Lux @ 2.5m @2.5°
- 2.5° beam angle
- Built in EWDMX receiver for wireless DMX (Not compatible with E-FLY)
- No need for cleaning or adjustment of reflector or lamp
- All lenses are anti-reflection coated
- 1 color wheel with total 12 colors + white
- Variable speed color scrolling both directions (rainbow)
- 1 gobo wheels with 8 interchangeable (quickout)
- Gobo wheel: 8 indexable, rotating gobos plus open
- Variable speed gobo scrolling in both directions
- Gobo Size: 14.0mm outside, 6mm image diameter
- Rotating, indexing prism: 8-facet
- Macro-function for rotating gobo/prism combinations
- Variable Frost Filter (Hybrid effect for Wash)
- Dual flag mechanical dimming system
- Variable speed strobe effect

- Preset variable/random strobe and dimming pulse effects
- Automatic Pan / Tilt position correction
- Maximum Pan-movement 630° or 540°/ 16 bit
- Maximum Tilt-movement 265° / 16 bit
- 3 Phase motors for fast, accurate Pan / Tilt positioning
- Vector Mode with blackout MIB function
- Battery powered and colored LCD Display
- 16 DMX channels USITT DMX-512 (16-bit resolution)
- Customizable DMX channel assignment
- DMX, stand-alone, Primary/Secondary, sound activated mode
- DMX recorder and edit function integrated
- Software update via DMX, using optional E-Loader
- 3-pin and 5-Pin XLR serial input/output
- With Wired Digital Communication Network
- Fan cooled - fans regulated automatic or DMX
- Constant temperature readout / management function
- DB rating @ 1M = 55.73db
- 2 x 1/4 turn fastening Omega Clamps
- Electronic ballast and power supply
- Power consumption: 338W max.
- Voltage: AC 100V ~ 240V 50/60Hz

- Dimensions (LxWxH): 360x330x470 mm

- Weight: 14.5 kg

- CE | cETLus

Specifications and documentation subject to change without notice.