



COLORado 1 Quad

A compact and robust IP65-rated wash light featuring fourteen 5W RGBW LEDs that produce a powerful and controlled beam of vibrant color. Perfect for a wide range of indoor and outdoor applications, including stage, architectural, and event lighting where a durable, all-weather wash fixture is required.

- Delivers 2,839 lumens of vibrant RGBW color mixing from its fourteen 5W LEDs.
- Produces a tight 14.1° beam angle for controlled and precise wash effects.
- Offers a wide color temperature range from 2800 K to 10,000 K for flexible white light control.
- Features five selectable dimming curves for smooth, seamless fades in any application.
- Built with IP-rated power and data connectors for reliable all-weather operation.
- Supports DMX and RDM with multiple channel profiles for versatile programming flexibility.

SPECIFICATIONS

Optical

Light Source: 14 LEDs (quad-color RGBW) 5 W, (350 mA), 50,000 hours life expectancy.

Color Temperature (range): 2800 to 10,000 K

Beam Angle: 14.1°

Field Angle: 27.2°

Lumens: 2839

Illuminance (total): 1385 lux @ 5 m

Dynamic Effects

Dimmer: Electronic

Shutter/Strobe: Electronic

Strobe Rate: 0 to 14 Hz

Standalone Color Mixing: Yes

Color Temperature Presets: Yes

Dim Modes: 5

Dim Curves: 4

Built-in Automated Programs: Yes

Customizable Programs: Yes

Recall Custom Programs: Yes

Construction / Physical

Dimensions: 11.96 x 9.96 x 7.95 in (304 x 246 x 202mm)

Weight: 9.8 lb (4.5 kg)

Exterior Color: Black

Housing Material: Aluminum die-cast

Accessory Holder/Gel Frame Size: 7.5 in (191 mm)

Connections

Power Connection: Edison (Local) plug to Seetronic Powerkon IP65

Power Input: Seetronic Powerkon IP65

Power Output: Seetronic Powerkon IP65

Data Connectors: 5-pin IP65 XLR

Cable Length (power): 5 ft (1.5 m)

Control

Control Protocol: DMX, RDM

DMX Channels: 4, 5, 6, 7, 9, 10, 13 or 15

Modes/Personalities (RGB): 3 personalities (TOUR, TR16, AR1.D)

Modes/personalities (RGBW): 6 personalities (ARC.2, AR2.D, AR2.S, SSP, 16Bit, 8Bit)

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power Linking: 10 units @ 100 V; 13 units @ 120 V; 22 units @ 208 V; 25 units @ 230 V; 25 units @ 240 V

Power and Current: 109 W, 0.892 A @ 120 V, 60 Hz

Power and Current: 110 W, 0.529 A @ 208 V, 60 Hz

Power and Current: 112 W, 0.492 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET

IP Rating: IP65, outdoor/wet, with pressure equalizing M12 GORE valve

Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN
Neutrik TRUE1 power linking cables
5-pin IP Rated DMX Cables
Color Blending Filters: DF60X1D

What's Included

COLORado 1 Quad
Seetronic Powerkon IP65 power cord
Gel frame holder (7.5 in/191 mm accessories)