



COLORado 2 Solo

A versatile indoor/outdoor wash light featuring three 40W RGBW LEDs to project a fully homogenized beam with a fast, smooth zoom and precision optics. With silent, convection-cooled operation and an IP-rated design, it is ideal for applications ranging from quiet theatrical stages to large outdoor festival productions.

- Projects a powerful, even wash from three 40W RGBW LEDs with superior color mixing.
- Delivers a wide 5° to 42° zoom range for flexible beam shaping and coverage.
- Operates silently with a fanless, convection-cooled design ideal for noise-sensitive environments.
- Features selectable color temperature presets from 3200 K to 10000 K for white balancing.
- Provides selectable dimming curves and multiple DMX personalities for enhanced programming versatility.
- Allows for simple power linking of up to 23 units for streamlined setups.

SPECIFICATIONS

Optical

Light Source: 3 LEDs (quad-color RGBW) 40 W, (2.5 A), 50,000 hours life expectancy

Beam Angle: 5° to 27°

Field Angle: 7° to 42°

Zoom Range: 5° to 42°

Illuminance:

Illuminance (5°): 9,720 lux @ 5 m

Illuminance (27°): 318 lux @ 5 m

Selectable PWM: 600 Hz, 1200 Hz, 2000 Hz, 2400 Hz, 6000 Hz, 25,000 Hz

Dynamic Effects

Dimmer: Electronic

Shutter/Strobe: Electronic

Zoom: Motorized

Strobe Rate: 0 to 25 Hz

Standalone Color Mixing: Yes

Color Temperature Presets: Yes

Dim Modes: 5

Built-in Automated Programs: Yes

Customizable Programs: Yes

Recall Custom Programs: Yes

Construction / Physical

Dimensions: 8.26 x 10.7 x 15.2in (210 x 274 x 387 mm)

Weight: 16.2lb (7.3kg)

Exterior Color: Black

Housing Material: Aluminum die-cast

Accessory Holder/Gel Frame Size: 7.5 in (190 mm)

Connections

Power Connection: Edison (Local) plug to Seetronic Powerkon IP65

Power Input: Seetronic Powerkon IP65

Power Output: Seetronic Powerkon IP65

Data Connectors: 3- and 5-pin IP65 XLR

Cable Length (power): 5 ft (1.5 m)

Control

Control Protocol: DMX, RDM

DMX Channels: 9, 12 or 17

Modes/Personalities: 5 personalities (HSIC, SSP, TOUR, TR16, STD.Y)

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power Linking: 12 units @ 120 V; 21 units @ 208 V; 23 units @ 230 V

Power and Current: 130 W, 1.11 A @ 120 V, 60 Hz

Power and Current: 124 W, 0.63 A @ 208 V, 60 Hz

Power and Current: 123 W, 0.57 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET

IP Rating: IP65, outdoor/wet, with pressure equalizing M12 GORE® valve

Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN

Neutrik TRUE1 power linking cables

5-pin DMX Cables

Color Blending Filters: DF60X1D

Ovation 7.5" Barndoor - IP

Ovation F 7.5" Barndoor

What's Included

COLORado 2 SOLO

Seetronic Powerkon IP65 power cord