

# COLORado Solo Batten 4

A compact and robust IP65-rated RGBAW LED batten featuring four individually-controlled, homogenized cells for creating seamless color washes or dynamic pixel-mappable effects. Built for the rigors of touring, festivals, installations, and theatrical productions, this versatile fixture excels in any application requiring a powerful linear wash or eye-candy effect.



- Utilizes 48 RGBAW LEDs across four cells for completely homogenized, shadow-free color mixing.
- Features an IP65-rated housing with IP power, DMX, and Ethernet connections for outdoor use.
- Delivers a wide color temperature range with selectable presets from 1800K to 8000K.
- Supports DMX, RDM, Art-Net, and sACN protocols for versatile system integration.
- Offers five selectable dimming curves for smooth fades and enhanced programming versatility.
- Provides a native 18° beam angle, expandable to 35° with an optional filter.

## SPECIFICATIONS

### Optical

**Light Source:** 48 LEDs (8 red, 8 green, 8 blue, 8 amber, 16 white) 3 W, (612 mA) 50,000 hours life expectancy

**Color Temperature (range):** 1800 to 8000 K

**CRI (3200 K):** 77.2

**Installed Optics:** 18°

**Beam Angle (Horizontal):** 18°

#### Beam Angle:

**(Horizontal w/ Filter):** 35°

**(Vertical):** 17°

**(Vertical w/ Filter):** 16°

**Field Angle (Horizontal):** 34°

#### Field Angle:

**(Horizontal w / Filter):** 66°

**(Vertical):** 30°

**(Vertical w / Filter):** 32°

**Lumens:** 3,730

**Illuminance (total):** 1,270 lux @ 5 m

**Illuminance w/ Filter (total):** 432 lux @ 5 m

**Selectable PWM:** 600, 1,200, 2,000, 4,000, 6,000, 25,000

### Dynamic Effects

**Dimmer:** Electronic

**Shutter/Strobe:** Electronic

**Strobe Rate:** 0 to 25Hz

**Standalone Color Mixing:** Yes

**Color Temperature Presets:** Yes

**Dim Modes:** 5

**Built-in Automated Programs:** Yes

**Customizable Programs:** Yes

**Recall Custom Programs:** Yes

### Construction / Physical

**Dimensions:** 14.65 x 9.06 x 9.96 in (372 x 230 x 253 mm)

**Dimensions (shipping size):** 17.32 x 8.85 x 13.58 in (440 x 225 x 345 mm)

**Weight:** 17.2 lb (7.8 kg)

**Weight (shipping weight):** 20.50 lb (9.3 kg)

**Exterior Color:** Black

**Housing Material:** Aluminum die-cast

**Accessory Holder/Gel Frame Size:** 13.5 x 3.81 in (342.9 x 97 mm)

### Connections

**Power Connection:** Edison (Local) plug to Seetronic Powerkon IP65

**Power Input:** Seetronic Powerkon IP65

**Power Output:** Seetronic Powerkon IP65

**Data Connectors:** 5-pin IP65 XLR, Seetronic etherCON IP65

**Cable Length (power):** 5 ft (1.5 m)

## Control

**Control Protocol:** Art-Net, DMX, Art-Net to DMX, sACN, RDM

### DMX Channels:

**1 Cell:** 3, 4, 5, 8, 8, 9, 10, 10, 13, 16

**4 Cell:** 12, 16, 20, 27, 29, 31, 35, 40, 56

### Art-Net Channels:

**1 Cell:** 3, 4, 5, 8, 8, 9, 10, 10, 13, 16

**4 Cell:** 12, 16, 20, 27, 29, 31, 35, 40, 56

**Modes/Personalities:** 19 personalities

## Electrical

**Input Voltage:** 100 to 240 VAC, 50/60 Hz (auto-ranging)

**Power Linking:** 13 units @ 120 V; 24 units @ 208 V; 25 units @ 230 V

**Power and Current:** 114 W, 0.990 A @ 120 V, 60 Hz [4.2 A inrush]

**Power and Current:** 116 W, 0.558 A @ 208 V, 60 Hz [3.60 A inrush]

**Power and Current:** 116 W, 0.538 A @ 230 V, 50 Hz [2.6 A inrush]

**Power and Current (resting):** 10 W, 0.09 A @ 120 V, 60 Hz

**Power and Current (resting):** 23 W, 0.11 A @ 208 V, 60 Hz

**Power and Current (resting):** 26 W, 0.11 A @ 230 V, 50 Hz

## Certifications / Qualifications

**Certifications:** CE, MET, FCC

**IP Rating:** IP65, temporary outdoor/wet use

**Temperature (Ambient):** -4 °F to 113 °F (-20 °C to 45 °C)

## Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN

Neutrik TRUE1 power linking cables

5-pin DMX Cables

Ethercon Cables

Colorado Solo Batten 4 Barndoor

## What's Included

COLORADO SOLO BATTEN 4, with glare shield

Seetronic Powerkon IP65 power cord

Wall Wash Filter

Omega Brackets

Quick Reference Guide