

ÉPIX Strip IP 50

The ÉPIX Strip IP 50 is an IP65 outdoor-rated, half-meter pixel-mapping LED strip fixture featuring 50 individually controlled LEDs for creating versatile visual effects. Its compact and weatherproof design is ideal for adding linear lighting details to stages, architectural elements, and outdoor installations, particularly in tight spaces.

- Features 50 tri-color RGB SMD 5050 LEDs with a high output of 8,640 NITS.
- Includes three interchangeable filters for diffused, rounded, or high-contrast black stealth looks.
- Offers a wide 160° viewing angle with milky filters for broad, even coverage.
- Supports Art-Net, Kling-Net, and sACN for versatile integration into professional control systems.
- Provides flicker-free S-PWM dimming control for clean on-camera and broadcast applications.
- Powered and controlled via the ÉPIX Drive 2000 IP for simplified system integration.



SPECIFICATIONS

Optical

Light Source: 50 LEDs (tri-color RGB) SMD 5050, 50,000 hours life expectancy

Viewing Angle:

With installed Square Milky Filter: 160°

With optional Round Milky Filter: 160°

With optional Black Stealth Filter: 125°

Illuminance:

Open: 8,640 NITS

Square Milky Filter (installed): 2,470 NITS

Black Stealth Filter (included): 1,455 NITS

Round Milky Filter (included): 1,360 NITS

Pixels: 50 x 1

Pixel Pitch: 10 mm

Refresh Rate: 4,800 Hz (S-PWM)

Construction / Physical

Dimensions (with installed Square Milky Filter): 19.68 x 1.33 x 3.93 in (500 x 34 x 100 mm)

Dimensions: (with included Black Stealth Filter) 19.68 x 1.33 x 3.46 in (500 x 34 x 88 mm)

Dimensions (with included Round Milky Filter): 19.68 x 1.77 x 5.03 in (500 x 45 x 128 mm)

Weight: 3.4 lb (1.5 kg)

Exterior Color: Black

Housing Material: Aluminum

Connections

Data Connectors: IP-65 4-pin XLR

Physical Linking: 20 inline ÉPIX Strip IP per port of Drive 2000 IP

Minimum required device linking cable size: 4 conductor (2 x 14 AWG, 2 x 16 AWG)

Max. Cable Lengths (Shielded):

Between ÉPIX Drive 2000 IP and first fixture: 65 ft (20 m)

Between fixtures: 60 ft (18 m)

Total (Drive to last fixture): 210 ft (64 m)

Max. Cable Lengths (Unshielded):

Between ÉPIX Drive 2000 IP and first fixture: 150 ft (45 m)

Between fixtures: 100 ft (30 m)

Total (Drive to last fixture): 300 ft (91 m)

Control

Control Protocol: Art-Net, Kling-Net, sACN

Control Channels Art-net, sACN: 7, 15, 30, 75, or 150

Electrical

Power and Current: 16 W, 0.133 A @ 120 V, 60 Hz

Power and Current: 17 W, 0.082 A @ 208 V, 60 Hz

Power and Current: 17 W, 0.073 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET

IP Rating: IP65, outdoor/wet

Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

Required Accessories

Controller (required): EPIX Drive 2000 IP

Compatible Mounting Options: M12 Bolt/Clamp (rear mounting)

Optional Accessories

ArKaos Media Master Express + KN software
Clamps
Neutrik powerCON cables
Neutrik etherCON cables

What's Included

EPIX Strip IP 50
Square milky filter (installed)
Round milky filter (included in box)
Black stealth filter (included in box)