



Maverick MK2 Wash

A powerful LED wash fixture featuring 12 Osram RGBW LEDs that provides an exceptionally even output, a wide zoom range, and advanced creative options like full pixel mapping and a virtual gobo wheel.

Ideal for touring productions, concerts, and broadcast applications requiring a versatile wash light with powerful aerial effects and precise color control.

- Houses twelve 40W Osram RGBW LEDs for intense, even wash coverage.
- Features an expansive 4.7° to 65.5° zoom for tight beams or broad washes.
- Achieve seamless fades with 16-bit dimming on master and individual colors.
- Provides a user-selectable 7500 K calibrated white for consistent color temperature.
- Supports DMX, Art-Net, sACN, Kling-Net, and W-DMX for total control flexibility.
- Operates silently, making it ideal for broadcast and other noise-sensitive applications.

SPECIFICATIONS

Optical

Light Source: 12 LEDs (quad-color RGBW) 40 W, (2.6 A), 50,000 hours life expectancy

Color Temperature (range): 2800 to 10000 K

Beam Angle: : 4.7° to 37.5°

Field Angle: 7.9° to 55.1°

Cutoff Angle: 9.2° to 65.5°

Zoom Range: 4.7° to 65.5°

Lumens – Source: 8,800

Lumens – Output: 5,900

Illuminance:

Illuminance (7.9°): 19,972 lux @ 5 m

Illuminance (55.1°): 807 lux @ 5 m

PWM Frequency: 600 Hz, 1,200 Hz, 2,000 Hz, 6,000 Hz, 15,000 Hz

Dynamic Effects

Pan and Tilt: 540°/270°

Pan and Tilt Ranges: 180°, 360°, 540° pan/90°, 180°, 270° tilt

Dimmer: Electronic

Shutter/Strobe: Electronic

Zoom: Motorized

Strobe Rate: 0 to 20 Hz

Standalone Color Mixing: No

Color Temperature Presets: Yes

Move-in-Black: Yes

Dim Curves: 4

Construction / Physical

Dimensions: 12.72 x 9.17 x 18.54 in (323 x 233 x 471 mm)

Weight: 32.8 lb (14.8 kg)

Exterior Color: Black

Housing Material: High-impact flame-retardant polymer

Connections

Power Connection: Edison plug to Seetronic Powerkon IP65

Power Input/Output: Seetronic Powerkon IP65

Data Connectors: 3- and 5-pin XLR

Cable Length (power): 5 ft (1.5 m)

Control

Control Protocol: Art-Net, sACN, Kling-Net, DMX, W-DMX, RDM

DMX Channels:

Single Mode: 20, 69, 115

Dual Mode – Function: 8, 20, 26

Dual Mode – Pixel: 36, 48, 60

Art-Net Channels:

Single Mode: 20, 69, 115

Dual Mode – Function: 8, 20, 26

Dual Mode – Pixel: 36, 48, 60

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power Linking: 2 units @ 120 V; 5 units @ 208 V; 5 units @ 230 V

Power and Current: 503 W, 4.08 A @ 120 V, 60 Hz

Power and Current: 506 W, 2.33 A @ 208 V, 60 Hz

Power and Current: 509 W, 2.17 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET, FCC

IP Rating: IP20, dry location

Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN

Safety Cable: SC-07

Ethercon extension cables

IP rated Seetronic Powerkon extensions

DMX cables

What's Included

MK2 Wash

Seetronic Powerkon IP65 power cord

Omega bracket with mounting hardware