

WELL POD 2



A compact, battery-powered PAR wash light offering high output, excellent color rendering, and flexible mounting with a removable split-yoke design.

Ideal for rental inventory and lighting professionals requiring a fast, flexible wash lighting solution for any indoor or outdoor production where quick setup is crucial.

- Features seven RGBWW LEDs for rich colors and high-quality whites from 2800K to 6500K.
- Offers multiple battery runtime selections, delivering up to 18 hours of continuous operation.
- Built with a rugged, IP65-rated housing for reliable performance in any outdoor environment.
- Provides versatile control options including DMX, CRMX, RDM, RF, and mobile app support.
- Sold as a six-unit kit in a road case that charges all fixtures with the lid closed.
- Includes adjustable PWM settings to ensure flicker-free output for on-camera applications.

SPECIFICATIONS

Optical

Light Source: 7 LEDs (RGBWW) 13.2 W, (556 mA), 50,000 hours life expectancy

Color Temperature (range): 2800 to 6500 K

Beam Angle: 11.5°

Field Angle: 21.6°

Cutoff Angle: 36.9°

Lumens: 1797 lm (AC power)

Illuminance: lux 1089 @ 5 m (AC power)

Lumens: 718 lm (OFF battery setting)

Illuminance: 436 lux @ 5 m (OFF battery setting)

Lumens: 834 lm (5-hour battery setting)

Illuminance: 507 lux @ 5 m (5-hour battery setting)

Lumens: 528 lm (8-hour battery setting)

Illuminance: 319 lux @ 5 m (8-hour battery setting)

Lumens: 335 lm (12-hour battery setting)

Illuminance: 202 lux @ 5 m (12-hour battery setting)

Lumens: 214 lm (18-hour battery setting)

Illuminance: 129 lux @ 5 m (18-hour battery setting)

Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 25,000 Hz

Dynamic Effects

Dimmer: Electronic

Shutter/Strobe: Electronic

Strobe Rate: 1 to 30 Hz

Standalone Color Mixing: Yes

Color Temperature Presets: Yes

Dim Modes: 4

Dim Curves: 4

Built-in Automated Programs: Yes

Customizable Programs: No

Recall Custom Programs: No

Construction / Physical

Dimensions: 8.11 x 5.31 x 8.76 in (206 x 138 x 222.5 mm)

Dimensions (w/o bracket): 5.43 x 5.43 x 5.67 in (138 x 138 x 144 mm)

Dimensions case: 32.7 x 19.3 x 15.4 in (832 x 492 x 390mm)

Weight: 7.2 lb (3.3 kg)

Weight (shipping weight): 113.8 lb (51.6 kg)

Exterior Color: Black

Housing Material: Aluminum die-cast

Connections

Power Connection: Edison (local) plug to Seetronic PowerKon IP65

Power Input (fixture and charging case): Seetronic PowerKon IP65

Power Output (fixture and charging case): Seetronic PowerKon IP65

Data Connectors: 5-pin XLR

Cable Length (power): 5 ft (1.5 m)

Software Connection: USB-C

Control

Control Protocol: RDM, CRMX, NFC, RF

DMX Channels: 5, 8, or 12

Modes/Personalities: 3 personalities (5Ch, 8Ch, 12Ch)

Wireless WDMX “G” Compatibility: G4S

Wireless Lumen Radio Compatibility: CRMX

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Single unit:

Power Linking: 34 units @ 120 V

Power Linking: 52 units @ 208 V

Power Linking: 54 units @ 230 V

Power and Current: 43 W, .35 A @ 120 V, 60 Hz

Power and Current: 47 W, .23 A @ 208 V, 60 Hz

Power and Current: 45 W, .22 A @ 230 V, 50 Hz

6 Pack case:

Power Linking: 4 units @ 120 V

Power Linking: 6 units @ 208 V

Power Linking: 6 units @ 230 V

Power and Current: 191 W, 2.75 A @ 120 V, 60 Hz

Power and Current: 185 W, 1.96 A @ 208 V, 60 Hz

Power and Current: 183 W, 1.76 A @ 230 V, 50 Hz

6 Pack case fuse: 4 hours (all fixtures in case)

Battery

Battery type: Lithium Ion

Rechargeable: Yes

Battery Charge Time: 8 hours

Battery Life: 12 hours

Battery Power: 25.9 V, 2.5 Ah

Certifications / Qualifications

Certifications: CE, UKCA, FCC, ROHS

IP Rating: IP65, temporary outdoor/wet use

Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

Optional Accessories

Clamps

WELL POD 2 - 15° Filter Pack

WELL POD 2 60° x 10° Filter Pack

WELL POD 2 White Fixture Cover

PowerKon Extension cables

5 pin DMX Cables

W-DMX Micro T-1 TRX G6

What's Included

(6) WELL POD 2

(1) 6 slot charging case

(6) detachable split yokes

(1) RF controller

(1) QRG