



WELL POD 3

The WELL POD 3 is a versatile, battery-powered wash light that delivers high output and superior color rendering in a flexible PAR fixture design with a removable split yoke. Ideal for indoor or outdoor productions and rental applications where lighting professionals require quick, flexible setup and long battery life.

- Features 19 RGBWW LEDs delivering 3,557 lumens for powerful, high-quality color mixing.
- Offers selectable battery runtimes of up to 18 hours for all-day event reliability.
- Built with a rugged, IP65-rated housing for dependable performance in any weather condition.
- Supports DMX, CRMX, RDM, and RF protocols for maximum control flexibility on any production.
- Ships as a four-fixture kit in a road-ready case with convenient in-case charging.
- Provides adjustable PWM settings to ensure completely flicker-free operation for on-camera use.

SPECIFICATIONS

Optical

Light Source: 19 LEDs (RGBWW), 13.2W, (960mA) 50,000 hours life

Color Temperature (range): 2800 to 6500 K

Beam Angle: 12.7°

Field Angle: 25.4°

Cutoff Angle: 47.2°

Lumens: 3557 lm (AC power)

Illuminance: 1692 lux @ 5 m (AC power)

Lumens: 1994 lm (OFF battery setting)

Illuminance: 946 lux @ 5 m (OFF battery setting)

Lumens: 2177 lm (5-hour battery setting)

Illuminance: 1033 lux @ 5 m (5-hour battery setting)

Lumens: 1379 lm (8-hour battery setting)

Illuminance: 655 lux @ 5 m (8-hour battery setting)

Lumens: 845 lm (12-hour battery setting)

Illuminance: 398 lux @ 5 m (12-hour battery setting)

Lumens: 555 lm (18-hour battery setting)

Illuminance: 261 lux @ 5 m (18-hour battery setting)

Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 25,000 Hz

Dynamic Effects

Dimmer: Electronic

Shutter/Strobe: Electronic

Strobe Rate: 1 to 30 Hz

Standalone Color Mixing: Yes

Color Temperature Presets: Yes

Dim Modes: 4

Dim Curves: 4

Built-in Automated Programs: Yes

Customizable Programs: No

Recall Custom Programs: No

Construction / Physical

Dimensions: 9.76 x 7 x 10.86 in (248 x 178 x 276 mm)

Dimensions (w/o bracket): 9.76 x 7 x 7 in (248 x 178 x 178 mm)

Dimensions case: 27 x 25.6 x 15 in (685 x 650 x 380 mm)

Weight: 11.2 lbs (5.1 kg)

Shipping Weight: 119.7 lb (54.3 kg)

Exterior Color: Black

Housing Material: Aluminum die-cast

Connections

Power Connection: Edison (local) plug to Seetronic Powerkon IP65

Power Input (fixture and charging case): Seetronic Powerkon IP65

Power Output(fixture and charging case): Seetronic Powerkon IP65

Data Connectors: 5-pin XLR

Cable Length (power): 5 ft (1.5 m)

Software Connection: USB-C

Control

Control Protocol: RDM, CRMX, NFC, RF

DMX Channels: 5, 8, or 12

Modes/Personalities: 3 personalities (5Ch, 8Ch, 12Ch)

Wireless WDMX “G” Compatibility: G4S

Wireless Lumen Radio Compatibility: CRMX

Electrical

Single Unit:

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power Linking: 20 units @ 120 V; 34 units @ 208 V; 37 units @ 230 V;

Power and Current: 72 W, 0.60 A @ 120 V, 60 Hz

Power and Current: 70 W, 0.35 A @ 208 V, 60 Hz

Power and Current: 70 W, 0.32 A @ 230 V, 50 Hz

4 Pack Case:

Power Linking: 5 units @ 120 V; 8 units @ 208 V; 9 units @ 230 V;

Power and Current: 135 W, 2.02 A @ 120 V, 60 Hz

Power and Current: 134 W, 1.45 A @ 208 V, 60 Hz

Power and Current: 135 W, 1.33 A @ 230 V, 50 Hz

4 Pack case fuse: T5A, 250V

Battery

Battery type: Lithium Ion

Rechargeable: Yes

Battery Charge Time: 8 hours

Battery Life: 3hr, 5hr, 8hr, 12hr

Battery Power: 25.9V, 6.6 Ah

Certifications / Qualifications

Certifications: CE, UKCA, FCC, ROHS

IP Rating: IP65, temporary outdoor/wet use

Temperature (Ambient): 14 °F to 113 °F (-10 °C to 45 °C)

Optional Accessories

Clamps

15° Lens pack

60°x10° Lens pack

White metal cover

PowerKon Extension cables

5 pin DMX Cables

What's Included

(4) WELL POD 3

(1) Charging case

(4) Omega brackets

(4) Detachable split yokes

(1) RF controller

(1) Quick Reference Guide