



Ovation Rêve E2

RGBACM Ellipsoidal with exceptional color quality and output, featuring the improved “Rêve” engine in a new lightweight carbon-fiber composite housing.

- RGBACM Ellipsoidal with exceptional color quality and output
- Improved “Rêve” engine with updated features and look
- Utilizes existing Ovation lenses and accessories

SPECIFICATIONS

Optical *

Light Source: RGBACM LED Array

** These specifications are still being finalized. Speak to a salesperson for more information.*

Dynamic Effects

Pan and Tilt:

Colors: VCW and CCT presets

Gobos (1): Metal gobo slot & Accessory Slot

Framing Shutters: 4

Construction / Physical

Dimensions: 19.6 x 12.1 x 18.5 in (498 x 307 x 470 mm)

Weight: 13.6 lb (6.2 kg)

IP Rating: IP20

Connections

Power Input: Seetronic Powerkon (powerCON Compatible)

Power Output: Seetronic Powerkon (powerCON Compatible)

Data Connectors: 5-Pin XLR

Control

Control Protocol: DMX, RDM, NFC

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power and Current: 251 W, 2.10 A @ 120 V, 60 Hz

Power and Current: 244 W, 1.19 A @ 208 V, 60 Hz

Power and Current: 243 W, 1.07 A @ 230 V, 50 Hz

Certifications / Qualifications

Compliance: CE, MET, FCC, CB

Optional Accessories

Ovation lenses and accessories

Ovation HD Lens Tubes