

Ovation Rêve P-3 IP



A high-output, IP65-rated LED PAR fixture that delivers multi-color and full-spectrum-white light with exceptional color rendering and versatile beam shaping via four interchangeable lenses.

This powerful instrument is perfectly suited for indoor or outdoor theatrical productions, houses of worship, special events, and rental applications, especially where on-camera performance is critical.

- Delivers linear color temperature presets from 2800 K to 8000 K with high CRI.
- Features a fully IP65-rated housing for dependable, all-weather use in any environment.
- Includes four interchangeable lenses to easily adapt beam angles from narrow spot to wide flood.
- Adjustable Pulse Width Modulation (PWM) ensures flicker-free operation for broadcast and film.
- Offers flexible integration with DMX and RDM control across nine operating personalities.
- An advanced RGBAM LED engine provides full-spectrum color mixing and superior white light.

SPECIFICATIONS

Optical

Light Source: 80 LEDs (10 red, 10 green, 10 blue, 20 amber, 30 mint) 4.4 to 7.8 W, (2.4 A). L70 rating: 55,000 hours under LED manufacturers test conditions (LM-80: 10,000hrs).

Color Temperature (range): 2800 to 8000 K

Color Temperature (at full): 5399 K

Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 25,000 Hz

Narrow Lens:

Beam Angle: 11.9°

Field Angle: 20.8°

Lumens: 10,051

Medium Lens:

Beam Angle: 25.6°

Field Angle: 37.8°

Illuminance: 1,950 lux @ 5 m

Lumens: 10,079

Wide Lens:

Beam Angle: 29.3°

Field Angle: 43.1°

Illuminance: 1,475 lux @ 5 m

Lumens: 9,936

Very Wide Lens:

Beam Angle: 43.5°

Field Angle: 87.9°

Illuminance: 401 lux @ 5 m

Lumens: 8,380

Dynamic Effects

Dimmer: Electronic

Shutter/Strobe: Electronic

Strobe Rate: 0 to 25 Hz

Standalone Color Mixing: Yes

Color Temperature Presets: Yes

Dim Modes: 4

Built-in Automated Programs: Yes

Construction / Physical

Dimensions: 18.82 x 11.81 x 8.27 in (478 x 300 x 210 mm)

Weight: 21.4 lb. (9.8 kg)

Exterior Color: Black

Housing Material: Aluminum diecast

Accessory Holder/Gel Frame Size: 7.5 in (191 mm)

Connections

Power Connection: Edison (Local) plug to Seetronic Powerkon IP65

Power Input: Seetronic Powerkon IP65

Power Output: Seetronic Powerkon IP65

Data Connectors: 5-pin XLR

Cable Length (power): 5 ft (1.5 m)

Software Connection: USB

Control

Control Protocol: DMX, RDM

DMX Channels: 1, 4, 5, 7, 11, 13ch1, 13ch2, 17 or HSV

Modes/Personalities: 9 personalities (1, 4, 5, 7, 11, 13ch1, 13ch2, 17, HSV)

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power Linking: 5 units @ 120 V; 8 units @ 208 V; 9 units @ 230 V;

Power and Current: 274 W, 2.31 A @ 120 V, 60 Hz

Power and Current: 267 W, 1.38 A @ 208 V, 60 Hz

Power and Current: 265 W, 1.25 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET, FCC, UKCA

IP Rating: IP65, outdoor/wet, with pressure equalizing M12 GORE valve

Noise Levels:

Idle: 17.4 dB(A) @ 1 m

Auto: 30.7 dB(A) @ 1 m

On: 31.9 dB(A) @ 1 m

Off: 2.3 dB(A) @ 1 m

Silent: 11.3 dB(A) @ 1 m

Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN

Safety Cable: SC-07

TRUE1 Style Power Extension Cables

5-pin IP65 DMX Cables

RDM2go

USB Jump Drive

Ovation F 7.5" Barndoor V2

What's Included

Ovation Reve P-3 IP

Seetronic Powerkon power cord

Omega bracket with mounting hardware

Narrow, Medium, Wide, Very Wide Lens

Gel Frame