



## Rogue Outcast 3X Wash

An IP65-rated LED wash fixture featuring a fast zoom, nine pixel-mappable zones, and 37 powerful RGBW LEDs that deliver excellent color blending and a strong output. Perfect for a wide range of applications from touring and outdoor festivals to on-camera use, especially in environments demanding durability against the elements.

- Generates a powerful, even field of light from thirty-seven 25 W RGBW LEDs.
- Offers a versatile zoom range from a tight 9.3° beam to an expansive 62.6° wash.
- Built with a rugged yet lightweight aluminum and magnesium alloy IP65-rated housing.
- Ensures flicker-free on-camera operation with selectable PWM and a calibrated white setting.
- Achieves exceptionally smooth fades with 16-bit dimming and six distinct dimming modes.
- Provides flexible programming with four DMX personalities and RDM for remote setup.

### SPECIFICATIONS

#### Optical

**Light Source:** 37 LEDs (quad-color RGBW) 25 W, (1.5 A), L70 rating: 36,000 hours under LED manufacturers test conditions (LM-80: 6,000hrs)

**Color Temperature (range):** 2800 to 10000 K

**Beam Angle:** 9.3° to 33.9°

**Field Angle:** 11.6° to 49.5°

**Cutoff angle:** 13.1° to 62.6°

**Zoom Angle:** 9.3° to 62.6°

**Lumens – Source:** 17,000

**Lumens – Output:** 13,440

#### Illuminance:

Illuminance (9.3°): 18,260 lux @ 5 m

Illuminance (62.6°): 1,556 lux @ 5 m

**Selectable PWM:** 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 15,000 Hz

#### Dynamic Effects

**Pan and Tilt:** 540°/270°

**Pan and Tilt Ranges:** 180°, 360°, 540° Pan/90°, 180°, 230° Tilt.

**Dimmer:** Electronic

**Shutter/Strobe:** Electronic

**Zoom:** Motorized

**Strobe Rate:** 0 to 25 Hz

**Standalone Color Mixing:** Yes

**Color Temperature Presets:** Yes

**Dim Curves:** 4

**Built-in Automated Programs:** Yes

**Customizable Programs:** No

**Recall Custom Programs:** No

#### Construction / Physical

**Dimensions:** 15.59 x 11.73 x 17.20 in (396 x 298 x 437 mm)

**Dimensions (shipping size):** 23.62x 14.17 x 18.70 in (600 x 360 x 475)

**Weight:** 38.2 lb. (17.38kg)

**Exterior Color:** Black

**Housing Material:** High-impact flame-retardant polymer.

#### Connections

**Power Connection:** Edison (local) plug to Seetronic PowerKON IP65

**Power Input:** Seetronic PowerKON IP65

**Power Output:** Seetronic PowerKON IP65

**Data Connectors:** 5-pin XLR

**Cable Length (power):** 5 ft (1.5 m)

#### Control

**Control Protocol:** DMX, RDM

**DMX Channels:** 21, 62, 71, 107

**Modes/Personalities:** 4 personalities

#### Electrical

**Input Voltage:** 100 to 240 VAC, 50/60 Hz (auto-ranging)

**Power Linking:** 2 units @ 120 V; 3 units @ 208 V; 3 units @ 230 V

**Power and Current:** 711 W, 5.98 A @ 120 V, 60 Hz

**Power and Current:** 701 W, 3.40 A @ 208 V, 60 Hz

**Power and Current:** 695 W, 3.07 A @ 230 V, 50 Hz

## Certifications / Qualifications

**Certifications:** CE, MET, FCC, FCC, UKCA

**IP Rating:** IP65, temporary outdoor/wet use

### Noise Levels:

Noise Level (Idle): 22.8 dB(A) @ 1 m

Noise Level (Auto): 47.5 dB(A) @ 1 m

Noise Level (Eco): 34.3 dB(A) @ 1 m

Noise Level (Full): 47.3 dB(A) @ 1 m

Noise Level (Max): 37.2 dB(A) @ 1 m

**Temperature (Ambient):** -4 °F to 113 °F (-20 °C to 45 °C)

## Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN

Safety Cable: SC-08

Seetronic IP65 PowerKon cables

DMX Cables

UPLOAD 08 software uploader

## What's Included

Rogue Outcast 3X Wash

Seetronic PowerKon IP65 power cord

(2) 140D Omega brackets with mounting hardware