



Rogue R1 BeamWash

A compact and versatile moving head that projects both a punchy beam and a wide wash, featuring seven 40W RGBW LEDs and an expansive zoom range for seamless transitions between tight aerial effects and broad coverage.

Its lightweight design and flicker-free camera operation make it an excellent choice for mobile productions, broadcast studios, and event stages where space and versatility are critical.

- Houses a custom-designed optical system for superior color blending and sharp beam effects.
- Offers a motorized zoom from a tight 3.4° beam to a wide 67.7° wash.
- Delivers exceptionally fast and fluid pan and tilt movement for dynamic lighting displays.
- Includes a user-selectable calibrated white at 7500 K and a tungsten emulation mode.
- Features RDM for remote addressing and flexible DMX channel profiles for versatile programming.
- Provides selectable PWM settings and 16-bit dimming for smooth, flicker-free camera use.

SPECIFICATIONS

Optical

Light Source: 7 LEDs (quad-color RGBW) 40 W, (980 mA), 50,000 hours life expectancy

Color Temperature (range): 2800 to 10000 K

Beam Angle: 4° to 37.8°

Field Angle: 5° to 58.2°

Cutoff Angle: 5.5° to 67.7°

Zoom Range: 3.4° to 67.7°

Lumens – Source: 5,400

Lumens – Output: 3,967 Wide

Illuminance:

Illuminance (5°): 13,939 lux @ 5 m

Illuminance (55°): 383 lux @ 5 m

Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 15,000 Hz

Dynamic Effects

Pan and Tilt: 540°/230°

Pan and Tilt Ranges: 180°, 360°, 540° pan/90°, 180°, 230° tilt

Dimmer: Electronic

Shutter/Strobe: Electronic

Zoom: Motorized

Strobe Rate: 0 to 20 Hz

Standalone Color Mixing: Yes

Color Temperature Presets: Yes

Dim Curves: 4

Built-in Automated Programs: Yes

Customizable Programs: No

Recall Custom Programs: No

Construction / Physical

Dimensions: 8.42 x 6.29 x 14.52 in (214 x 160 x 369 mm)

Weight: 11.8 lb (5.35 kg)

Exterior Color: Black

Housing Material: High-impact flame-retardant polymer

Connections

Power Connection: Edison (Local) plug to Neutrik® powerCON®

Power Input: Neutrik® powerCON®

Power Output: Neutrik® powerCON®

Data Connectors: 5-pin XLR

Cable Length (power): 5 ft (1.5 m)

Control

Control Protocol: DMX

DMX Channels: 14, 15, 19 or 21

Modes/Personalities: 4 personalities (14, 15, 19, 21)

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power Linking: 5 units @ 120 V; 8 units @ 208 V; 9 units @ 230 V

Power and Current: 285 W, 2.38 A @ 120 V, 60 Hz

Power and Current: 284 W, 1.37 A @ 208 V, 60 Hz

Power and Current: 284 W, 1.23 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET

IP Rating: IP20, dry location

Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN

Safety Cable: SC-07

Neutrik® powerCON® cables

DMX Cables

Flight Case: CP6CASER1W

UPLOAD 08 software uploader

What's Included

Rogue R1 BeamWash

Neutrik® powerCON® power cord

Omega bracket with mounting hardware