



Rogue R3 Beam

The Rogue R3 Beam is a powerful 300W moving head fixture that produces an intense, ultra-narrow 0.8° beam, featuring a 14-color wheel, a 17-gobo wheel, and dual overlapping 8 and 24-facet prisms for dynamic aerial effects.

Perfect for large-scale concerts, festivals, and productions requiring powerful, long-throw aerial beam effects that make a significant visual impact.

- Delivers an intense 208,000 lux at 15 meters from a 300W Ushio NSL lamp.
- Offers a tight 0.8° beam angle with motorized frost and focus for versatile beam shaping.
- Features individually controllable and stackable 8-facet and 24-facet prisms for complex aerial looks.
- Includes a 14-color wheel and 17-gobo wheel, both with variable-speed continuous scroll.
- Built for dynamic aerial effects with fast, precise 540° pan and 270° tilt movement.
- Supports DMX and RDM control for simplified setup and remote troubleshooting.

SPECIFICATIONS

Optical

Light Source: 300W NSL Ushio lamp, 8000 K (color temp), 8,000 hours life expectancy

Color Temperature (at full): 7657 K

CRI: 80.8

Front Lens Diameter: 153 mm

Beam Angle: 0.8°

Field Angle: 1.6°

Cutoff Angle: 2°

Lumens – Output: 30,878

Illuminance (total): 208,006 lux @ 15 m

Connections

Power Connection: Edison (Local) plug to Neutrik

Power Input: Neutrik powerCON

Power Output: Neutrik® powerCON®

Data Connectors: 3- and 5-pin XLR

Cable Length (power): 5 ft (1.5 m)

Control

Control Protocol: DMX, RDM

DMX Channels: 16 or 19

Modes/Personalities: 2 personalities (16, 19)

Dynamic Effects

Pan and Tilt: 540°/270°

Pan and Tilt Ranges: 180°, 360°, 540° pan/90°, 180°, 270° tilt

Colors: 14 + white, split colors, continuous scroll at variable speeds

Gobos: 17 + open (17 metal), continuous scroll at variable speeds

Dimmer: Motorized

Shutter/Strobe: Motorized

Focus: Motorized

Frost: Motorized

Prism: 8 facets, motorized, rotating

Prism: 24 facets, motorized, rotating

Strobe Rate: 0 to 15 Hz

Move in Black: Yes

Construction / Physical

Dimensions: 12.79 x 8.66 x 21.65 in (325 x 220 x 550 mm)

Weight: 34.4 lb (15.6kg)

Exterior Color: Black

Housing Material: High-impact flame-retardant polymer

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power and Current: 422 W, 4.20 A @ 100 V, 60 Hz

Power and Current: 418 W, 3.55 A @ 120 V, 60 Hz

Power and Current: 411 W, 1.98 A @ 208 V, 60 Hz

Power and Current: 411 W, 1.78 A @ 230 V, 50 Hz

Power and Current: 406 W, 1.68 A @ 240 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET, UKCA

IP Rating: IP20, dry location

Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

Noise Levels:

Noise Level (Idle): 41.6 dB(A) level @ 1 m

Noise Level (Auto): 37.9 dB(A) level @ 1 m

Noise Level (Max): 38.4 dB(A) level @ 1 m

Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN
Safety Cable: SC-07
DMX cables
Flight Case: #CP2CASER2XR3SPOT
UPLOAD 08 software uploader

What's Included

Rogue R3 Beam
Neutrik powerCON power cord
2 Omega brackets with mounting hardware