



Rogue R3E Spot

A compact and lightweight 350W LED moving yoke spot that provides a wide zoom range and a complete effects package, including dual gobo and color wheels, a rotating prism, motorized iris, and frost.

Perfect for rental houses, touring productions, and installations in clubs or theaters seeking a versatile, feature-rich spot fixture that can integrate with existing lighting rigs.

- Features selectable LED output to match the brightness of legacy Rogue R1X Spot fixtures.
- Provides a wide zoom range of 8.4° to 42.8° for flexible beam and wash applications.
- Creates seamless gobo morphing effects using one rotating and one static gobo wheel.
- Offers an expanded color palette with two wheels, featuring eight colors, white, and split-color ability.
- Supports DMX and RDM protocols with 3-pin and 5-pin connectors for flexible system integration.
- Ensures flicker-free on-camera performance with selectable Pulse Width Modulation (PWM) settings.

SPECIFICATIONS

Optical

Light Source: 1LEDs (CW) 350 W, (5 A), 8527 K, 50,000 hours life expectancy.

Color Temperature (at full): 8527 K

Front lens diameter: 90mm

CRI: 68.2

Beam Angle: 8.4° to 33°

Field Angle: 10.1° to 39.3°

Cutoff Angle: 11.5° to 42.8°

Zoom Range: 8.4° to 42.8°

Lumens – Source: 24,500

Lumens – Output: 15,705

Illuminance:

7°: 35,405 lux @ 5 m

42.8°: 2,492 lux @ 5 m

Selectable PWM: 600 Hz, 1,200 Hz, 2000 Hz, 4000 Hz, 6,000 Hz, 15,000 Hz

Dynamic Effects

Pan and Tilt: 540°/270°

Pan and Tilt Ranges: 180°, 360°, 540° pan/90°, 180°, 270° tilt

Colors (1): 8 + white, split colors, continuous scroll at variable speeds

Colors (2): 8 + white, split colors, continuous scroll at variable speeds

Gobos (1): 7 + open (7 metal), rotating, interchangeable, indexing, slot-n-lock, continuous scroll at variable speeds

Gobos (2): 8 + open (8 metal), continuous scroll at variable speeds

Gobo Size:

Gobo Wheel 1 (rotating): size: 20 mm (outside), 16 mm (image), 1.5 mm (max. thickness)

Gobo Wheel 2 (static): size: 24 mm (outside), 16 mm (image), 0.6 (max. thickness)

Dimmer: Electronic

Shutter/Strobe: Electronic

Zoom: Motorized

Focus: Motorized

Frost: Motorized

Iris: Motorized

Prism: 3 Facets, motorized, rotating

Strobe Rate: 0 to 25 Hz

Move in Black: Yes

Construction / Physical

Dimensions: 13.77 x 9.44 x 23.03 in (350 x 240 x 585 mm)

Weight: 34 lb (15.4 kg)

Exterior Color: Black

Housing Material: Aluminum die-cast, High-impact flame-retardant polymer, Steel

Software update: USB-C

Connections

Power Connection: Edison (local) plug to Seetronic Powerkon IP65

Power Input: Seetronic Powerkon IP65

Power Output: Seetronic Powerkon IP65

Data Connectors: 3- and 5-pin XLR

Cable Length (power): 5 ft (1.5 m)

Software Connection: USB-C

Control

Control Protocol: DMX, RDM

DMX Channels: 19 or 25

Modes/Personalities: 2 personalities (19, 25)

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power Linking: 4 units @ 120 V; 8 units @ 208 V; 8 units @ 230 V; 9 units @ 240 V

Power and Current: 535 W, 4.541 A @ 120 V, 60

Power and Current: 522 W, 2.576 A @ 208 V, 60 Hz

Power and Current: 523 W, 2.345 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET, FCC, UKCA

IP Rating: IP20, dry location

Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

Noise Levels:

Idle: 4.1 dB(A) @ 1 m

Max: 35.0 dB(A) @ 1 m

Auto: 33.3 dB(A) @ 1 m

Eco: 31.2 dB(A) @ 1 m

Full: 40.2 dB(A) @ 1 m

Optional Accessories

Clamps

Neutrik powerCON cables

Neutrik etherCON cables

DMX Cables

Flight Cases

What's Included

Rogue R3E Spot

Seetronic PowerKon power cord

2 140D Omega brackets with mounting hardware