



WELL STX 360

A large, battery-operated, and IP65-rated LED tube that delivers 360 degrees of bright, high-CRI, pixel-mappable RGBWW light with versatile wireless control. Ideal for creating dynamic set pieces, vibrant accent lighting, and on-camera eye-candy for events, broadcast, and architectural applications where wireless freedom is essential.

- Delivers excellent on-camera performance with 512 high-CRI RGBWW LEDs.
- Offers detailed pixel-mapping effects with 16 individually controllable zones per tube.
- Built with a rugged, IP65-rated housing for reliable performance in any weather condition.
- Provides selectable runtimes of 3, 5, 8, and 12 hours to optimize battery performance.
- Supports versatile wireless operation through an integrated W-DMX receiver.
- Ships as a complete tour-ready kit with four fixtures in a charging flight case.

SPECIFICATIONS

Optical

Light Source: 512 LEDs (256 RGB / 256 WW) SMD 5050, 50,000 hours life expectancy

Color Temperature (range): 2800 to 8000 K

Color Temperature (at full): 9670 K

CRI: 91.9 @ 4000 K

Beam Angle: 360°

Field Angle: 360°

Illuminance (total): 5 lux @ 5 m – 3 hr run time

Lumens – Output: 1,718 lm – 3 hr run time

PWM Frequency: Scrambled PWM

Dynamic Effects

Dimmer: Electronic

Shutter/Strobe: Electronic

Strobe Rate: 0 to 28 Hz

Standalone Color Mixing: Yes

Color Temperature Presets: Yes

Dim Modes: 4

Built-in Automated Programs: Yes

Construction / Physical

Dimensions: 59.09 x 2.75 x 2.75 in (1501 x 70 x 70 mm)

Dimensions (charging case): 69.8 x 19.5 x 6.4 in (1773 x 495 x 163 mm)

Weight: 9 lb (4.1 kg)

Weight (charging case): 85 lb (38.6 kg)

Threaded Bolt: M12-1.75

Exterior Color: Black

Housing Material: Aluminum alloy, Plastic

Connections

Power Connection:

Single Charger: Edison (Local) plug to Seetronic Powerkon IP65

Charging Case: Edison (Local) plug to Seetronic Powerkon IP65

Power Input:

Single Charger: Seetronic Powerkon IP65

Charging Case: Seetronic Powerkon IP65

Power Output (charging case): Seetronic Powerkon IP65

Cable Length (Power):

Single Charger: 5 ft (1.5 m)

Charging Case: 5 ft (1.5 m)

Control

Control Protocol: W-DMX

DMX Channels: 4, 15, 64 or 67

Modes/Personalities: 4 personalities

Electrical

Input Voltage:

Charging Case: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Single Charger: 24 VDC, 2.5 A, 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power Linking (charging case): 8 units @ 100 V; 10 units @ 120 V; 10 units @ 208 V; 11 units @ 230 V; 12 units @ 230 V

Power and Current:

Single Charger: 41 W, 0.403 A @ 100 V, 60 Hz

Charging Case: 164 W, 1.612A @ 100 V, 60 Hz

Single Charger: 40 W, 0.331 A @ 120 V, 60 Hz

Charging Case: 160 W, 1.324 A @ 120 V, 60 Hz

Single Charger: 66 W, 0.315 A @ 208 V, 60 Hz

Charging Case: 264 W, 1.260 A @ 208V, 60 Hz

Single Charger: 67 W, 0.291 A @ 230 V, 50 Hz

Charging Case: 268 W, 1.188 A @ 230 V, 50 Hz

Single Charger: 67 W, 0.281 A @ 240 V, 50 Hz

Charging Case: 268 W, 1.124 A @ 240 V, 50 Hz

Resting (Single Charger): 3 W, 0.035 A @ 100 V, 60 Hz

Resting (Charging Case): 12 W, 0.140 A @ 100 V, 60 Hz

Resting (Single Charger): 4 W, 0.036 A @ 120 V, 60 Hz

Resting (Charging Case): 16 W, 0.144 A @ 120 V, 60 Hz

Resting (Single Charger): 9 W, 0.043 A @ 208 V, 60 Hz

Resting (Charging Case): 36 W, 0.172 A @ 208 V, 60 Hz

Resting (Single Charger): 9 W, 0.041 A @ 230 V, 50 Hz

Resting (Charging Case): 36 W, 0.164 A @ 230 V, 50 Hz

Resting (Single Charger): 10 W, 0.042 A @ 240 V, 50 Hz

Resting (Charging Case): 40 W, 0.168 A @ 240 V, 50 Hz

Battery

Battery type: Lithium Ion

Quantity of cells: 5 cells

Rechargeable: Yes

Watt Hours: 185.9 Wh

Battery Charge Time: 4 hours

Battery Life: 3,5,8,12 hours

Battery Power: 18.5 V, 10.05 Ah

Certifications / Qualifications

Certifications: CE, FCC

IP Rating: IP65, for temporary outdoor use

Temperatures:

Startup: -4 °F to 113 °F (-20 °C to 45 °C)

Operating: -22 °F to 113 °F (-30 °C to 45 °C)

Optional Accessories

Safety Cable: SC-07

IP Rated Seetronic® Powerkon Extensions

What's Included

(4) WELL STX 360

True 1 style power cord with Edison plug (EU bare end)

Charging flight case

(4) tripod stands

(4) hanging eye bolts

(1) IR Remote

Quick Reference Guide