

Rogue Outcast 2 Beam



A lightweight, IP65-rated moving head beam fixture that harnesses a powerful 300W lamp to project an intensely bright, tight beam with multifaceted aerial looks from split colors, gobos, and rotating prisms.

Suited for both indoor and outdoor productions, including tours, festivals, and large-scale events that demand a powerful, weather-resistant fixture for creating cutting aerial beam effects.

- Features a 300W Ushio lamp projecting a razor-sharp 0.8° beam for intense, focused aerial effects.
- Built with a lightweight, IP65-rated alloy housing for reliable performance in any weather condition.
- Offers independently controlled and layerable 5-facet linear and 8-facet round prisms for dynamic visuals.
- Expands creative options with a 17-pattern static gobo wheel and a 14-color wheel for split-color effects.
- Includes a frost filter to create an even light distribution for versatile soft-edged wash looks.
- Supports both DMX and RDM protocols for comprehensive remote control and fixture management.

SPECIFICATIONS

Optical

Light Source: 300W NSL Ushio lamp, 8000 K (color temp), 8,000 hours life expectancy

Color Temperature (at full): 7353 K

Front lens diameter: 160 mm

CRI: 75.5

Beam Angle: 0.8°

Field Angle: 1.6°

Cutoff Angle: 2°

Lumens – Output: 29,130

Illuminance (total): 204,855 lux @ 15 m

Construction / Physical

Dimensions: 14.41 x 9.61 x 22.6 in (366 x 244 x 574 mm)

Weight: 45.19 lb (20.5 kg)

Exterior Color: Black

Housing Material: Aluminum/Magnesium diecast

Connections

Power Connection: Edison plug to Seetronic Powerkon IP65

Power Input: Seetronic Powerkon IP65

Data Connectors: 5-pin IP rated

Cable Length (power): 5 ft (1.5 m)

Dynamic Effects

Pan and Tilt: 540°/260°

Pan and Tilt Ranges: 540°, 360°, 180° pan/260°, 180°, 90° tilt

Colors: 14 + white, split colors, continuous scroll at variable speeds

Gobos: 17 + open (17 metal), 17 static, continuous scroll at variable speeds; size: 106 mm (outside), 6 mm (image), 0.6 – 0.8 mm (max. thickness)

Dimmer: Electronic

Shutter/Strobe: Motorized

Focus: Motorized

Frost: Motorized

Prism:

Detail: 5 Facets, motorized, rotating

Detail 2: 8 Facets, motorized, rotating

Move-in-Black: Yes

Control

Control Protocol: DMX, RDM

DMX Channels: 16 or 18

Modes/Personalities: 2 personalities (16, 18)

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power and Current: 413 W, 3.51 A @ 120 V, 60 Hz

Power and Current: 403 W, 2.01 A @ 208 V, 60 Hz

Power and Current: 404 W, 1.82 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET, UKCA

IP Rating: IP65, temporary outdoor/ wet, with pressure equalizing M12 GORE valve

Temperature (Ambient): -14 °F to 113 °F (-10 °C to 45 °C)

Maximum Exterior Surface Temperature (Tc): 80° C / 176° F

Maximum Ambient Temperature (Ta): 45° C / 113° F

Optional Accessories

Clamps

IP65 5 pin DMX Cables

IP65 PowerKon Extension cables

Flight Case

What's Included

Rogue Outcast 2 Beam

Seetronic Powerkon IP65 power cord

(2) Omega brackets with mounting hardware