



Rogue R2X Wash VW

Rogue R2X Wash VW is a versatile wash fixture that produces a full spectrum of white light from 2600 to 6075 K using 19 LEDs, offering five zones of pixel-mapping control and a wide 8.2° to 63° zoom.

Ideal for broadcast and exhibition markets, this unit excels in any application requiring precise control over a wide range of white light temperatures for full area coverage.

- Houses nineteen powerful 25-watt variable white LEDs for brilliant, high-output illumination.
- Features a unique lens design for superior light blending and a smooth, even wash.
- Provides five zones of independent LED control for creating compelling pixel-mapping effects.
- Achieves exceptionally smooth fades with 16-bit dimming and six selectable dimming curves.
- Supports DMX and RDM protocols for versatile programming and remote fixture management.
- Power link up to 8 units at 230 V to simplify cabling and setup.

SPECIFICATIONS

Optical

Light Source: 19 LEDs (CW and WW) 25 W, (1.5 A), 50,000 hours life expectancy

Color Temperature (range): 2600 to 6075 K

Beam Angle: 8° to 34.4°

Field Angle: 11.3° to 50.4°

Cutoff Angle: 17.1° to 63°

Zoom Range: 8.2° to 63°

Lumens – Source: 15,700 lm

Lumens – Output: 10,918 lm

Illuminance:

Illuminance (11.3°): 14,499 lux @ 5 m

Illuminance (50.4°): 1,266 lux @ 5 m

Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 15,000 Hz

Dynamic Effects

Pan and Tilt: 540°/230°

Pan and Tilt Ranges: 180°, 360°, 540° pan/90°, 180°, 230° tilt

Dimmer: Electronic

Shutter/Strobe: Electronic

Zoom: Motorized

Strobe Rate: 0 to 20 Hz

Standalone Color Temperature Mixing: Yes

Color Temperature Presets: Yes

Dim Curves: 4

Built-in Automated Programs: Yes

Customizable Programs: No

Recall Custom Programs: No

Construction / Physical

Dimensions: 8.58 x 12.05 x 15.67 in (218 x 306 x 398 mm)

Weight: 22.8 lb (10.3 kg)

Exterior Color: Black

Housing Material: High-impact flame-retardant polymer

Connections

Power Connection: Edison (Local) plug to Neutrik® powerCON®

Power Input: Neutrik® powerCON®

Power Output: Neutrik® powerCON®

Data Connectors: 3- and 5-pin XLR

Cable Length (power): 5 ft (1.5 m)

Control

Control Protocol: DMX, RDM

DMX Channels: 15, 18, 23, 34 or 36

Modes/Personalities: 7 personalities (15CH, 18CH, 23CH, 23CH MS, 34CH, 36CH or 36CH MS)

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power Linking: 4 units @ 120 V; 7 units @ 208 V; 8 units @ 230 V

Power and Current: 336 W, 2.825 A @ 120 V, 60 Hz

Power and Current: 335 W, 1.620 A @ 208 V, 60 Hz

Power and Current: 339 W, 1.467 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET, FCC, UKCA

IP Rating: IP20, dry location

Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN

Safety Cable: SC-08

Neutrik® powerCON® cables

DMX Cables

Flight Case: CP6CASER2W

UPLOAD 08 software uploader

What's Included

Rogue R2X Wash VW

Neutrik® powerCON® power cord

Omega bracket with mounting hardware