

STRIKE Array 1

The STRIKE Array 1 is an IP65-rated audience blinder with intense, warm white LEDs in independently focusable, interlocking pods that provide scalable configurations and tungsten-emulating Red Shift dimming.

With its high CRI and variable PWM, this modular fixture is ideal for broadcast, touring, festivals, and any large-scale indoor or outdoor event requiring powerful and versatile audience lighting.



- Simplifies setup with a remote driver that automatically addresses up to eight connected pods.
- Mount individual pods with an included yoke or interlock them for scalable array designs.
- Delivers a broadcast-ready 2700 K output with a high CRI of 83.9.
- Provides exceptionally smooth 18-bit dimming curves for seamless fades and transitions.
- Allows precise directional control with manual pan and tilt adjustment on each pod.
- Supports DMX, RDM, ArtNet, and sACN for flexible and professional control integration.

SPECIFICATIONS

Optical	Construction / Physical
Light Source (Single Pod): 48 LED (WW) 1.33 W, (1.1 A), 2700 K, 50,000 hours life expectancy	Dimensions: 8.19 x 8.62 x 4.57 in (208 x 219 x 116 mm) (Single Unit with Bracket)
Light Source (Single Pod): 5 LED (Amber) 1.92 W, (.770 A), 50,000 hours life expectancy	Dimensions: 7.48 x 7.48 x 4.57 in (190 x 190 x 116 mm) (Single Unit with Frame)
Color Temperature (at full): 2657 K	Dimensions: 10.87 x 9.06 x 4.57 in (276 x 230 x 116 mm) (Single Unit with Frame and Bracket)
CRI: 83.9	Dimensions: 7.375 x 4.00 x 7.375 in (186.87 x 101.6 x 186.87 mm) (Control Box)
Beam Angle: 62.8°	Weight: 3.2 lbs (1.5 kg) (Single Unit with Bracket)
Field Angle: 104.5°	Weight: 6.6 lbs (3.0 kg) (Single Unit with Frame)
Lumens (Single Pod): 4,353 lm @ 5 m	Weight: 7.6 lbs (3.5 kg) (Single Unit with Frame and Bracket)
Illuminance (total) (Single Pod): 153 lux @ 5 m	Weight: 6.4 lbs (2.9 kg) (Control Box)
Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 25,000 Hz	Exterior Color: Black
	Housing Material: Aluminum die-cast
Dynamic Effects	Connections
Dimmer: Electronic	Power Connection: Edison (Local) plug to Seetronic Powerkon IP65
Strobe Rate: 0 to 25 Hz	Power Input: Seetronic Powerkon IP65
Dim Modes: 4	Power Output: Seetronic Powerkon IP65
Built-in Automated Programs: Yes	Device Outputs (4): 4-pin XLR
	Data Connectors: 5-pin IP65 XLR, Seetronic Etherkon IP65
	Software Connection: USB
	Cable Length (power): 5 ft (1.5 m)
	Total max. cable length (shielded cables) between Driver and last Head: 147 ft (45 m)

Control

Control Protocol: DMX, RDM, ArtNet, sACN

DMX Channels: 1,2,5,4P-5CH,4P-14CH,4P-23CH,4P-26CH,8P-9CH,8P-26CH,8P-43,8P-46CH

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power and Current (4 PODS): 253 W, 2.13 A @ 120 V, 60 Hz

Power and Current (4 PODS): 248 W, 1.21 A @ 208 V, 60 Hz

Power and Current (4 PODS): 248 W, 1.09 A @ 230 V, 50 Hz

Power Linking: 2 units @ 120 V; 5 units @ 208 V; 5 units @ 230 V

Power Linking: 5 units @ 120 V; 9 units @ 208 V; 11 units @ 230 V

Power and Current (8 PODS): 509 W, 4.22 A @ 120 V, 60 Hz

Power and Current (8 PODS): 494 W, 2.38 A @ 208 V, 60 Hz

Power and Current (8 PODS): 490 W, 2.14 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET, FCC

IP Rating: IP65, temporary outdoor/wet use, with pressure equalizing M6 GORE valve

Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN

Safety Cable: SC-07

IP Rated Seetronic® Powerkon Extensions

IP Rated DMX cables

IP Rated EtherCon Cables

UPLOAD 03 software uploader

What's Included

4pc Strike Array 1, mounted in the Square Frame with Yokes

4pc linking cables (1m)

1pc Seetronic Powerkon IP65

1pc driver

4pc "head only yokes"

5pc Omega Bracket